

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFIER	Celatom® Perlite unexpanded (all grades)
CHEMICAL NAME	Sodium Potassium Aluminum Silicate
CHEMICAL FAMILY	Silicate
MATERIAL USE	Functional additive, filter aid
RESTRICTION ON USE	None Known
MANUFACTURER	EP Minerals, LLC., 9785 Gateway Dr., Reno, NV 89521
TELEPHONE NO.	(775) 824 7600 (Monday – Friday 8:00 am PST – 5:00 pm PST)
EMERGENCY TELEPHONE NO.	(775) 824 7600 (Monday – Friday 8:00 am PST – 5:00 pm PST)
SDS DATE OF PREPARATION	February 3, 2022

Initial Supplier Identifier
Données relatives au fournisseur

Univar Solutions Canada Ltd.

64 Arrow Road
North York, ON M9M 2L9
Telephone: 1-866-686-4827

SECTION 2: HAZARDS IDENTIFICATION

OSHA GHS HAZARD CLASSIFICATION	Not classified as hazardous
HAZARDS NOT OTHERWISE CLASSIFIED	None
LABEL ELEMENTS	No GHS labeling required

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT IDENTIFICATION	APPROXIMATE CONCENTRATION (%)	C.A.S. NUMBERS	EINECS
Perlite, unexpanded	100%	130885-09-5	Not Assigned

SECTION 4: FIRST AID MEASURES

EYE	Flush eyes with generous quantities of water or eye rinse solution. Consult physician if irritation persists.
SKIN	Use moisture renewing lotions if dryness occurs.
INGESTION	Drink generous amounts of water to reduce bulk and drying effects.
INHALATION	Remove to fresh air. Blow nose to evacuate dust.
Most important symptoms/effects, acute and delayed	Dust may cause abrasive irritation to eyes. Prolonged skin contact may cause dryness. Dust may cause nose, throat and upper respiratory tract irritation. Prolonged inhalation of high concentration of dust may cause lung effects.
Indication of immediate medical attention and special treatment, if necessary	Immediate medical attention is not normally required. If dust irritates the eyes, seek medical attention.

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA	Not applicable, the material is not combustible.
SPECIFIC HAZARDS ARISING FROM THE CHEMICAL	Not applicable, the material is not combustible.
SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS	Not applicable, the material is not combustible.

MATERIAL NAME	Celatom® Perlite unexpanded (all grades)	Page 2 of 4
---------------	--	-------------

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS	If dust is present, use respirator fitted with particulate filter as specified in Section 8. Protect eyes with goggles.
ENVIRONMENTAL PRECAUTIONS	This material is not a significant environmental concern.
METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP	Vacuum clean spillage, wet sweep or wash away. Avoid creating dust. Place in a container for use or disposal.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING	Minimize dust generation. Avoid contact with eyes. Avoid breathing dust. Repair or dispose of broken bags. Observe all label precautions and warnings.
CONDITIONS FOR SAFE STORAGE	Store in a dry place to maintain packaging integrity and product quality. Do not store near hydrofluoric acid or strongly basic solutions.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES:				
Component	OSHA PEL	ACGIH TLV	MSHA PEL	NIOSH REL
Perlite, unexpanded	5 mg/m ³ (respirable dust) 15 mg/m ³ (total dust)	None Established	30 mppcf	5 mg/m ³ (respirable dust) 10 mg/m ³ (total dust)
ENGINEERING CONTROLS	Use general or local exhaust ventilation to control dust within recommended exposure limits. Refer to ACGIH publication "Industrial Ventilation" or similar publications for design of ventilation systems.			
PERSONAL PROTECTIVE EQUIPMENT:				
EYE / FACE PROTECTION	Goggles to protect from dust			
SKIN PROTECTION	No special equipment is needed.			
RESPIRATORY PROTECTION	Respirators fitted with filters certified to standard 42CFR84 under series N95 should be worn when dust is present. If the dust concentration is less than ten (10) times the Permissible Exposure Limit (PEL) use a quarter or half-mask respirator with a N95 dust filter or a single use dust mask rated N95. If dust concentration is greater than ten (10) times and less than fifty (50) times the PEL, a full-face piece respirator fitted with replaceable N95 filters is recommended. If dust concentration is greater than fifty (50) and less than two hundred (200) times the PEL use a power air-purifying (positive pressure) respirator with a replaceable N95 filter. If dust concentration is greater than two hundred (200) times the PEL use a type C, supplied air respirator (continuous flow, positive pressure), with full face piece, hood or helmet.			
GENERAL HYGIENE	Avoid breathing dust. Avoid contact with eyes. Wash hands after handling and before eating or drinking.			

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE, COLOR	White to off white powder	ODOR	Odorless
PHYSICAL STATE	Solid	ODOR THRESHOLD	Not applicable
VAPOR PRESSURE	Not applicable	VAPOR DENSITY	Not applicable
BOILING POINT	Not applicable	MELTING POINT	> 800° C
FLASH POINT	Not applicable	pH (10% SUSPENSION)	7
FLAMMABILITY LIMITS	Not applicable	EVAPORATION RATE	Not applicable
DECOMPOSITION TEMPERATURE	> 800° C	SPEC. GRAVITY / RELATIVE DENSITY	2.3
AUTOIGNITION TEMPERATURE	Not applicable	PARTITION COEFFICIENT – n-OCTANOL/WATER	Not applicable
FLAMMABILITY (solid/gas)	Not applicable	SOLUBILITY – WATER	< 1%
		VISCOSITY	Not applicable

MATERIAL NAME	Celatom® Perlite unexpanded (all grades)	Page 3 of 4
SECTION 10: STABILITY AND REACTIVITY		
REACTIVITY	Material is not reactive.	
CHEMICAL STABILITY	Material is stable.	
POSSIBILITY OF HAZARDOUS REACTIONS	Material is not reactive.	
CONDITIONS TO AVOID	Not applicable	
INCOMPATIBLE MATERIALS	Products containing silica may react violently with hydrofluoric acid and strongly basic solutions.	
HAZARDOUS DECOMPOSITION PRODUCTS	Not applicable	
SECTION 11: TOXICOLOGICAL INFORMATION		
POTENTIAL HEALTH EFFECTS	See below and Section 11 for additional information	
Likely Routes of Exposure	See below	
EYE	May cause irritation (tear formation and redness) if dust gets in eyes.	
SKIN	Not absorbed by the skin, but may cause dryness if prolonged exposure.	
INGESTION	Ingestion of small to moderate quantities is not considered harmful, but may cause irritation of the mouth, throat and stomach.	
INHALATION	Acute inhalation can cause dryness of the nasal passage and lung congestion, coughing and general throat irritation. Chronic inhalation of dust should be avoided.	
CHRONIC EFFECTS	Chronic inhalation of dust in excess of the Permissible Exposure Limit (PEL) established by OSHA over a rolonged number of years may cause lung changes.	
CARCINOGENICITY	Analyses of these products by X-ray diffraction have not identified any phases of crystalline silica to be present above the detection limit (0.05%).	
NTP	Perlite is not classified as a carcinogen.	
IARC	Perlite is not classified as a carcinogen.	
NUMERICAL MEASURES OF TOXICITY	LD50 oral mouse 12,960 mg/kg	
CORROSIVENESS, SENSITIZATION, IRRITANCY	Not applicable	
REPRODUCTIVE TOXICITY	Not available	
TERATOGENICITY, MUTAGENICITY	Not available	
SECTION 12: ECOLOGICAL INFORMATION		
ECOTOXICITY:	These products have no demonstrated toxicity in regards to aquatic or terrestrial life.	
PERSISTENCE AND DEGRADABILITY	Non-biodegradable, inert.	
BIOACCUMULATIVE POTENTIAL	Little potential for bioaccumulation	
MOBILITY IN SOIL	No mobility	
OTHER ADVERSE EFFECTS	None known	
SECTION 13: DISPOSAL CONSIDERATIONS		
WASTE DISPOSAL	If this material as supplied becomes a waste, use solid waste disposal common to landfill type operations or in slurry to sumps. Not considered a hazardous waste under RCRA (40CFR Part 261).	
PACKAGING DISPOSAL	Dispose of in accordance with applicable laws and regulations, typically solid waste disposal common to landfill type operations.	

MATERIAL NAME	Celatom® Perlite unexpanded (all grades)		Page 3 of 4								
SECTION 14: TRANSPORT INFORMATION											
BASIC SHIPPING INFORMATION	DOT shipping classification 55 (no restrictions). Technical name is "Perlite".										
ADDITIONAL INFORMATION	No special requirements or placarding necessary.										
SECTION 15: REGULATORY INFORMATION											
U.S. FEDERAL:											
TSCA	Perlite is not on the EPA TSCA inventory list by name but as a natural material, it is automatically included.										
CERCLA	Perlite is not classified as a hazardous substance under regulations of the Comprehensive Environmental Response Compensation and Liability Act (CERCLA), 40 CFR 302.										
SARA TITLE III	Not listed.										
SECTION 16: OTHER INFORMATION											
	NFPA 1 0 - 0 4-Extreme 3-High 2-Moderate 1-Slight 0-Insignificant HMIS <table border="1" style="border-collapse: collapse;"> <tr><td>0</td><td>Health</td></tr> <tr><td>0</td><td>Flammability</td></tr> <tr><td>0</td><td>Reactivity</td></tr> <tr><td>E</td><td>Protective Equipment</td></tr> </table>			0	Health	0	Flammability	0	Reactivity	E	Protective Equipment
0	Health										
0	Flammability										
0	Reactivity										
E	Protective Equipment										
REVISION DATE	February 3, 2022										
REVISION NO.	10										

Disclaimer: As of the date of the preparation of this document, the foregoing information is believed to be accurate and is provided in good faith to comply with applicable federal and state laws. No warranty, representation or guaranty of any kind, express or implied, is hereby provided or intended with respect to the completeness of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by the purchase, resale, use or exposure to our product. Customer users of silica must comply with all applicable health and safety laws, regulations and orders, including OSHA Hazardous Communication Standard.