

Safety Data Sheet
ISOBUTYL ACETATE

Version 1.5

Revision Date: 11/05/2022

SECTION 1. IDENTIFICATION**Product name** : ISOBUTYL ACETATE

Synonyms : 2-methylpropyl acetate

Recommended use of the chemical and restrictions on use

Recommended use : Solvent.

Restricted Uses : No data available

Manufacturer or supplier's details**Company** : Univar Solutions Canada Ltd.
Address : 64 Arrow Road
North York, ON, M9M 2L9
Canada**Emergency telephone number:**

Local Emergency Contact : During Office hours Monday-Friday, 8.00 am - 4.30 pm (Pacific Standard Time) : 1-866-686-4827

Additional Information: : Responsible Party: Product Compliance Department
E-mail: SDSNA@univarsolutions.com
SDS Requests: 1-855-429-2661
Website: www.univarsolutions.com**SECTION 2. HAZARD IDENTIFICATION****Hazardous Classification of the substance or mixture**

Flammable liquids : Category 2

Specific target organ toxicity : Category 3 (Central nervous system)
- single exposure**Label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H336 May cause drowsiness or dizziness.Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.

Safety Data Sheet

ISOBUTYL ACETATE

Version 1.5

Revision Date: 11/05/2022

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Hazardous components

CAS-No.	Chemical name	% by Weight	Synonyms
110-19-0	Isobutyl acetate	80 - 100	Isobutyl acetate

The exact ranges of this mixture are being withheld due to a Trade Secret.

SECTION 4. FIRST-AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

Safety Data Sheet
ISOBUTYL ACETATE

Version 1.5

Revision Date: 11/05/2022

Do not induce vomiting without medical advice.

SECTION 5. FIREFIGHTING MEASURES

- | | |
|---|---|
| Suitable extinguishing media | : Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during fire-fighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : Carbon oxides |
| Further information | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. |
| Environmental precautions | : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods and materials for containment and cleaning up | : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). |

SECTION 7. HANDLING AND STORAGE

- | | |
|---|---|
| Advice on protection against fire and explosion | : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. |
|---|---|

Safety Data Sheet

ISOBUTYL ACETATE

Version 1.5

Revision Date: 11/05/2022

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
110-19-0	Isobutyl acetate	TWA	150 ppm 713 mg/m3	CA AB OEL
		TWA	150 ppm	CA BC OEL
		TWA	150 ppm	CA ON OEL
		STEL	187 ppm	CA ON OEL
		TWAEV	150 ppm 713 mg/m3	CA QC OEL

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Organic vapour type
- Hand protection
- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Safety Data Sheet

ISOBUTYL ACETATE

Version 1.5

Revision Date: 11/05/2022

Appearance	: liquid
Colour	: Clear, colorless
Odour	: fruity
Odour Threshold	: No data available
pH	: 6.7 @ 20 °C (68 °F)
Freezing Point (Melting point/freezing point)	: < -90 °C (-130 °F)
Boiling Point (Boiling point/boiling range)	: 117 - 118 °C (243 - 244 °F) (1013 hPa)
Flash point	: 16.7 - 22 °C (62.1 - 72 °F) Method: Tag closed cup
Evaporation rate	: < 1.7 (Butyl Acetate = 1)
Flammability (solid, gas)	: No data available
Upper explosion limit	: 10.5 %(V)
Lower explosion limit	: 1.3 %(V)
Vapour pressure	: < 15 mmHg @ 20 °C (68 °F)
Relative vapour density	: 4 @ 20 - 25 °C (68 - 77 °F) (Air = 1.0)
Relative density	: 0.871 - 0.873 @ 20 °C (68 °F) Reference substance: (water = 1)
Density	: No data available
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: log Pow: 2.3
Auto-ignition temperature	: 421 - 430 °C
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: 0.7 mPa.s @ 20 °C (68 °F)
Viscosity, kinematic	: 0.8 mm ² /s @ 20 °C (68 °F)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Keep away from heat, flame, sparks and other ignition sources.
Incompatible materials	: Strong acids Strong bases

Safety Data Sheet
ISOBUTYL ACETATE

Version 1.5

Revision Date: 11/05/2022

Hazardous decomposition products : Strong oxidizing agents
: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION**STOT - single exposure****Components:****110-19-0:**

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

Further information**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****110-19-0:**Toxicity to fish : LC50 (*Oryzias latipes* (Japanese medaka)): 16.6 mg/l
Exposure time: 96 hToxicity to daphnia and other aquatic invertebrates : (*Daphnia magna* (Water flea)): 25 mg/l
Exposure time: 48 h
Test Type: static test

Acute aquatic toxicity- Assessment : Harmful to aquatic life.

Chronic aquatic toxicity- Assessment : This product has no known ecotoxicological effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Safety Data Sheet

ISOBUTYL ACETATE

Version 1.5

Revision Date: 11/05/2022

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Univar Solutions ChemCare: 1-800-637-7922

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

TDG (Transportation of Dangerous Goods):

UN1213, ISOBUTYL ACETATE, 3, II

IATA (International Air Transport Association):

UN1213, Isobutyl acetate, 3, II

IMDG (International Maritime Dangerous Goods):

UN1213, ISOBUTYL ACETATE, 3, II, Flash Point: 16.7 - 22 °C (62.1 - 72 °F)

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

Safety Data Sheet

ISOBUTYL ACETATE

Version 1.5

Revision Date: 11/05/2022

NZIoC	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PHIL	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Univar Solutions EHS Product Compliance Department (1-855-429-2661) SDSNA@univarsolutions.com.

Revision Date : 11/05/2022

Legacy SDS: : R0003754

Material number:

16187981, 16178789, 16177094, 16168230, 16169613, 16163893, 16162425, 16135261, 16146754, 16143922, 16143309, 16117695, 16115213, 16071916, 16062126, 16056262, 16055692, 16050557, 721555, 651548, 546856, 546858, 501463, 88701, 88857, 73453, 86602, 158776, 124706, 502776, 39845, 20414, 20413, 20412, 20411, 20410, 20409, 20408, 88074

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic

Safety Data Sheet

ISOBUTYL ACETATE

Version 1.5

Revision Date: 11/05/2022

GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		