

Safety Data Sheet

TERT BUTYL ACETATE

Version 1.8

Revision Date: 07/15/2025

SECTION 1. IDENTIFICATION

Product name : TERT BUTYL ACETATE

Synonyms : No data available

Recommended use of the chemical and restrictions on use

Recommended use : Solvent
Industrial chemical

Restricted Uses : No data available

Manufacturer or supplier's details

Company : Univar Solutions Canada Ltd.
Address : 64 Arrow Road
North York, ON, M9M 2L9
Canada

Emergency telephone number:

Local Emergency Contact : During Office hours Monday-Friday, 8.00 am - 4.30 pm (Pacific Standard Time) : 1-866-686-4827

Additional Information: : Responsible Party: Product Compliance Department
E-mail: SDSNA@univarsolutions.com
SDS Requests: 1-855-429-2661
Website: www.univarsolutions.com

SECTION 2. HAZARD IDENTIFICATION

Hazardous Classification of the substance or mixture

Flammable liquids : Category 2

Acute toxicity (Inhalation) : Category 4

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.

Safety Data Sheet

TERT BUTYL ACETATE

Version 1.8

Revision Date: 07/15/2025

P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equip-
ment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist or vapours.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/
face protection/ hearing protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately
all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air
and keep comfortable for breathing. Call a POISON CENTER/
doctor if you feel unwell.

P370 + P378 In case of fire: Use dry sand, dry chemical or alco-
hol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container
tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-
posal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Hazardous components

CAS-No.	Chemical name	% by Weight	Synonyms
540-88-5	Tert-butyl acetate	80 - 100	Tert-Butyl Ace- tate

The exact ranges of this mixture are being withheld due to a Trade Secret.

SECTION 4. FIRST-AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical
advice.

In case of skin contact : If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.

Safety Data Sheet

TERT BUTYL ACETATE

Version 1.8

Revision Date: 07/15/2025

If swallowed	Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Do not induce vomiting without medical advice.
Most important symptoms and effects, both acute and delayed	: Harmful if inhaled.
	May cause respiratory irritation. May cause drowsiness or dizziness.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during fire-fighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: No hazardous combustion products are known
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

Safety Data Sheet

TERT BUTYL ACETATE

Version 1.8

Revision Date: 07/15/2025

/ national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Container may be opened only under exhaust ventilation hood. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
540-88-5	Tert-butyl acetate	TWA	200 ppm 950 mg/m3	CA AB OEL
		TWAEV	50 ppm	CA QC OEL
		STEV	150 ppm	CA QC OEL
		TWA	50 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Organic vapour type
- Hand protection

Safety Data Sheet

TERT BUTYL ACETATE

Version 1.8

Revision Date: 07/15/2025

Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Eye wash bottle with pure water Tightly fitting safety goggles
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: Clear, colorless
Odour	: pungent, characteristic
Odour Threshold	: 71 ppb
pH	: 6 - 7 @ 20 - 25 °C (68 - 77 °F)
Freezing Point (Melting point/freezing point)	: -58.15 °C (-72.67 °F)
Boiling Point (Boiling point/boiling range)	: 97.8 °C (208.0 °F)
Flash point	: 4 °C (39 °F) (1013 hPa)
Evaporation rate	: 2.8 (Butyl Acetate = 1)
Flammability (solid, gas)	: No data available
Upper explosion limit	: 6.88 %(V)
Lower explosion limit	: 1.26 %(V)
Vapour pressure	: 42 mmHg @ 20 °C (68 °F)
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.86 g/cm ³ @ 25 °C (77 °F)
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: log Pow: 1.64
Auto-ignition temperature	: 589 °C
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: < 1 mPa.s @ 25 °C (77 °F)
Viscosity, kinematic	: < 1 mm ² /s

Safety Data Sheet

TERT BUTYL ACETATE

Version 1.8

Revision Date: 07/15/2025

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Keep away from heat, flame, sparks and other ignition sources.
Incompatible materials	: Plastics Acids Bases nitrates Strong oxidizing agents
Hazardous decomposition products	: acetic acid Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if inhaled.

Product:

Acute inhalation toxicity : Acute toxicity estimate: 22 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The component/mixture is moderately toxic after short term inhalation.

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation: Not classified due to lack of data.

Respiratory sensitisation: Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

Safety Data Sheet

TERT BUTYL ACETATE

Version 1.8

Revision Date: 07/15/2025

Components:

540-88-5:

Target Organs: Respiratory system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Based on available data, the classification criteria are not met.

Product:

May be harmful if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

Safety Data Sheet

TERT BUTYL ACETATE

Version 1.8

Revision Date: 07/15/2025

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

TDG (Transportation of Dangerous Goods):

UN1123, BUTYL ACETATES, 3, II

IATA (International Air Transport Association):

UN1123, BUTYL ACETATES, 3, II

IMDG (International Maritime Dangerous Goods):

UN1123, BUTYL ACETATES, 3, II, Flash Point: 4 °C (39 °F)

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all of the information required by the HPR.

NPRI Components : 75-65-0

The components of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

AIIC : On the inventory, or in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : Not in compliance with the inventory

SECTION 16. OTHER INFORMATION

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with

Safety Data Sheet

TERT BUTYL ACETATE

Version 1.8

Revision Date: 07/15/2025

which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Univar Solutions EHS Product Compliance Department (1-855-429-2661) SDSNA@univarsolutions.com.

Revision Date : 07/15/2025

Legacy SDS: : R0348217

Material number:

16222651, 16214401, 16141748, 16177971, 16175575, 16168438, 16169761, 16154827, 16146088, 16161745, 16137966, 16143315, 16143304, 16065868, 16056728, 16056725, 16052024, 16013557, 734537, 612821, 606888, 584139, 554270, 554253, 556647, 53935, 102271, 103494, 70028, 502845, 502844, 556646

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIC	Australia Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50			Lethal Concentration 50%

Safety Data Sheet
TERT BUTYL ACETATE

Version 1.8

Revision Date: 07/15/2025