

Safety Data Sheet

VERSENE™ 100 XL Chelating Agent

Version 1.3

Revision Date: 11/05/2022

SECTION 1. IDENTIFICATION

Product name : VERSENE™ 100 XL Chelating Agent

Synonyms : No data available

Recommended use of the chemical and restrictions on use

Recommended use : Chelating agent

Restricted Uses : No data available

Supplier or Repackaging Details

Company : Univar Solutions Canada Ltd.
Address : 64 Arrow Road
 North York, ON, M9M 2L9
 Canada

Manufactured By : THE DOW CHEMICAL COMPANY

Emergency telephone number:

Local Emergency Contact : During Office hours Monday-Friday, 8.00 am - 4.30 pm (Pacific Standard Time) : 1-866-686-4827

Additional Information: : Responsible Party: Product Compliance Department
 E-mail: SDSNA@univarsolutions.com
 SDS Requests: 1-855-429-2661
 Website: www.univarsolutions.com

SECTION 2. HAZARD IDENTIFICATION

Hazardous Classification of the substance or mixture

Corrosive to metals : Category 1

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Serious eye damage : Category 1

Specific target organ toxicity - repeated exposure (Inhalation) : Category 2

Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H290 May be corrosive to metals.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H332 Harmful if inhaled.

Safety Data Sheet

VERSENE™ 100 XL Chelating Agent

Version 1.3

Revision Date: 11/05/2022

H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements

: **Prevention:**

P234 Keep only in original packaging.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P314 Get medical advice/ attention if you feel unwell.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P390 Absorb spillage to prevent material damage.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Chemical name	% by Weight	Synonyms
64-02-8	Tetrasodium ethylenediaminetetraacetate	30 - 60	Tetrasodium ethylenediaminetetraacetate
1310-73-2	Sodium hydroxide	1 - 5	Sodium hydroxide

The exact ranges of this mixture are being withheld due to a Trade Secret.

SECTION 4. FIRST-AID MEASURES

General advice

: Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled

: Consult a physician after significant exposure.

Safety Data Sheet

VERSENE™ 100 XL Chelating Agent

Version 1.3

Revision Date: 11/05/2022

In case of skin contact	:	If unconscious, place in recovery position and seek medical advice.
		If skin irritation persists, call a physician.
		If on skin, rinse well with water.
In case of eye contact	:	If on clothes, remove clothes.
		Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
		In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
If swallowed	:	Continue rinsing eyes during transport to hospital.
		Remove contact lenses.
		Protect unharmed eye.
		Keep eye wide open while rinsing.
		Take victim immediately to hospital.
		Clean mouth with water and drink afterwards plenty of water.
		Keep respiratory tract clear.
		Do not induce vomiting without medical advice.
	:	Do not give milk or alcoholic beverages.
		Never give anything by mouth to an unconscious person.
		If symptoms persist, call a physician.
	:	Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Water spray Foam Dry chemical Carbon dioxide (CO ₂)
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire-fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Nitrogen oxides (NO _x) Carbon oxides
Specific extinguishing methods	:	Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform

Safety Data Sheet

VERSENE™ 100 XL Chelating Agent

Version 1.3

Revision Date: 11/05/2022

respective authorities.

Methods and materials for containment and cleaning up : Neutralise with acid.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Storage period : 24 Months

Packaging material : Unsuitable material: Zinc, Aluminium, Carbon steel, Metal (other than steel or aluminium)
Suitable material: Plastic material, including expanded plastics material, Stainless steel

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1310-73-2	Sodium hydroxide	(c)	2 mg/m ³	CA AB OEL
		C	2 mg/m ³	CA BC OEL
		C	2 mg/m ³	CA QC OEL

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.
In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

Safety Data Sheet

VERSENE™ 100 XL Chelating Agent

Version 1.3

Revision Date: 11/05/2022

Eye protection	:	with the producers of the protective gloves. Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	colourless, yellow
Odour	:	slight, ammoniacal
Odour Threshold	:	No data available
pH	:	11.0 - 11.8 @ 1 % @ 20 - 25 °C (68 - 77 °F)
Freezing Point (Freezing Point)	:	<= -25 °C (<= -13 °F)
Boiling Point (Boiling point/boiling range)	:	106 - 107 °C (223 - 225 °F) (1013 hPa)
Flash point	:	Not applicable
Evaporation rate	:	Estimated < 0.8 (Butyl Acetate = 1)
Flammability (solid, gas)	:	No data available
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	similar to water
Relative vapour density	:	No data available
Relative density	:	1.26 - 1.30 @ 25 °C (77 °F) Reference substance: (water = 1)
Density	:	No data available
Solubility(ies)	:	No data available
Water solubility	:	completely miscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	log Pow: < 0
Auto-ignition temperature	:	No data available
Thermal decomposition	:	No data available
Viscosity	:	
Viscosity, dynamic	:	Estimated 19 mPa.s @ 20 °C (68 °F)
Viscosity, kinematic	:	11 mm ² /s @ 20 °C (68 °F)

Safety Data Sheet**VERSENE™ 100 XL Chelating Agent**

Version 1.3

Revision Date: 11/05/2022

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No hazards to be specially mentioned.
Conditions to avoid	: Keep away from heat, flame, sparks and other ignition sources.
Incompatible materials	: aluminum Copper Copper alloys Nickel Organic materials Oxidizing agents Strong acids Zinc
Hazardous decomposition products	: Ammonia Nitrogen oxides (NOx) Carbon oxides metal oxides

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Product:**

Acute oral toxicity	: Assessment: The substance or mixture has no acute oral toxicity
Acute inhalation toxicity	: Assessment: The component/mixture is moderately toxic after short term inhalation.

Components:**64-02-8:**

Acute oral toxicity	: LD50 (Rat): 630 mg/kg Assessment: The component/mixture is moderately toxic after single ingestion.
Acute inhalation toxicity	: LC50 (Rat): 10 mg/l Test atmosphere: dust/mist Assessment: The component/mixture is moderately toxic after short term inhalation.
Acute dermal toxicity	: Remarks: No data available

1310-73-2:

Acute oral toxicity	: LD50 (Rabbit): 325 mg/kg
---------------------	----------------------------

Safety Data Sheet
VERSENE™ 100 XL Chelating Agent

Version 1.3

Revision Date: 11/05/2022

Skin corrosion/irritation**Components:****64-02-8:**

Species: Rabbit

Result: No skin irritation

1310-73-2:

Species: Rabbit

Result: Causes severe burns.

Serious eye damage/eye irritation**Components:****64-02-8:**

Species: Rabbit

Result: Risk of serious damage to eyes.

1310-73-2:

Species: Rabbit

Result: Risk of serious damage to eyes.

Respiratory or skin sensitisation**Components:****64-02-8:**

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity**Components:****64-02-8:**

Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Carcinogenicity**Components:****64-02-8:**

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

Reproductive toxicity**Components:****64-02-8:**

Teratogenicity - Assessment : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

Safety Data Sheet
VERSENE™ 100 XL Chelating Agent

Version 1.3

Revision Date: 11/05/2022

STOT - repeated exposure**Product:**

Exposure routes: Inhalation

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity**Product:**

No aspiration toxicity classification

Components:**64-02-8:**

No aspiration toxicity classification

Further information**Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****64-02-8:**

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 486 mg/l
Exposure time: 96 h
Test Type: static test

Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): 625 mg/l
aquatic invertebrates : Exposure time: 24 h
Test Type: static test

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 2.77 mg/l
End point: Growth rate
Exposure time: 72 h
Test Type: static test

Acute aquatic toxicity- As- : Toxic to aquatic life.
essment

Chronic aquatic toxicity- As- : Toxic to aquatic life with long lasting effects.
essment

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Safety Data Sheet
VERSENE™ 100 XL Chelating Agent

Version 1.3

Revision Date: 11/05/2022

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Univar Solutions ChemCare: 1-800-637-7922

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION**TDG (Transportation of Dangerous Goods):**

UN3267, CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S., (TETRASODIUM ETHYLENEDIAMINETETRAACETATE, SODIUM HYDROXIDE), 8, III

IATA (International Air Transport Association):

UN3267, CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S., (TETRASODIUM ETHYLENEDIAMINETETRAACETATE, SODIUM HYDROXIDE), 8, III

IMDG (International Maritime Dangerous Goods):

UN3267, CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S., (TETRASODIUM ETHYLENEDIAMINETETRAACETATE, SODIUM HYDROXIDE), 8, III, Marine Pollutant (TETRASODIUM ETHYLENEDIAMINETETRAACETATE)

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

Safety Data Sheet

VERSENE™ 100 XL Chelating Agent

Version 1.3

Revision Date: 11/05/2022

SECTION 16. OTHER INFORMATION

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Univar Solutions EHS Product Compliance Department (1-855-429-2661) SDSNA@univarsolutions.com.

Revision Date : 11/05/2022

Legacy SDS: : 140000000262

Material number:

16153158, 16154126, 16153000, 16154209, 16156893, 16140588, 16120701, 16120581, 16119721, 69452, 616831, 53075, 87837, 103607, 86417, 54191, 16049474, 69371

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Invento-	UVCB	Unknown or Variable Composition, Com-

Safety Data Sheet**VERSENE™ 100 XL Chelating Agent**

Version 1.3

Revision Date: 11/05/2022

	ry		plex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50		Lethal Concentration 50%	