



SAFETY DATA SHEET

DOW CHEMICAL CANADA ULC

Product name: XIAMETER™ OFS-6341 Silane

Issue Date: 08/09/2024

Print Date: 08/10/2024

DOW CHEMICAL CANADA ULC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: XIAMETER™ OFS-6341 Silane

Other means of identification: Triethoxy(octyl)silane

Recommended use of the chemical and restrictions on use

Identified uses: Impregnation agents

COMPANY IDENTIFICATION

DOW CHEMICAL CANADA ULC
#2400, 215 - 2ND STREET S.W.
CALGARY AB T2P 1M4
CANADA

Customer Information Number:

800-258-2436

SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact (transportation emergencies only): 1-800-424-9300

Local Emergency Contact (transportation emergencies only): 1-800-424-9300

24-Hour Emergency Contact: 1-989-636-4400

2. HAZARDS IDENTIFICATION

Hazard classification

This product is hazardous under the criteria of the Hazardous Products Regulation (HPR) as implemented under the Workplace Hazardous Materials Information System (WHMIS 2015).

Flammable liquids - Category 4

Skin irritation - Category 2

Label elements

Hazard pictograms



Signal word: **WARNING!**

Hazards

H227 Combustible liquid.
H315 Causes skin irritation.

Precautionary statements**Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, protective clothing, eye protection, face protection and/or hearing protection.

Response

P302 + P352 IF ON SKIN: Wash with plenty of water.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage

P403 Store in a well-ventilated place.

Disposal

P501 Dispose of contents and/or container to an approved waste disposal plant.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms: Triethoxy(octyl)silane

This product is a substance.

Substance name: Triethoxy(octyl)silane

CASRN: 2943-75-1

Chemical name	Common name and synonym	CASRN	Concentration (w/w)
Triethoxy(octyl)silane	triethoxyoctylsilane	2943-75-1	>= 96.0 - <= 100.0 %

4. FIRST AID MEASURES

Description of first aid measures

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air and keep comfortable for breathing; consult a physician.

Skin contact: Wash off with plenty of water. Suitable emergency safety shower facility should be available in work area.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: Rinse mouth with water. No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed:

Causes skin irritation.

Indication of any immediate medical attention and special treatment needed

Notes to physician: If burn is present, treat as any thermal burn, after decontamination. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam. Dry sand.

Unsuitable extinguishing media: High volume water jet. Do not use direct water stream..

Special hazards arising from the substance or mixture

Hazardous combustion products: Carbon oxides. Silicon oxides. Formaldehyde.

Unusual Fire and Explosion Hazards: Flash back possible over considerable distance.. Exposure to combustion products may be a hazard to health.. Closed containers may rupture via pressure build-up when exposed to fire or extreme heat.. Vapours may form explosive mixtures with air..

Advice for firefighters

Fire Fighting Procedures: Use water spray to cool unopened containers.. Evacuate area.. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.. Fire residues and contaminated fire extinguishing water must be disposed of in

accordance with local regulations.. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed.. Do not use a solid water stream as it may scatter and spread fire..

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus.. Use personal protective equipment..

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet. Clean up remaining materials from spill with suitable absorbant. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. See sections: 7, 8, 11, 12 and 13.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not get on skin or clothing. Avoid inhalation of vapour or mist. Avoid contact with eyes. Do not swallow. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied. Use with local exhaust ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Conditions for safe storage: Keep in properly labelled containers. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Do not store with the following product types: Strong oxidizing agents. Explosives. Gases. Unsuitable materials for containers: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Consult local authorities for recommended exposure limits.

Component	Regulation	Type of listing	Value
Ethanol	ACGIH	TWA	1,000 ppm
	Further information: URT irr: Upper Respiratory Tract irritation		
	ACGIH	STEL	1,000 ppm
	Further information: URT irr: Upper Respiratory Tract irritation		
	CA AB OEL	TWA	1,880 mg/m ³ 1,000 ppm
	CA BC OEL	STEL	1,000 ppm
	CA QC OEL	STEV	1,000 ppm
	Further information: C3: Carcinogenic effect detected in animals. Results of studies relating to the carcinogenicity of these substances in animals are not necessarily applicable to humans.		

The following substance(s), which have Occupational Exposure Limit(s) (OEL), may be formed during handling or processing: Ethanol

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields).

Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl chloride ("PVC" or "vinyl"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	liquid
Color	Colorless to pale yellow

Odor alcohol-like

Odor Threshold No data available

pH No data available

Melting point/freezing point

Melting point/ range No data available

Freezing point No data available

Boiling point, initial boiling point and boiling range

Boiling point (760 mmHg) > 65 °C

Flash point **closed cup** 65 °C

Evaporation Rate (Butyl Acetate = 1) No data available

Flammability

Flammability (solid, gas) Not applicable

Flammability (liquids) Not applicable

Upper/lower flammability or explosive limits

Lower explosion limit No data available

Upper explosion limit No data available

Vapor Pressure No data available

Relative vapour density

Relative Vapor Density (air = 1) No data available

Density and / or relative density

Relative Density (water = 1) 0.877

Solubility(ies)

Water solubility No data available

Partition coefficient: n-octanol/water (log value) No data available

Auto-ignition temperature No data available

Decomposition temperature No data available

Kinematic Viscosity 2.04 cSt at 25 °C

Explosive properties Not explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

Molecular weight No data available

Particle characteristics

Particle size Not applicable

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents. When heated to temperatures above 150 °C (300 °F) in the presence of air, product can form formaldehyde vapours. Safe handling conditions may be maintained by keeping vapour concentrations within the occupational exposure limit for formaldehyde. Vapours may form explosive mixture with air.

Conditions to avoid: Heat, flames and sparks.

Incompatible materials: Avoid contact with oxidizing materials.

Hazardous decomposition products:

Decomposition products can include and are not limited to: Ethanol.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data are available.

Information on likely routes of exposure

Inhalation, Eye contact, Skin contact, Ingestion.

Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

Acute Toxicity Endpoints:

Not classified based on available information.

Acute oral toxicity

Information for the Product:

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):

LD50, > 5,000 mg/kg Estimated.

Information for components:

Triethoxy(octyl)silane

LD50, Rat, male and female, 5,110 mg/kg OECD 401 or equivalent

Acute dermal toxicity

Information for the Product:

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):
LD50, > 2,000 mg/kg Estimated.

Information for components:

Triethoxy(octyl)silane

LD50, Rabbit, female, 8,000 mg/kg OECD 402 or equivalent

LD50, Rabbit, male, 6,730 mg/kg OECD 402 or equivalent

Acute inhalation toxicity

Information for the Product:

No adverse effects are anticipated from single exposure to vapor.

As product: The LC50 has not been determined.

Information for components:

Triethoxy(octyl)silane

LC50, Rat, male and female, 4 hrs, vapour, > 22 ppm OECD Test Guideline 403 No deaths occurred at this concentration.

Skin corrosion/irritation

Causes skin irritation.

Information for the Product:

Based on information for component(s):
Brief contact may cause moderate skin irritation with local redness.
Prolonged contact may cause moderate skin irritation with local redness.

Information for components:

Triethoxy(octyl)silane

Brief contact may cause moderate skin irritation with local redness.
Prolonged contact may cause moderate skin irritation with local redness.

Serious eye damage/eye irritation

Not classified based on available information.

Information for the Product:

Based on information for component(s):
May cause slight eye irritation.
Corneal injury is unlikely.

Information for components:

Triethoxy(octyl)silane

May cause slight eye irritation.
Corneal injury is unlikely.

Sensitization

For skin sensitization:

Not classified based on available information.

For respiratory sensitization:

Not classified based on available information.

Information for the Product:

For skin sensitization:

Contains component(s) which did not cause allergic skin sensitization in guinea pigs.

For respiratory sensitization:

No relevant data found.

Information for components:

Triethoxy(octyl)silane

For similar material(s):

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Triethoxy(octyl)silane

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Aspiration Hazard

Not classified based on available information.

Information for the Product:

Based on available information, aspiration hazard could not be determined.

Information for components:

Triethoxy(octyl)silane

Material is not classified as an aspiration hazard based on insufficient data, however materials with low viscosity may be aspirated into the lungs during ingestion or vomiting.

Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Triethoxy(octyl)silane

In animals, effects have been reported on the following organs:

Urinary tract.

Findings from a combined repeated-dose toxicity study with reproductive/developmental screening endpoints on n-octyltriethoxysilane have shown neurological effects in rats at high doses (1000 mg/kg). Paralysis and paresis of the limbs, and demyelination of the brain, spinal cord, sciatic and tibial nerves was noted in some animals.

Carcinogenicity

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Triethoxy(octyl)silane

No relevant data found.

Teratogenicity

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Triethoxy(octyl)silane

Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Dose levels producing these effects were many times higher than any dose levels expected from exposure due to use.

Reproductive toxicity

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:**Triethoxy(octyl)silane**

In animal studies, did not interfere with reproduction.

Mutagenicity

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:**Triethoxy(octyl)silane**

In vitro genetic toxicity studies were negative.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data are available.

Toxicity**Triethoxy(octyl)silane****Acute toxicity to fish**

Not expected to be acutely toxic to aquatic organisms.

No toxicity at the limit of solubility

LC50, Oncorhynchus mykiss (rainbow trout), flow-through, 96 hrs, > 0.055 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

No toxicity at the limit of solubility

EC50, Daphnia magna (Water flea), flow-through test, 48 hrs, > 0.049 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

No toxicity at the limit of solubility

ErC50, Pseudokirchneriella subcapitata (green algae), static test, 72 hrs, Growth rate inhibition, > 0.13 mg/l, OECD Test Guideline 201 or Equivalent

No toxicity at the limit of solubility

NOEC, Pseudokirchneriella subcapitata (green algae), static test, 72 hrs, Growth rate inhibition, > 0.13 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

EC50, activated sludge, 3 Hour, Respiration rates., > 1,000 mg/l, activated sludge test (OECD 209)

Chronic toxicity to fish

No toxicity at the limit of solubility

NOEC, Fathead minnow (*Pimephales promelas*), 32 d, mortality, > 0.036 mg/l

Chronic toxicity to aquatic invertebrates

No toxicity at the limit of solubility

NOEC, *Daphnia magna* (Water flea), 21 d, number of offspring, >= 0.199 mg/l

Persistence and degradability**Triethoxy(octyl)silane**

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail

Biodegradation: 31.5 %

Exposure time: 28 d

Method: OECD Test Guideline 301D or Equivalent

Stability in Water (1/2-life)

, 30 Hour, pH 7, Half-life Temperature 20 °C, Estimated.

Bioaccumulative potential**Triethoxy(octyl)silane**

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

Partition coefficient: n-octanol/water(log Pow): 6.41 OECD Test Guideline 117 or Equivalent

Bioconcentration factor (BCF): 1,890 Carp (*Cyprinus carpio*) 56 d OECD Test Guideline 305 or Equivalent

Mobility in soil**Triethoxy(octyl)silane**

Partition coefficient (Koc): > 5000 Estimated.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN SDS SECTION 1: Identified Uses. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling &

Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10
Regulatory Information, MSDS Section 15

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility of the waste generator. Do not re-use containers for any purpose.

14. TRANSPORT INFORMATION

TDG

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

**Transport in bulk
according to Annex I or II
of MARPOL 73/78 and the
IBC or IGC Code**

Not regulated for transport
Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Canadian Domestic Substances List (DSL)

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

16. OTHER INFORMATION

Revision

Identification Number: 4099689 / A208 / Issue Date: 08/09/2024 / Version: 10.0

In case this version of the SDS contains significant changes from the previous version, they are listed below or noted by bold, double bars in the left-hand margin throughout this document.

Changes encompass identification, hazards, tox/eco-tox information and the addition/removal of the ingredients, and regulatory information, hazard information, uses, risk management measures and other key regulatory changes of the product. Detailed explanation of the changes can be obtained upon request.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	Canada. British Columbia OEL
CA QC OEL	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
STEL	short-term exposure limit
STEV	Short-term exposure value
TWA	8-hour Occupational exposure limit

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DOW CHEMICAL CANADA ULC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

CA