

SAFETY DATA SHEET



XIAMETER(R) OFS-6920 SILANE

Version 1.6 Revision Date: 09/14/2017 SDS Number: 799288-00007 Date of last issue: 03/10/2017
Date of first issue: 11/20/2014

SECTION 1. IDENTIFICATION

Product name : XIAMETER(R) OFS-6920 SILANE

Product code : 000000000004074881

Manufacturer or supplier's details

Company name of supplier : Dow Corning Canada, Inc

Address : Unit 9 Suite 700 6975 Meadowvale Town Centre Cir
Mississauga, ON L5N 2V7 Canada

Telephone : (800) 248-2481

Emergency telephone : Product Safety : (888) 335-1331 NEWALTA : (800) 567-7455

Recommended use of the chemical and restrictions on use

Recommended use : Additives

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Organosilane

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Triethoxy(3-mercaptopropyl)silane	14814-09-6	>= 1.7 - <= 2.3

SECTION 4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.
Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

XIAMETER(R) OFS-6920 SILANE

Version	Revision Date:	SDS Number:	Date of last issue: 03/10/2017
1.6	09/14/2017	799288-00007	Date of first issue: 11/20/2014

If swallowed	:	If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	:	None known.
Protection of first-aiders	:	No special precautions are necessary for first aid responders.
Notes to physician	:	Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	:	None known.
Specific hazards during fire fighting	:	Exposure to combustion products may be a hazard to health.
Hazardous combustion products	:	Carbon oxides Silicon oxides Sulfur oxides Formaldehyde
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Follow safe handling advice and personal protective equipment recommendations.
Environmental precautions	:	Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g., by containment or oil barriers). Retain and dispose of contaminated wash water.

XIAMETER(R) OFS-6920 SILANE

Version	Revision Date:	SDS Number:	Date of last issue: 03/10/2017
1.6	09/14/2017	799288-00007	Date of first issue: 11/20/2014

Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
 For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
 Clean up remaining materials from spill with suitable absorbent.
 Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
 Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
 Keep away from water.
 Protect from moisture.
 Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
 Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
 Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Contains no substances with occupational exposure limit values.

Occupational exposure limits of decomposition products

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethanol	64-17-5	TWA	1,000 ppm 1,880 mg/m ³	CA AB OEL
		STEL	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,880 mg/m ³	CA QC OEL

SAFETY DATA SHEET



XIAMETER(R) OFS-6920 SILANE

Version 1.6	Revision Date: 09/14/2017	SDS Number: 799288-00007	Date of last issue: 03/10/2017 Date of first issue: 11/20/2014
----------------	------------------------------	-----------------------------	---

		STEL	1,000 ppm	ACGIH
--	--	------	-----------	-------

Engineering measures : Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic vapor Type

Hand protection

Remarks : Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.
For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : No data available

Odor : characteristic

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : ≥ 150 °C

SAFETY DATA SHEET



XIAMETER(R) OFS-6920 SILANE

Version 1.6	Revision Date: 09/14/2017	SDS Number: 799288-00007	Date of last issue: 03/10/2017 Date of first issue: 11/20/2014
----------------	------------------------------	-----------------------------	---

Flash point	:	105.56 °C Method: Seta closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Not applicable
Self-ignition	:	The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	1.0268
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	1.5 cSt (25 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.

XIAMETER(R) OFS-6920 SILANE

Version	Revision Date:	SDS Number:	Date of last issue: 03/10/2017
1.6	09/14/2017	799288-00007	Date of first issue: 11/20/2014

Possibility of hazardous reactions : Use at elevated temperatures may form highly hazardous compounds.
Can react with strong oxidizing agents.
Hazardous decomposition products will be formed upon contact with water or humid air.
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Exposure to moisture.

Incompatible materials : Oxidizing agents
Water

Hazardous decomposition products

Contact with water or humid air : Ethanol

Thermal decomposition : Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Ingredients:**Triethoxy(3-mercaptopropyl)silane:**

Acute oral toxicity : LD50 (Rat): 0.73 ml/kg
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Ingredients:**Triethoxy(3-mercaptopropyl)silane:**

Species: Rabbit
Result: No skin irritation
Remarks: Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

XIAMETER(R) OFS-6920 SILANE

Version	Revision Date:	SDS Number:	Date of last issue: 03/10/2017
1.6	09/14/2017	799288-00007	Date of first issue: 11/20/2014

Ingredients:**Triethoxy(3-mercaptopropyl)silane:**

Species: Rabbit

Result: No eye irritation

Remarks: Based on data from similar materials

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Ingredients:**Triethoxy(3-mercaptopropyl)silane:**

Assessment: Does not cause skin sensitization.

Test Type: Skin: test type not specified

Remarks: On basis of test data.

Germ cell mutagenicity

Not classified based on available information.

Ingredients:**Triethoxy(3-mercaptopropyl)silane:**

Genotoxicity in vitro : Test Type: Mutagenicity (in vitro mammalian cytogenetic test)

Result: positive

Remarks: On basis of test data.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Ingredients:****Triethoxy(3-mercaptopropyl)silane:**

SAFETY DATA SHEET



XIAMETER(R) OFS-6920 SILANE

Version	Revision Date:	SDS Number:	Date of last issue: 03/10/2017
1.6	09/14/2017	799288-00007	Date of first issue: 11/20/2014

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 6.7 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

The ingredients of this product are reported in the following inventories:

KECI : All ingredients listed, exempt or notified.

XIAMETER(R) OFS-6920 SILANE

Version	Revision Date:	SDS Number:	Date of last issue: 03/10/2017
1.6	09/14/2017	799288-00007	Date of first issue: 11/20/2014

TCSI	:	All ingredients listed or exempt.
REACH	:	For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office.
TSCA	:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
AICS	:	All ingredients listed or exempt.
IECSC	:	All ingredients listed or exempt.
ENCS/ISHL	:	All components are listed on ENCS/ISHL or exempted from inventory listing.
PICCS	:	All ingredients listed or exempt.
DSL	:	All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA BC OEL / STEL	:	short-term exposure limit
CA QC OEL / TWAEV	:	Time-weighted average exposure value

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dan-

XIAMETER(R) OFS-6920 SILANE

Version	Revision Date:	SDS Number:	Date of last issue: 03/10/2017
1.6	09/14/2017	799288-00007	Date of first issue: 11/20/2014

gerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/14/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8