

SAFETY DATA SHEET

Classified in accordance with Health Canada Hazardous Products Regulations (SOR/2015-17)

1. Identification

Identification
Product name: FLOZOL® 2252

Additional identification
Chemical name: Polymer

Recommended use and restriction on use
Recommended use: Oilfield Chemical
Restrictions on use: None identified.

Details of the supplier of the safety data sheet

Supplier
Company Name: LUBRIZOL CANADA LIMITED
Address: 6-14845 Yonge Street, Suite 118
Aurora, Ontario, L4G 6H8
CA
Telephone: 905.264.4646

Emergency telephone number:
FOR TRANSPORT EMERGENCY CALL CHEMTREC (+1)703 527 3887 OR WITHIN CANADA 800 424 9300

2. Hazard(s) identification

Hazard Classification

Flammable liquids	Category 3
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific Target Organ Toxicity - Single Exposure	Category 3

Unknown toxicity

Acute toxicity, inhalation, dust or mist	49.5 %
--	--------

Label Elements:

Hazard Symbol:

**Signal Word:**

Warning

Hazard Statement:

Flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
Suspected of causing cancer.
Suspected of damaging the unborn child.
May cause respiratory irritation.

Precautionary Statements:**Prevention:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instructions on this label). IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. In case of fire: Use CO₂, dry chemical or foam to extinguish. Water can be used to cool and protect exposed material.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal:

Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

3. Composition/information on ingredients**Mixtures**

Chemical name	CAS number	Percent by Weight **
Xylene	1330-20-7	30 - 60%
Toluene	108-88-3	0.1 - 1%
++ Ethyl benzene	100-41-4	5 - 10%

++ The listed components are subcomponents of the hazardous ingredients listed above.

** The actual concentrations listed in the section have been withheld as proprietary or due to batch to batch variability in concentration.

4. First-aid measures

General information:	IF exposed or concerned: Get medical advice/attention.
Ingestion:	Rinse mouth. Get medical attention if symptoms occur.
Inhalation:	Remove to fresh air and keep at rest in a position comfortable for breathing.
Skin Contact:	Take off immediately all contaminated clothing. Take off contaminated clothing and wash before re-use. Rinse skin with water [or shower]. Wash skin thoroughly with soap and water. If skin irritation occurs, get medical attention. Get medical attention if symptoms occur.
Eye contact:	Rinse cautiously with water for several minutes. Flush thoroughly with water. If irritation occurs, get medical assistance. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: Symptoms may be delayed. See section 11.

Indication of immediate medical attention and special treatment needed

Treatment: Treat symptomatically.

5. Fire-fighting measures

General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.
Suitable (and unsuitable) extinguishing media	
Suitable extinguishing media:	CO2, Dry chemical or Foam. Water can be used to cool and protect exposed material.
Unsuitable extinguishing media:	Not determined.
Specific hazards arising from the chemical:	Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations. Vapors may travel considerable distance to a source of ignition and flash back. Water may cause splattering. Container may rupture on heating. See section 10 for additional information.
Special protective equipment and precautions for firefighters	
Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

**Personal precautions,
protective equipment and
emergency procedures:**

Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep upwind. Keep unauthorized personnel away. See Section 8 of the SDS for Personal Protective Equipment.

Environmental Precautions:

Avoid release to the environment. Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

**Methods and material for
containment and cleaning up:**

In case of leakage, eliminate all ignition sources. Dike far ahead of larger spill for later recovery and disposal. Pick up free liquid for recycle and/or disposal. Residual liquid can be absorbed on inert material. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewer, basements or confined areas.

7. Handling and storage

Precautions for safe handling:

Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Ground and bond container and receiving equipment. Use non-sparking tools. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin. Avoid contact with eyes. Observe good industrial hygiene practices. Use only in well-ventilated areas. Provide adequate ventilation. Use personal protective equipment as required. Wash hands thoroughly after handling. Launder contaminated clothing before reuse. Avoid environmental contamination.

**Maximum Handling
Temperature:**

Not determined.

**Conditions for safe storage,
including any
incompatibilities:**

Keep container tightly closed. Keep cool. Store in a well-ventilated place. Do not store near potential sources of ignition.

**Maximum Storage
Temperature:**

Not determined.

8. Exposure controls/personal protection

Control Parameters: Occupational Exposure Limits

Chemical name	Type	Exposure Limit Values	Source
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values, as amended (02 2012)
Xylene	STEL	150 ppm	US. ACGIH Threshold Limit Values, as amended (02 2012)
Xylene	TWA	20 ppm	US. ACGIH Notice of Intended Changes (NIC) to Threshold Limit Values, as amended (01 2021)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2016)
Xylene	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2016)
Xylene	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
++ Ethyl benzene	TWA	20 ppm	US. ACGIH Threshold Limit Values, as amended (02 2012)
++ Ethyl benzene	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
++ Ethyl benzene	STEL	125 ppm 545 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
++ Ethyl benzene	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
++ Ethyl benzene	STEL	125 ppm 545 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
Toluene	TWA	20 ppm	US. ACGIH Threshold Limit Values, as amended (02 2012)
Toluene	STEL	150 ppm 560 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
Toluene	REL	100 ppm 375 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
Toluene	TWA	200 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000), as amended (02 2006)
Toluene	Ceiling	300 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000), as amended (02 2006)
Toluene	MAX. CONC	500 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000), as amended (02 2006)

Appropriate engineering controls:

Use explosion-proof ventilation equipment to stay below exposure limits.

Individual protection measures, such as personal protective equipment

General information:

Use explosion-proof ventilation equipment. Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Eye/face protection:

Wear tight-fitting goggles or face shield. Safety glasses. If potential for splash or mist exists, wear chemical goggles or faceshield.

Skin Protection

Hand Protection:

Use nitrile or neoprene gloves. Use good industrial hygiene practices. In case of skin contact, wash hands and arms with soap and water. Viton. Teflon. Polyvinyl alcohol. Note: polyvinyl alcohol gloves are water soluble and should not be used when there is potential for water contact.

Other:

Wear apron or protective clothing in case of contact. Do not wear rings, watches or similar apparel that could entrap the material.

Respiratory Protection:

A respiratory protection program compliant with all applicable regulations must be followed whenever workplace conditions require the use of a respirator. Use respirator with an organic vapor and dust/mist cartridge if the recommended exposure limit is exceeded. Use self-contained breathing apparatus for entry into confined space, for other poorly ventilated areas and for large spill clean-up sites.

Hygiene measures:

Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Observe good industrial hygiene practices. Avoid contact with skin. Avoid contact with eyes. Wash contaminated clothing before reuse. When using do not smoke. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Appearance

Physical state:

liquid

Form:

liquid

Color:

Dark

Odor:

Aromatic hydrocarbons

Odor threshold:

No data available.

pH:

Not applicable

Freezing point:

No data available.

Boiling Point:

> 137 °C

Flash Point:

35 °C (Pensky-Martens Closed Cup)

Evaporation rate:

No data available.

Flammability (solid, gas):

No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

No data available.

Flammability limit - lower (%):

No data available.

Explosive limit - upper:

No data available.

Explosive limit - lower:

No data available.

Vapor pressure:

No data available.

Vapor density:

No data available.

Relative density:

0.895 15.6 °C

Solubility(ies)

Solubility in water:

Slightly Soluble

Solubility (other):

No data available.

Partition coefficient (n-octanol/water):

3.8 (Measured)

Auto-ignition temperature:

No data available.

Decomposition temperature:

No data available.

Viscosity:

22 mm²/s (40 °C) 8.5 mm²/s(100 °C)

Other information

Pour Point Temperature: 15 °C

Percent volatile: 50 %(Percent by Weight)

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous reactions: Will not occur.

Conditions to avoid: Heat, sparks, flames.

Incompatible Materials: Strong acids. Reducing agents. Strong oxidizing agents. Strong alkalis. Oxidizing agents.

Hazardous Decomposition Products: Thermal decomposition or combustion may generate smoke, carbon monoxide, carbon dioxide, and other products of incomplete combustion.

11. Toxicological information**Information on likely routes of exposure**

Inhalation: No data available.

Ingestion: No data available.

Skin Contact: Causes skin irritation.

Eye contact: Causes serious eye irritation.

Information on toxicological effects**Acute toxicity****Oral**

Product: LD 50 (Rat): > 5,000 mg/kg (Read across) Not classified
Ingestion can cause central nervous system effects such as headache, dizziness, drowsiness, and generalized weakness.

Dermal

Product: LD 50 (Rabbit): > 2,000 mg/kg (Read across) Not classified
Components of this material may be absorbed through the skin.

Inhalation

Product: ATEmix (, 4 h): > 20 mg/l. Vapour High concentrations may cause headaches, dizziness, fatigue, nausea, vomiting, drowsiness, stupor, other central nervous system effects leading to visual impairment, respiratory failure, unconsciousness and death. The LC50 in rat (4 hr) for xylene is 6,700 ppm.

Skin Corrosion/Irritation:

Product:

Remarks: Causes skin irritation. Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying, and cracking of the skin.

Serious Eye Damage/Eye Irritation:

Product:

Remarks: Causes serious eye irritation.

Respiratory sensitization:

No data available

Skin sensitization:

Xylene

(Literature) Not a skin sensitizer.

Toluene

(Literature) Not a skin sensitizer.

Specific Target Organ Toxicity - Single Exposure:

Xylene

May cause respiratory irritation.

++ Ethyl benzene

Nose, throat and lung irritant.

Toluene

Narcotic effect.

Toluene

Nose, throat and lung irritant.

Aspiration Hazard:

Xylene

May be fatal if swallowed and enters airways.

Toluene

Material can be aspirated into the lungs during the act of swallowing or vomiting. This could result in severe injury to the lungs and death.

Other effects:**Chronic Effects****Carcinogenicity:**

Product:

Not available.

++ Ethyl benzene

A National Toxicology Program (NTP) study found an increased incidence of renal tubule neoplasms in male and female rats exposed to ethylbenzene by inhalation for two years. In male and female mice similarly exposed, increased incidences of alveolar/bronchiolar neoplasms, and hepatocellular neoplasms, respectively, were observed.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

++ Ethyl benzene

Overall evaluation: 2B. Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity:

Product:	The Ames Salmonella test for mutagenicity was negative for this product.
Xylene	This material has not exhibited mutagenic or genotoxic potential in laboratory tests.
++ Ethyl benzene	In vitro and in vivo genetic toxicity studies were negative.
Toluene	In vitro and in vivo genetic toxicity studies were negative. Results of tests in workers exposed to higher concentrations of toluene have shown that this material can cause irreversible changes in the genetic material (DNA) of a cell. The human health consequences of these changes is not fully understood.

Reproductive toxicity:

Xylene	Not Classified based on available data. Based on available data this product is not expected to be classified a reproductive hazard. Xylene is fetotoxic in rats and rabbits in the absence of maternal toxicity.
++ Ethyl benzene	Not Classified based on available data. Based on available data this product is not expected to be classified a reproductive hazard.
Toluene	Prolonged and repeated exposure of pregnant animals to toluene by inhalation has been reported to cause adverse fetal developmental effects.

Specific Target Organ Toxicity - Repeated Exposure:

Xylene	Xylene has been found to cause cardiac, liver and kidney effects, anemia and eye damage in laboratory animals. Prolonged and repeated inhalation of hydrocarbon solvents such as xylene can cause chronic neurological disturbances. Chronic exposure to xylene has been shown to cause hearing loss in experimental animals. Unknown: Target Organ(s): Central nervous system., Hearing
++ Ethyl benzene	Target Organ(s): hearing, Kidney, Liver
Toluene	Inhalation: Target Organ(s): Central nervous system., Hearing Repeated overexposure to toluene may cause loss of appetite, liver enlargement, and kidney and lung damage. Repeated inhalation of hydrocarbon solvents such as toluene can cause chronic neurological disturbances. Chronic exposure to toluene has been shown to cause hearing loss in animal experiments. The effect may be potentiated by acetyl salicylic acid and n-hexane to produce irreversible auditory damage. Prolonged and repeated exposure to toluene may cause color vision loss in humans.

12. Ecological information

Ecotoxicity

Fish

Product:	LC 50 (Rainbow Trout, 4 d): 33.24 mg/l
Xylene	LC 50 (Rainbow Trout, 96 h): 2.6 mg/l NOEC (Rainbow Trout, 56 d): > 1.3 mg/l
++ Ethyl benzene	LC 50 (Rainbow Trout, 96 h): 4.2 mg/l
Toluene	LC 50 (Coho salmon, silver salmon (<i>Oncorhynchus kisutch</i>), 4 d): 5.5 mg/l NOEC (<i>Oncorhynchus kisutch</i> ; <i>Oncorhynchus mykiss</i> , 40 d): 1.39 mg/l

Aquatic Invertebrates

Xylene	EC 50 (Water flea (<i>Daphnia magna</i>), 48 h): 3.82 mg/l NOEC (Water flea (<i>Daphnia magna</i>), 21 d): 1.57 mg/l EC 50 (Water flea (<i>Daphnia magna</i>), 21 d): > 1.57 mg/l
++ Ethyl benzene	EC 50 (Water flea (<i>Daphnia magna</i>), 48 h): 1.8 mg/l NOEC (<i>Ceriodaphnia dubia</i> , 7 d): 0.96 mg/l
Toluene	EC 50 (Water Flea (<i>Ceriodaphnia Dubia</i>), 2 d): 3.78 mg/l NOEC (<i>Ceriodaphnia dubia</i> , 7 d): 0.74 mg/l

Toxicity to Aquatic Plants

Xylene	EC 50 (Algae (<i>Pseudokirchneriella subcapitata</i>), 73 h): 4.36 mg/l
++ Ethyl benzene	EC 50 (Green algae (<i>Selenastrum capricornutum</i>), 96 h): 3.6 mg/l NOEC (Green algae (<i>Selenastrum capricornutum</i>), 96 h): 3.4 mg/l
Toluene	EC 50 (Green algae (<i>Chlorella vulgaris</i>), 3 h): 134 mg/l

Toxicity to soil dwelling organisms

No data available

Sediment Toxicity

No data available.

Toxicity to Terrestrial Plants

No data available

Toxicity to Above-Ground Organisms

No data available

Toxicity to microorganisms

Product:	EC 50 (Sludge, 0.1 d): > 1,000 mg/l
Xylene	LD 50 (Bacteria, 0.1 Days): > 100 mg/l
++ Ethyl benzene	EC 50 (Bacteria, 24 h): 96 mg/l
Toluene	EC 50 (Bacteria, 1 d): 84 mg/l

Persistence and Degradability

Biodegradation

Product:	Miscellaneous, 1 %, 28 d
Xylene	OECD TG 301 F, 90 %, 28 d, Readily biodegradable
++ Ethyl benzene	OECD TG 310, 79 %, 28 d, Readily biodegradable
Toluene	Miscellaneous, 80 %, 20 d, Readily biodegradable

Bioaccumulative potential

Bioconcentration Factor (BCF)

Xylene	Bioconcentration Factor (BCF): 25.9 (Measured)
++ Ethyl benzene	Coho salmon, silver salmon (<i>Oncorhynchus kisutch</i>), Bioconcentration Factor (BCF): 1 (Measured)
Toluene	Fish, Bioconcentration Factor (BCF): 90

Partition Coefficient n-octanol / water (log Kow)

Product:	Log Kow: 3.8 (Measured)
Xylene	Log Kow: 3.16 (estimated)
++ Ethyl benzene	Log Kow: 3.6 (Measured)
Toluene	Log Kow: 2.73 20 °C

Mobility:

No data available

Other adverse effects

Product:	Harmful to aquatic life with long lasting effects.
----------	--

13. Disposal considerations

Disposal instructions:

Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations. Dispose of packaging or containers in accordance with local, regional, national and international regulations. Empty containers retain material residue. Do not cut, weld, braze, solder, drill, grind or expose containers to heat, flame, spark or other sources of ignition.

Contaminated Packaging:

Container packaging may exhibit hazards.

14. Transport information

TDG

UN number or ID number:	UN 1993
UN Proper Shipping Name:	FLAMMABLE LIQUID, N.O.S.(Xylene, Ethyl benzene)
Transport Hazard Class(es)	
Class:	3
Label(s):	3
Packing Group:	III
Environmental Hazards:	Not regulated.

IMDG

UN number or ID number:	UN 1993
UN Proper Shipping Name:	FLAMMABLE LIQUID, N.O.S.(Xylene, Ethyl benzene)
Transport Hazard Class(es)	
Class:	3
Label(s):	3
Packing Group:	III
Environmental Hazards:	Not regulated.
Special precautions for user:	None established

IATA

UN number or ID number:	UN 1993
Proper Shipping Name:	Flammable liquid, n.o.s.(Xylene, Ethyl benzene)
Transport Hazard Class(es):	
Class:	3
Label(s):	3
Packing Group:	III
Environmental Hazards	Not regulated.
Special precautions for user:	None established

Transport in bulk according to Annex II of MARPOL and the IBC Code

None known.

Shipping descriptions may vary based on mode of transport, quantities, temperature of the material, package size, and/or origin and destination. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material. For transportation, steps must be taken to prevent load shifting or materials falling, and all relating legal statutes should be obeyed. Review classification requirements before shipping materials at elevated temperatures.

15. Regulatory information**HMIRA Status**

Not Registered

Inventory Status**Australia (AIC)**

All components are in compliance with chemical notification requirements in Australia.

Canada (DSL/NDL)

All substances contained in this product are in compliance with the Canadian Environmental Protection Act and are present on the Domestic Substances List (DSL) or are exempt.

China (IECSC)

All components of this product are listed on the Inventory of Existing Chemical Substances in China.

European Union (REACH)To obtain information on the REACH compliance status of this product, please e-mail
REACH@SDSInquiries.com.**Great Britain (UK REACH)**To obtain information on the UK REACH compliance status of this product, please e-mail
REACH@SDSInquiries.com.**Japan (ENCS)**

This product contains a substance that is not listed on the Japanese Existing and New Chemical Substances (ENCS) list.

Korea (ECL)

This product contains a substance or polymer that has been notified and is restricted to import by the notifier.

New Zealand (NZIoC)

All components are in compliance with chemical notification requirements in New Zealand.

Philippines (PICCS)

All components are in compliance with the Philippines Toxic Substances and Hazardous and Nuclear Wastes Control Act of 1990 (R.A. 6969).

Switzerland (SWISS)

All components are in compliance with the Environmentally Hazardous Substances Ordinance in Switzerland.

Taiwan (TCSCA)

All components of this product are listed on the Taiwan inventory.

Turkey (KKDIK)

To obtain information on the KKDIK compliance status of this product, please e-mail REACH@SDSInquiries.com.

United States (TSCA)

All substances contained in this product are listed on the TSCA inventory or are exempt.

The information that was used to confirm the compliance status of this product may deviate from the chemical information shown in Section 3.


16. Other information, including date of preparation or last revision

HMIS Hazard ID

Health	*	2
Reactivity		3
Physical Hazards		0

Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible; *Chronic health effect

NFPA Hazard ID



Flammability
Health
Reactivity
Special hazard.

Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible

Issue Date: 22.12.2021

Version #: 3.0

Source of information: Internal company data and other publically available resources.

SDS_CA - FLOZOL® 2252

Further Information:

Contact supplier (see Section 1)

Disclaimer:

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state, and local regulations remains the responsibility of the user.