

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Solvent 142-66

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2023
1.13	08/05/2026	100000004966	Date of first issue: 08/14/2014

SECTION 1. IDENTIFICATION

Product Identifier : Solvent 142-66
Product code : 000000000000102995
Synonyms : No data available
Manufacturer or supplier's details
Company : Univar Solutions USA
Address : 3250 Lacey Rd., Suite 600
Downers Grove, IL 60515
United States of America (USA)

Emergency telephone number:

Univar Solutions USA:-CHEMTREC INTERNATIONAL Tel # 703-527-3887
CHEMTREC INTERNATIONAL Tel # 703-527-3887

Additional Information: : Phone: 1-855-429-2661
Regulatory Information Number: 1-855-429-26611-855-429-2661
Email:
SDSNA@univarsolutions.comSDSNA@univarsolutions.com

Recommended use of the chemical and restrictions on use

Recommended use : Solvent

SECTION 2. HAZARD IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Flammable liquids : Category 4
Specific target organ toxicity : Category 3 (Central nervous system)
- single exposure
Aspiration hazard : Category 1

Other hazards

None known.

Hazards associated with a change in physical form:

No data available

GHS label elements

Hazard pictograms :



Signal word : Danger

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Solvent 142-66

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2023
1.13	08/05/2026	100000004966	Date of first issue: 08/14/2014

Hazard statements : H227 Combustible liquid.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.

Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P331 Do NOT induce vomiting.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Hazards resulting from a reaction with other chemicals under normal conditions of use:

No data available

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Chemical name	Weight percent	Trade secret
64742-47-8	Distillates (petroleum), hydrotreated light	90 - 100	-

Actual concentration is withheld as a trade secret
Any concentration shown as a range is due to batch variation.

SECTION 4. FIRST-AID MEASURES

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Solvent 142-66

Version 1.13	Revision Date: 08/05/2026	SDS Number: 100000004966	Date of last issue: 11/11/2023 Date of first issue: 08/14/2014
-----------------	------------------------------	-----------------------------	---

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.
If inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	: If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If swallowed	: Keep respiratory tract clear. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: None known.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Carbon dioxide (CO ₂) Dry powder Alcohol-resistant foam Water mist
Unsuitable extinguishing media	: High volume water jet
Specific hazards during fire-fighting	: Do not allow run-off from fire fighting to enter drains or water courses. Do not use a solid water stream as it may scatter and spread fire. Cool closed containers exposed to fire with water spray.
Hazardous combustion products	: No hazardous combustion products are known
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containment. Use a water spray to cool fully closed containers.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Solvent 142-66

Version 1.13	Revision Date: 08/05/2026	SDS Number: 100000004966	Date of last issue: 11/11/2023 Date of first issue: 08/14/2014
-----------------	------------------------------	-----------------------------	---

Special protective equipment and precautions for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Material can create slippery conditions.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Keep away from open flames, hot surfaces and sources of ignition.

Keep away from combustible material.

Precautions for safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
Avoid contact with skin and eyes.

Conditions for safe storage : No smoking.
Keep in a well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Solvent 142-66

Version 1.13 Revision Date: 08/05/2026 SDS Number: 100000004966 Date of last issue: 11/11/2023
Date of first issue: 08/14/2014

Further information on storage stability : the technological safety standards.
: No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
64742-47-8	Distillates (petroleum), hydrotreated light	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA	200 mg/m ³ (total hydrocarbon vapor)	ACGIH
		TWA (Mist)	5 mg/m ³	OSHA P0
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL

Engineering measures : Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.
In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Wear suitable protective equipment.
Avoid contact with skin.
When using do not eat, drink or smoke.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State : liquid
Colour : Clear, colorless
Odour : hydrocarbon-like
Odour Threshold : No data available
pH : No data available
Freezing point : No data available
Boiling point (Boiling) : 179 - 213.9 °C (354 - 417.0 °F)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Solvent 142-66

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2023
1.13	08/05/2026	100000004966	Date of first issue: 08/14/2014

point/boiling range)	
Flash point	: 63 - 67 °C (145 - 153 °F) Method: Pensky-Martens closed cup
Evaporation rate	: < 1 (Butyl Acetate = 1)
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: 0.22 - 0.54 mmHg @ 20 °C (68 °F)
Relative vapour density	: No data available
Relative density	: 0.78 - 0.81 @ 15.5 °C (59.9 °F) Reference substance: (water = 1)
Density	: 0.780 - 0.81 g/cm ³ @ 15.5 °C (59.9 °F)
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: 1.38 - 1.8 mm ² /s @ 40 °C (104 °F)
Particle characteristics	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Keep away from heat, flame, sparks and other ignition sources. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow evaporation to dryness.
Incompatible materials	: Oxidizing agents Strong acids Strong bases Strong oxidizing agents
Hazardous decomposition products	: Carbon oxides

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Solvent 142-66

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2023
1.13	08/05/2026	100000004966	Date of first issue: 08/14/2014

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin Absorption

Acute toxicity

Components:

64742-47-8:

Acute inhalation toxicity : Remarks: No data available

Skin corrosion/irritation

Components:

64742-47-8:

Result : Irritating to skin.

Serious eye damage/eye irritation

Components:

64742-47-8:

Result : Not irritating to eyes

Carcinogenicity

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

STOT - single exposure

Components:

64742-47-8:

Target Organs	: Nervous system
Assessment	: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

Aspiration toxicity

Components:

64742-47-8:

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Solvent 142-66

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2023
1.13	08/05/2026	100000004966	Date of first issue: 08/14/2014

Experience with human exposure

Product:

General Information : Prolonged skin contact may cause skin irritation.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Univar Solutions ChemCare: 1-800-637-7922

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Solvent 142-66

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2023
1.13	08/05/2026	100000004966	Date of first issue: 08/14/2014

Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations

49 CFR Road

UN/ID/NA number	: UN 1268
Proper shipping name	: PETROLEUM DISTILLATES, N.O.S.
Class	: CBL
Packing group	: III
Labels	: Combustible Liquid
ERG Code	: 128
Marine pollutant	: no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	: Flammable (gases, aerosols, liquids, or solids) Specific target organ toxicity (single or repeated exposure) Aspiration hazard
-----------------------------	--

SARA 313	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
-----------------	---

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Solvent 142-66

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2023
1.13	08/05/2026	100000004966	Date of first issue: 08/14/2014

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

108-88-3	**Toluene	>= 0 - < 0.1 %
71-43-2	**Benzene	>= 0 - < 0.1 %
100-41-4	**Ethylbenzene	>= 0 - < 0.1 %
91-20-3	**Naphthalene	>= 0 - < 0.1 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

108-88-3	**Toluene	>= 0 - < 0.1 %
71-43-2	**Benzene	>= 0 - < 0.1 %
100-41-4	**Ethylbenzene	>= 0 - < 0.1 %
91-20-3	**Naphthalene	>= 0 - < 0.1 %

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

64742-47-8	Distillates (petroleum), hydrotreated light
71-43-2	**Benzene

Pennsylvania Right To Know

64742-47-8	Distillates (petroleum), hydrotreated light
------------	---

Maine Chemicals of High Concern

108-88-3	**Toluene
71-43-2	**Benzene

Vermont Chemicals of High Concern

108-88-3	**Toluene
71-43-2	**Benzene
100-41-4	**Ethylbenzene

Washington Chemicals of High Concern

108-88-3	**Toluene
71-43-2	**Benzene
100-41-4	**Ethylbenzene

California Prop 65

⚠ WARNING: This product can expose you to chemicals including Distillates (petroleum), hydrotreated light, **Benzene, **Ethylbenzene, **Naphthalene, which is/are known to the State of California to cause cancer, and **Toluene, **Benzene, which is/are known to the State of Califor-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Solvent 142-66

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2023
1.13	08/05/2026	100000004966	Date of first issue: 08/14/2014

nia to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

64742-47-8 Distillates (petroleum), hydrotreated light

California Permissible Exposure Limits for Chemical Contaminants

64742-47-8 Distillates (petroleum), hydrotreated light

The components of this product are reported in the following inventories:

TSCA	:	All substances listed as active on the TSCA inventory
AIIC	:	All components are listed on the inventory, regulatory obligations/restrictions apply
CA. DSL	:	All components of this product are on the Canadian DSL
ENCS	:	Not in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
NZIoC	:	Not in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

Special Notes: : ** Other substances in the product which may present a health or environmental hazard.

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Solvent 142-66


Version
1.13

Revision Date:
08/05/2026

SDS Number:
100000004966

Date of last issue: 11/11/2023
Date of first issue: 08/14/2014

NFPA 704:



HMIS® IV:

HEALTH		1
FLAMMABILITY		2
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Solvent 142-66

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2023
1.13	08/05/2026	100000004966	Date of first issue: 08/14/2014

Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 08/05/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN