

Safety Data Sheet

ETHANOL SDA 3A 200 PROOF

Version 1.7

Revision Date: 11/11/2023

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : ETHANOL SDA 3A 200 PROOF

Recommended use of the chemical and restrictions on use

Recommended use : Solvent

Manufacturer or supplier's details

Company : Univar Solutions USA
Address : 3075 Highland Pkwy Suite 200
 Downers Grove, IL 60515
 United States of America (USA)

Emergency telephone number:

Transport North America: CHEMTREC (1-800-424-9300)

CHEMTREC INTERNATIONAL Tel # 703-527-3887

Additional Information: : Responsible Party: Product Compliance Department
 E-mail: SDSNA@univarsolutions.com
 SDS Requests: 1-855-429-2661
 Website: www.univarsolutions.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 4

Acute toxicity (Dermal) : Category 3

Eye irritation : Category 2A

Reproductive toxicity : Category 1B

Effects on or via lactation :

Specific target organ toxicity - single exposure : Category 1 (Eyes, Blood, Central nervous system)

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

Specific target organ toxicity - repeated exposure : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Safety Data Sheet

ETHANOL SDA 3A 200 PROOF

Version 1.7

Revision Date: 11/11/2023

- Hazard statements : H225 Highly flammable liquid and vapour.
H302 + H332 Harmful if swallowed or if inhaled.
H311 Toxic in contact with skin.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H360 May damage fertility or the unborn child.
H362 May cause harm to breast-fed children.
H370 Causes damage to organs.
H372 Causes damage to organs through prolonged or repeated exposure.
- Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P263 Avoid contact during pregnancy/ while nursing.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Safety Data Sheet
ETHANOL SDA 3A 200 PROOF

Version 1.7

Revision Date: 11/11/2023

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Chemical name	Weight percent
64-17-5	Ethanol	90 - 100
67-56-1	Methanol	5 - 10

Any Concentration shown as a range is due to batch variation.

Synonyms : Ethanol SDA 3A 200 Proof Ferm,**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
Do not induce vomiting without medical advice.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
Flash back possible over considerable distance.

Safety Data Sheet

ETHANOL SDA 3A 200 PROOF

Version 1.7

Revision Date: 11/11/2023

Hazardous combustion products	: Carbon oxides Hazardous decomposition products due to incomplete combustion
Specific extinguishing methods	: Use a water spray to cool fully closed containers.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	: Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
Advice on safe handling	: Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Container may be opened only under exhaust ventilation

Safety Data Sheet

ETHANOL SDA 3A 200 PROOF

Version 1.7

Revision Date: 11/11/2023

Conditions for safe storage : hood.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
: No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
64-17-5	Ethanol	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,900 mg/m3	OSHA P0
		STEL	1,000 ppm	ACGIH
		PEL	1,000 ppm 1,900 mg/m3	CAL PEL
67-56-1	Methanol	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m3	NIOSH REL
		ST	250 ppm 325 mg/m3	NIOSH REL
		TWA	200 ppm 260 mg/m3	OSHA Z-1
		STEL	250 ppm 325 mg/m3	OSHA P0
		TWA	200 ppm 260 mg/m3	OSHA P0
		C	1,000 ppm	CAL PEL
		PEL	200 ppm 260 mg/m3	CAL PEL
		STEL	250 ppm 325 mg/m3	CAL PEL

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.
In the case of vapour formation use a respirator with an approved filter.

Hand protection

Safety Data Sheet

ETHANOL SDA 3A 200 PROOF

Version 1.7

Revision Date: 11/11/2023

Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: Clear, colorless
Odour	: sweet, alcohol-like
Odour Threshold	: No data available
pH	: Not applicable
Freezing Point (Melting point/freezing point)	: Expected -114 °C (-173 °F)
Boiling Point (Boiling point/boiling range)	: 78 °C (172 °F)
Flash point	: 12.8 - 16 °C (55.0 - 61 °F) Method: ASTM D 56, closed cup
Evaporation rate	: 2 (Butyl Acetate = 1)
Flammability (solid, gas)	: No data available
Upper explosion limit	: 19.0 - 20.0 %(V)
Lower explosion limit	: 3.3 - 4 %(V)
Vapour pressure	: 44.59 - 49.99 mmHg @ 20 °C (68 °F)
Relative vapour density	: 1.6(Air = 1.0)
Relative density	: 0.79 - 0.83 @ 15.5 °C (59.9 °F)
Density	: 0.79 g/cm ³ @ 20 °C (68 °F)
Solubility(ies)	
Water solubility	: completely soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: log Pow: -0.35 @ 20 °C (68 °F)
Auto-ignition temperature	: 363 - 400 °C 1,013 hPa
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: 1.08 mm ² /s @ 40 °C (104 °F)

Safety Data Sheet
ETHANOL SDA 3A 200 PROOF

Version 1.7

Revision Date: 11/11/2023

Oxidizing properties : The substance or mixture is not classified as oxidizing.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : No hazards to be specially mentioned.
Vapours may form explosive mixture with air.

Conditions to avoid : Keep away from heat, flame, sparks and other ignition sources.

Incompatible materials : acetyl compounds
Acids
Alkali metals
Ammonia
halogens
Peroxides
Strong oxidizing agents

Hazardous decomposition products : Carbon oxides
Unidentified organic and inorganic compounds.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate: 2,000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : Acute toxicity estimate: Assessment: The component/mixture is toxic after single contact with skin.

Components:**64-17-5:**

Acute oral toxicity : LD50 (Rat): 7,060 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): 124.7 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : Remarks: No data available

67-56-1:

Safety Data Sheet
ETHANOL SDA 3A 200 PROOF

Version 1.7

Revision Date: 11/11/2023

Acute oral toxicity	: Assessment: The component/mixture is toxic after single ingestion.
Acute inhalation toxicity	: Assessment: The component/mixture is toxic after short term inhalation. Remarks: Supporting toxicological evidence is limited for this classification. This harmonized classification will replace the indicated classification due to industry leaders and the EU Harmonized Classification (Annex VII).
Acute dermal toxicity	: Assessment: The component/mixture is toxic after single contact with skin.

Serious eye damage/eye irritation**Product:**

Result: Irritating to eyes.

Components:**64-17-5:**

Species: Rabbit

Result: Irritating to eyes.

Carcinogenicity**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity**Product:**

Reproductive toxicity - Assessment

Presumed human reproductive toxicant, Effects on or via lactation

STOT - single exposure**Product:**

Target Organs: Eyes, Blood, Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 1.

Target Organs: Respiratory system, Central nervous system

Assessment: May cause respiratory irritation., May cause drowsiness or dizziness.

Safety Data Sheet

ETHANOL SDA 3A 200 PROOF

Version 1.7

Revision Date: 11/11/2023

Components:

67-56-1:

Target Organs: Eyes, Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 1.

STOT - repeated exposure

Product:

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

Safety Data Sheet

ETHANOL SDA 3A 200 PROOF

Version 1.7

Revision Date: 11/11/2023

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Univar Solutions ChemCare: 1-800-637-7922
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

DOT (Department of Transportation):

UN1170, Ethanol solutions, 3, II

IATA (International Air Transport Association):

UN1170, Ethanol solution, 3, II

IMDG (International Maritime Dangerous Goods):

UN1170, ETHANOL SOLUTION, 3, II, Flash Point: 12.8 - 16 °C (55.0 - 61 °F)

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Methanol	67-56-1	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards

- : Flammable (gases, aerosols, liquids, or solids)
Acute toxicity (any route of exposure)
Serious eye damage or eye irritation
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)

SARA 302

- : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

Safety Data Sheet

ETHANOL SDA 3A 200 PROOF

Version 1.7

Revision Date: 11/11/2023

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

67-56-1 Methanol

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

67-56-1 Methanol

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

64-17-5 Ethanol

67-56-1 Methanol

Clean Water Act

The following Hazardous Substances are listed under the U.S. Clean Water Act, Section 311, Table 116.4A:

75-07-0 Acetaldehyde

The following Hazardous Chemicals are listed under the U.S. Clean Water Act, Section 311, Table 117.3:

75-07-0 Acetaldehyde

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

Massachusetts Right To Know

64-17-5 Ethanol

67-56-1 Methanol

75-07-0 Acetaldehyde

Pennsylvania Right To Know

64-17-5 Ethanol

67-56-1 Methanol

75-07-0 Acetaldehyde

California Prop 65

⚠ WARNING: This product can expose you to chemicals including Acetaldehyde, which is/are known to the State of California to cause cancer, and Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

ISHL : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

Safety Data Sheet

ETHANOL SDA 3A 200 PROOF


Version 1.7

Revision Date: 11/11/2023

IECSC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

NFPA:



HMIS III:

HEALTH	2*
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Univar Solutions Product Compliance Department (1-855-429-2661) SDSNA@univarsolutions.com.

Revision Date : 11/11/2023

Legacy SDS: : R0020122

Material number:

16192171, 16154117, 16154028, 16154783, 16142563, 16142587, 16134513, 16133680, 16132845, 16129051, 16127972, 16126071, 16056017, 703264, 160938, 131694, 132684, 160169, 161419, 117615, 132625, 146118, 161058, 161045, 161460, 161478

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level

Safety Data Sheet

ETHANOL SDA 3A 200 PROOF

Version 1.7

Revision Date: 11/11/2023

EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		