



SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY

Product name: FOAMYSENSE™ N750 Polymer

Issue Date: 06/08/2022

Print Date: 06/09/2022

THE DOW CHEMICAL COMPANY encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: FOAMYSENSE™ N750 Polymer

Recommended use of the chemical and restrictions on use

Identified uses: Thickener. Binder. Lubricant. Processing aid. We recommend that you use this product in a manner consistent with the listed use. If your intended use is not consistent with the stated use, please contact your sales or technical service representative.

COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY
2211 H.H. DOW WAY
MIDLAND MI 48674
UNITED STATES

Customer Information Number:

800-258-2436
SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: CHEMTREC +1 800-424-9300

Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Combustible dust

Label elements

Signal word: **WARNING!**

Hazards

May form combustible dust concentrations in air.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture.

Component	CASRN	Concentration
Poly(ethylene oxide)	25322-68-3	>= 95.0 - <= 100.0 %
Fumed silica (generic)	112945-52-5	<= 3.0 %
Calcium as mixed salts	Not available	< 1.0 %

4. FIRST AID MEASURES

Description of first aid measures

General advice:

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: No emergency medical treatment necessary.

Skin contact: Wash off with plenty of water.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Water fog or fine spray.. Dry chemical fire extinguishers.. Carbon dioxide fire extinguishers.. Foam.. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective..

Unsuitable extinguishing media: No data available

Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating.. Combustion products may include and are not limited to:.. Carbon monoxide.. Carbon dioxide..

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation.. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.. Do not permit dust to accumulate. When suspended in air dust can pose an explosion hazard. Minimize ignition sources. If dust layers are exposed to elevated temperatures, spontaneous combustion may occur.. Pneumatic conveying and other mechanical handling operations can generate combustible dust. To reduce the potential for dust explosions, electrically bond and ground equipment and do not permit dust to accumulate. Dust can be ignited by static discharge..

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry.. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed.. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles.. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container.. Burning liquids may be extinguished by dilution with water.. Do not use direct water stream. May spread fire.. Hand held dry chemical or carbon dioxide extinguishers may be used for small fires.. Dust explosion hazard may result from forceful application of fire extinguishing agents.. Move container from fire area if this is possible without hazard.. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage..

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves).. If protective equipment is not available or not used, fight fire from a protected location or safe distance..

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Isolate area. Spilled material may cause a slipping hazard. Keep unnecessary and unprotected personnel from entering the area. Material becomes slippery when wet. Refer to section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Contain spilled material if possible. Collect with vacuum equipment. Collect in suitable and properly labeled containers. Attempt to neutralize by adding materials such as Soda ash. See Section 13, Disposal Considerations, for additional information.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with eyes. Wash thoroughly after handling. No smoking, open flames or sources of ignition in handling and storage area. Good housekeeping and controlling of dusts are necessary for safe handling of product. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Keep away from heat, sparks and flame. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Conditions for safe storage: Keep in a dry place. Store indoors. Store in a closed container. Store away from sources of heat or ignition. See Section 10 for more specific information.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Poly(ethylene oxide)	US WEEL	TWA aerosol	10 mg/m3
Fumed silica (generic)	OSHA Z-3	TWA	20 million particles per cubic foot
	Further information: a: Based on impinger samples counted by light-field techniques.; mppcf X 35.3 = million particles per cubic meter = particles per c.c		
	OSHA Z-3	TWA Dust	20 Million particles per cubic foot, Silica
	OSHA Z-3	TWA Dust	80 mg/m3 / %SiO ₂ , Silica

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields).

Skin protection

Hand protection: Chemical protective gloves should not be needed when handling this material. Consistent with general hygienic practice for any material, skin contact should be minimized.

Other protection: No precautions other than clean body-covering clothing should be needed.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator. The following should be effective types of air-purifying respirators: Particulate filter.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	Powder
Color	White to off-white
Odor	Ammoniacal
Odor Threshold	Not relevant
pH	8 - 10 <i>pH Electrode</i> Aqueous solution
Melting point/range	<i>Thermal analysis</i> Decomposes without melting.
Freezing point	Solid.
Boiling point (760 mmHg)	Not applicable to solids
Flash point	closed cup Not applicable to solids
Evaporation Rate (Butyl Acetate = 1)	Not applicable to solids
Flammability (solid, gas)	May form combustible dust concentrations in air.
Lower explosion limit	Not applicable to solids
Upper explosion limit	Not applicable to solids
Vapor Pressure	Solid.
Relative Vapor Density (air = 1)	Not applicable to solids
Relative Density (water = 1)	1.15 - 1.26 <i>Volume Displacement</i>
Water solubility	completely soluble
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	345 °C (653 °F) <i>Other guidelines</i>
Decomposition temperature	> 300 °C (> 572 °F) <i>Differential Scanning Calorimetry (DSC)</i> Decomposes on heating.
Kinematic Viscosity	Solid.
Explosive properties	Not impact sensitive.
Oxidizing properties	No
Molecular weight	No test data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: No data available

Chemical stability: Thermally stable at typical use temperatures.

Possibility of hazardous reactions: Polymerization will not occur.

Conditions to avoid: Product can oxidize at elevated temperatures. Generation of gas during decomposition can cause pressure in closed systems. Avoid static discharge. Avoid moisture. Avoid direct sunlight or ultraviolet sources.

Incompatible materials: Avoid contact with: Strong acids. Strong bases. Strong oxidizers.

Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials.. Decomposition products can include and are not limited to:.. Carbon dioxide.. Alcohols.. Ethers.. Hydrocarbons.. Ketones.. Polymer fragments..

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

Acute Toxicity Endpoints:

Not classified based on available information.

Acute oral toxicity

Information for the Product:

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

Typical for this family of materials.

LD50, Rat, > 4,000 mg/kg Estimated. No deaths occurred at this concentration.

Information for components:

Poly(ethylene oxide)

Typical for this family of materials. LD50, Rat, > 10,000 mg/kg

Fumed silica (generic)

LD50, Rat, > 10,000 mg/kg

Calcium as mixed salts

Single dose oral LD50 has not been determined.

Acute dermal toxicity

Information for the Product:

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Typical for this family of materials.

LD50, Rabbit, > 5,000 mg/kg Estimated.

Information for components:

Poly(ethylene oxide)

Typical for this family of materials. LD50, Rabbit, > 20,000 mg/kg

Fumed silica (generic)

LD50, Rabbit, > 5,000 mg/kg

Calcium as mixed salts

The dermal LD50 has not been determined.

Acute inhalation toxicity

Information for the Product:

No adverse effects are anticipated from inhalation.

As product: The LC50 has not been determined.

Information for components:

Poly(ethylene oxide)

Typical for this family of materials. LC50, Rat, 6 Hour, dust/mist, > 2.5 mg/l No deaths occurred at this concentration.

Fumed silica (generic)

The LC50 has not been determined.

Calcium as mixed salts

The LC50 has not been determined.

Skin corrosion/irritation

Not classified based on available information.

Information for the Product:

Based on product testing:
Essentially nonirritating to skin.

Information for components:

Poly(ethylene oxide)

Prolonged exposure not likely to cause significant skin irritation.
May cause more severe response if skin is abraded (scratched or cut).

Fumed silica (generic)

Essentially nonirritating to skin.
Mechanical injury only.

Serious eye damage/eye irritation

Not classified based on available information.

Information for the Product:

Based on product testing:
May cause slight eye irritation.
Corneal injury is unlikely.

Information for components:

Poly(ethylene oxide)

May cause slight temporary eye irritation.
Corneal injury is unlikely.

Fumed silica (generic)

Solid or dust may cause irritation or corneal injury due to mechanical action.

Sensitization

For skin sensitization:

Not classified based on available information.

For respiratory sensitization:

Not classified based on available information.

Information for the Product:

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:
No relevant data found.

Information for components:

Poly(ethylene oxide)

For this family of materials:
Did not cause allergic skin reactions when tested in humans.
For this family of materials, sensitization studies done in guinea pigs have been negative.

For respiratory sensitization:
No relevant data found.

Fumed silica (generic)

For skin sensitization:
No relevant data found.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Not classified based on available information.

Information for the Product:

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Information for components:

Poly(ethylene oxide)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Fumed silica (generic)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Aspiration Hazard

Not classified based on available information.

Information for the Product:

Based on physical properties, not likely to be an aspiration hazard.

Information for components:

Poly(ethylene oxide)

Based on physical properties, not likely to be an aspiration hazard.

Fumed silica (generic)

Based on physical properties, not likely to be an aspiration hazard.

Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Not classified based on available information.

Information for the Product:

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Information for components:

Poly(ethylene oxide)

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Recent findings of kidney failure and death in burn patients, as well as some studies using animal burn models, suggest that polyethylene glycol may have been a factor.

The use of topical applications containing this material may not be appropriate in severely burned patients.

Fumed silica (generic)

No relevant data found.

Carcinogenicity

Not classified based on available information.

Information for the Product:

Did not cause cancer in laboratory animals.

Information for components:

Poly(ethylene oxide)

Polyethylene glycols did not cause cancer in long-term animal studies.

Fumed silica (generic)

No relevant data found.

Teratogenicity

Not classified based on available information.

Information for the Product:

For the major component(s): Did not cause birth defects or any other fetal effects in laboratory animals.

Information for components:

Poly(ethylene oxide)

For this family of materials: Did not cause birth defects or any other fetal effects in laboratory animals.

Fumed silica (generic)

No relevant data found.

Reproductive toxicity

Not classified based on available information.

Information for the Product:

In animal studies, did not interfere with reproduction.

Information for components:

Poly(ethylene oxide)

For this family of materials: In animal studies, did not interfere with reproduction.

Fumed silica (generic)

No relevant data found.

Mutagenicity

Not classified based on available information.

Information for the Product:

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Information for components:

Poly(ethylene oxide)

For this family of materials: In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Fumed silica (generic)

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

For this family of materials:

LC50, Pimephales promelas (fathead minnow), static test, 96 Hour, > 1,000 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

For this family of materials:

LC50, Daphnia magna (Water flea), static test, 48 Hour, > 100 mg/l, OECD Test Guideline 202 or Equivalent

Toxicity to bacteria

For this family of materials:

IC50, Bacteria, 16 Hour, Respiration rates., > 5,000 mg/l

Persistence and degradability

Biodegradability: For this family of materials: Material has inherent, ultimate biodegradability with pre-adaptation according to OECD test (s) guidelines (reaches > 60 or 70% biodegradation in OECD test(s).

10-day Window: Not applicable

Biodegradation: 77.7 %

Exposure time: 56 d

Method: OECD Test Guideline 302B or Equivalent

Theoretical Oxygen Demand: 2.54 mg/mg

Chemical Oxygen Demand: 1.83 mg/mg

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	0 - 3 %
10 d	0 - 3 %
20 d	5 - 6 %

Bioaccumulative potential

Bioaccumulation: For this family of materials: No bioconcentration is expected because of the relatively high molecular weight (MW greater than 1000).

Mobility in soil

No relevant data found.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device. Landfill.

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

**Transport in bulk
according to Annex I or II
of MARPOL 73/78 and the
IBC or IGC Code**

Not regulated for transport
Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Combustible dust

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Worker and Community Right-To-Know Act:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

California Prop. 65

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Revision

Identification Number: 99176306 / A001 / Issue Date: 06/08/2022 / Version: 5.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

OSHA Z-3	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
TWA	8-hour time weighted average
US WEEL	USA. Workplace Environmental Exposure Levels (WEEL)

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of

Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US