

SAFETY DATA SHEET



D.E.H.® 39 Epoxy Hardener

Version	Revision Date:	SDS Number:	Date of last issue: 06-16-2017
12.0	07-13-2020	101234570	Date of first issue: 07-13-2020

BLUE CUBE OPERATIONS LLC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

SECTION 1. IDENTIFICATION

Product name : D.E.H.® 39 Epoxy Hardener

Product code : 000000001000000520

Manufacturer or supplier's details

Company name of supplier : BLUE CUBE OPERATIONS LLC

Address : 190 CARONDELET PLAZA, SUITE 1530
CLAYTON MO 63105-3467

Telephone : (844) 238-3445

E-mail address : INFO@OLIN.COM

24-Hour Emergency Contact : +1 800 424 9300

Local Emergency Contact : 1-800-424-9300

Recommended use of the chemical and restrictions on use

Identified uses : Curing agent.
Used in applications such as:
Adhesives.
Casting.
Tooling.
Civil engineering.
Composites.
Marine and protective coatings.
Potting and encapsulation.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Acute toxicity (Dermal) : Category 3

Skin corrosion : Category 1B

Serious eye damage : Category 1

Skin sensitization : Sub-category 1B

Reproductive toxicity : Category 1B

D.E.H.® 39 Epoxy Hardener

Version	Revision Date:	SDS Number:	Date of last issue: 06-16-2017
12.0	07-13-2020	101234570	Date of first issue: 07-13-2020

Effects on or via lactation

Specific target organ systemic toxicity - repeated exposure (Inhalation) : Category 1 (Respiratory Tract)

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : Toxic in contact with skin.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
May damage fertility or the unborn child.
May cause harm to breast-fed children.
Causes damage to organs (Respiratory Tract) through prolonged or repeated exposure if inhaled.

Precautionary Statements : **Prevention:**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
Avoid contact during pregnancy/ while nursing.
Wash skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
IF exposed or concerned: Get medical advice/ attention.
If skin irritation or rash occurs: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.

Storage:

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

D.E.H.® 39 Epoxy Hardener

Version 12.0	Revision Date: 07-13-2020	SDS Number: 101234570	Date of last issue: 06-16-2017 Date of first issue: 07-13-2020
-----------------	------------------------------	--------------------------	---

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	: Substance
Substance name	: AMINOETHYLPIPERAZINE HIGH PURITY
CAS-No.	: 140-31-8
Synonyms	: 2-Piperazin-1-ylethylamine

Components

Chemical name	CAS-No.	Concentration (% w/w)
Aminoethylpiperazine	140-31-8	>= 98
Diethylenetriamine	111-40-0	< 2
Aminoethylethanolamine	111-41-1	< 0.5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled	: Move person to fresh air; if effects occur, consult a physician.
In case of skin contact	: Immediate continued and thorough washing in flowing water for at least 30 minutes is imperative while removing contaminated clothing. Prompt medical consultation is essential. Wash clothing before reuse. Properly dispose of leather items such as shoes, belts, and watchbands. Suitable emergency safety shower facility should be immediately available.
In case of eye contact	: Wash immediately and continuously with flowing water for at least 30 minutes. Remove contact lenses after the first 5 minutes and continue washing. Obtain prompt medical consultation, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.
If swallowed	: Do not induce vomiting. Give one cup (8 ounces or 240 ml) of water or milk if available and transport to a medical facility. Do not give anything by mouth unless the person is fully conscious.
Most important symptoms and effects, both acute and delayed	: Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.
Protection of first-aiders	: First Aid responders should pay attention to self-protection

D.E.H.® 39 Epoxy Hardener

Version 12.0	Revision Date: 07-13-2020	SDS Number: 101234570	Date of last issue: 06-16-2017 Date of first issue: 07-13-2020
-----------------	------------------------------	--------------------------	---

and use the recommended protective clothing (chemical resistant gloves, splash protection).
If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Notes to physician : Chemical eye burns may require extended irrigation. Obtain prompt consultation, preferably from an ophthalmologist. If burn is present, treat as any thermal burn, after decontamination.
Due to irritant properties, swallowing may result in burns/ulceration of mouth, stomach and lower gastrointestinal tract with subsequent stricture. Aspiration of vomitus may cause lung injury. Suggest endotracheal/esophageal control if lavage is done.
No specific antidote.
Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water fog or fine spray.
Dry chemical fire extinguishers.
Carbon dioxide fire extinguishers.
Foam.
Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Unsuitable extinguishing media : Do not use direct water stream.
May spread fire.

Specific hazards during fire fighting : Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

Hazardous combustion products : During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating.
Combustion products may include and are not limited to:
Nitrogen oxides.
Carbon monoxide.
Carbon dioxide.

Further information : Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed.
Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container.
Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire.
Move container from fire area if this is possible without ha-

D.E.H.® 39 Epoxy Hardener

Version 12.0	Revision Date: 07-13-2020	SDS Number: 101234570	Date of last issue: 06-16-2017 Date of first issue: 07-13-2020
-----------------	------------------------------	--------------------------	---

zard.

Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.

Special protective equipment for fire-fighters : Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves).
Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location.
For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate area.
Only trained and properly protected personnel must be involved in clean-up operations.
Ventilate area of leak or spill.
Keep upwind of spill.
Refer to section 7, Handling, for additional precautionary measures.
Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions : Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up : Small spills:
Absorb with materials such as:
Clay.
Dirt.
Milsorb®.
Sand.
Do NOT use absorbent materials such as:
Moist organic absorbents.
Peat moss.
Ground corn cobs.
Cellulose.
Sawdust.
Remove with shovel.
Collect in suitable and properly labeled containers.
Large spills:
Dike area to contain spill.
Ground and bond all containers and handling equipment.
Knock down and dilute vapors with water fog or spray.
Collect with vacuum equipment.
Wash the spill site with large quantities of water.
See Section 13, Disposal Considerations, for additional information.

D.E.H.® 39 Epoxy Hardener

Version 12.0 Revision Date: 07-13-2020 SDS Number: 101234570 Date of last issue: 06-16-2017
 Date of first issue: 07-13-2020

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not get in eyes, on skin, on clothing.
 Avoid prolonged or repeated contact with skin.
 Do not swallow.
 Avoid breathing vapor.
 Keep container closed.
 Use with adequate ventilation.
 Wash thoroughly after handling.
 Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.
 See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.
- Conditions for safe storage : Store in the following material(s):
 Stainless steel.
 Avoid contact with metals such as:
 Brass.
 Bronze.
 Copper.
 Copper alloys.
 Protect from atmospheric moisture.
- Recommended storage temperature : 32 - 86 °F / 0 - 30 °C
- Storage period : 24 Months

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Diethylenetriamine	111-40-0	TWA	1 ppm	ACGIH
		TWA	1 ppm 4 mg/m ³	OSHA P0
Aminoethylethanolamine	111-41-1	TWA	0.05 mg/m ³	OLIN OEL
Further information: Absorbed via Skin, Skin Sensitizer				

- Engineering measures** : Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations.
 Local exhaust ventilation may be necessary for some operations.

Personal protective equipment

- Filter type : The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

SAFETY DATA SHEET



D.E.H.® 39 Epoxy Hardener

Version 12.0	Revision Date: 07-13-2020	SDS Number: 101234570	Date of last issue: 06-16-2017 Date of first issue: 07-13-2020
-----------------	------------------------------	--------------------------	---

Respiratory protection : Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if handling at elevated temperatures without sufficient ventilation, use an approved air-purifying respirator.

Hand protection

Remarks : Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Polyethylene. Ethyl vinyl alcohol laminate ('EVAL'). Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ('latex'). Neoprene. Nitrile/butadiene rubber ('nitrile' or 'NBR'). Polyvinyl alcohol ('PVA'). Polyvinyl chloride ('PVC' or 'vinyl'). Viton. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Eye protection : Use chemical goggles.

Skin and body protection : Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Liquid.
Color	: Colorless
Odor	: Ammoniacal
Odor Threshold	: No test data available
pH	: 13 Method: Literature
Melting point/range	: Not applicable to liquids
Freezing point	: 1 °F / -17 °C Method: Literature
Boiling point/boiling range	: 430 °F / 221 °C

SAFETY DATA SHEET



D.E.H.® 39 Epoxy Hardener

Version 12.0	Revision Date: 07-13-2020	SDS Number: 101234570	Date of last issue: 06-16-2017 Date of first issue: 07-13-2020
-----------------	------------------------------	--------------------------	---

	Method: Literature
Flash point	: 216 °F / 102 °C
	Method: Pensky-Martens Closed Cup ASTM D 93, closed cup
Evaporation rate	: No test data available
Flammability (solid, gas)	: Not applicable to liquids
Upper explosion limit / Upper flammability limit	: No test data available
Lower explosion limit / Lower flammability limit	: 1.8 %(V) (284 °F / 140 °C) Method: Literature
Vapor pressure	: < 0.01 mmHg (68 °F / 20 °C) Method: Literature
Relative vapor density	: 4.5 Method: Literature
Relative density	: 0.987 (68 °F / 20 °C) Method: Literature
Density	: 0.984 g/cm3 (68 °F / 20 °C) Method: Literature
Partition coefficient: n-octanol/water	: log Pow: -1.48 Method: Measured
Autoignition temperature	: No test data available
Decomposition temperature	: No test data available
Viscosity	
Viscosity, kinematic	: 12.1 mm2/s (77 °F / 25 °C) Method: Literature
Explosive properties	: Not explosive
Oxidizing properties	: No
Molecular weight	: No data available

Note: These are the Reference Points for these Physical Properties listed above, unless otherwise noted in their respective Physical Property value information: Boiling Point at 760 mmHg; Evaporation Rate Butyl Acetate = 1; Relative Vapor Density Air = 1; and Relative Density Water = 1.
NOTE: The physical data presented above are typical values and should not be construed as a specification.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No data available
------------	---------------------

D.E.H.® 39 Epoxy Hardener

Version 12.0	Revision Date: 07-13-2020	SDS Number: 101234570	Date of last issue: 06-16-2017 Date of first issue: 07-13-2020
-----------------	------------------------------	--------------------------	---

-
- | | | |
|------------------------------------|---|--|
| Chemical stability | : | Thermally stable at typical use temperatures. |
| Possibility of hazardous reactions | : | Polymerization will not occur. |
| Conditions to avoid | : | Exposure to elevated temperatures can cause product to decompose.
Generation of gas during decomposition can cause pressure in closed systems.
Reaction with carbon dioxide may form an amine carbamate.
Smoke may be generated depending on vapor pressure of mixture.
Product absorbs carbon dioxide from the air. |
| Incompatible materials | : | Avoid contact with oxidizing materials.
Avoid contact with:
Acids.
Acrylates.
Alcohols.
Aldehydes.
Halogenated hydrocarbons.
Ketones.
Nitrites.
Avoid contact with metals such as:
Brass.
Bronze.
Copper.
Copper alloys.
Avoid contact with absorbent materials such as:
Ground corn cobs.
Moist organic absorbents.
Peat moss.
Sawdust. |
| Hazardous decomposition products | : | Decomposition products depend upon temperature, air supply and the presence of other materials.
Decomposition products can include and are not limited to:
Ammonia.
Ethylenediamine.
Volatile amines. |

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Product:**

- | | | |
|---------------------------|---|--|
| Acute oral toxicity | : | Remarks: Low toxicity if swallowed.
Swallowing may result in gastrointestinal irritation or ulceration.
Swallowing may result in burns of the mouth and throat.

LD50 (Rat): 2,140 mg/kg |
| Acute inhalation toxicity | : | Remarks: At room temperature, exposure to vapor is minimal |

D.E.H.® 39 Epoxy Hardener

Version 12.0	Revision Date: 07-13-2020	SDS Number: 101234570	Date of last issue: 06-16-2017 Date of first issue: 07-13-2020
-----------------	------------------------------	--------------------------	---

due to low volatility; vapor from heated material may cause respiratory irritation.

Exposure time: 8 h
Test atmosphere: vapor
Symptoms: No deaths occurred following exposure to a saturated atmosphere.
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: The LC50 has not been determined.

Acute dermal toxicity : Remarks: Prolonged or widespread skin contact may result in absorption of harmful amounts.

LD50 (Rabbit): 866 mg/kg

Components:**Aminoethylpiperazine:**

Acute oral toxicity : LD50 (Rat): 2,140 mg/kg

Acute inhalation toxicity : Exposure time: 8 h
Test atmosphere: vapor
Symptoms: No deaths occurred following exposure to a saturated atmosphere.
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: The LC50 has not been determined.

Acute dermal toxicity : LD50 (Rabbit): 866 mg/kg

Diethylenetriamine:

Acute oral toxicity : LD50 (Rat): 1,620 mg/kg

Acute inhalation toxicity : Remarks: Prolonged exposure to aerosol/mist may cause serious adverse effects, even death.
Excessive exposure may cause severe irritation to upper respiratory tract (nose and throat) and lungs.

LC50 (Rat): > 0.07 - < 0.3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The component/mixture is highly toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): 1,045 mg/kg

Aminoethylethanolamine:

Acute oral toxicity : LD50 (Rat): 2,150 mg/kg

Acute inhalation toxicity : Remarks: At room temperature, exposure to vapor is minimal due to low volatility; vapor from heated material may cause respiratory irritation.

SAFETY DATA SHEET



D.E.H.® 39 Epoxy Hardener

Version	Revision Date:	SDS Number:	Date of last issue: 06-16-2017
12.0	07-13-2020	101234570	Date of first issue: 07-13-2020

Based on the available data, narcotic effects were not observed.

Remarks: The LC50 has not been determined.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Symptoms: No deaths occurred at this concentration.
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Product:

Result : Causes burns.
Remarks : Brief contact may cause skin burns. Symptoms may include pain, severe local redness and tissue damage.

Remarks : Classified as corrosive to the skin according to DOT guidelines.

Components:

Aminoethylpiperazine:

Result : Causes burns.
Remarks : Brief contact may cause skin burns. Symptoms may include pain, severe local redness and tissue damage.

Remarks : Classified as corrosive to the skin according to DOT guidelines.

Diethylenetriamine:

Result : Causes burns.
Remarks : Brief contact may cause severe skin burns. Symptoms may include pain, severe local redness and tissue damage.

Remarks : Classified as corrosive to the skin according to DOT guidelines.

Aminoethylethanolamine:

Result : Causes burns.
Remarks : Avoid all skin contact.
Brief contact may cause skin burns. Symptoms may include pain, severe local redness and tissue damage.
May cause more severe response on covered skin (under clothing, gloves).

Remarks : Classified as corrosive to the skin according to DOT guidelines.

D.E.H.® 39 Epoxy Hardener

Version	Revision Date:	SDS Number:	Date of last issue: 06-16-2017
12.0	07-13-2020	101234570	Date of first issue: 07-13-2020

Serious eye damage/eye irritation**Product:**

Result	: Corrosive
Remarks	: May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Components:**Aminoethylpiperazine:**

Result	: Corrosive
Remarks	: May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Diethylenetriamine:

Result	: Corrosive
Remarks	: May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur. Vapor may cause eye irritation experienced as mild discomfort and redness.

Aminoethylethanolamine:

Result	: Corrosive
Remarks	: May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Respiratory or skin sensitization**Product:**

Assessment	: The product is a skin sensitizer, sub-category 1B.
Remarks	: Skin contact may cause an allergic skin reaction. Has caused allergic skin reactions when tested in guinea pigs. Individuals having an allergic skin reaction to this product may have an allergic skin reaction to similar material(s). The similar material(s) is/are: Triethylenetetramine (TETA). Aminoethylethanolamine (AEEA). Piperazine.

Remarks	: For respiratory sensitization: No relevant data found.
---------	---

Components:**Aminoethylpiperazine:**

Assessment	: The product is a skin sensitizer, sub-category 1B.
Remarks	: Skin contact may cause an allergic skin reaction. Has caused allergic skin reactions when tested in guinea pigs.

D.E.H.® 39 Epoxy Hardener

Version	Revision Date:	SDS Number:	Date of last issue: 06-16-2017
12.0	07-13-2020	101234570	Date of first issue: 07-13-2020

Individuals having an allergic skin reaction to this product may have an allergic skin reaction to similar material(s).
The similar material(s) is/are:
Triethylenetetramine (TETA).
Aminoethylethanolamine (AEEA).
Piperazine.

Remarks : For respiratory sensitization:
No relevant data found.

Diethylenetriamine:

Assessment : The product is a skin sensitizer, sub-category 1B.
Remarks : Has caused allergic skin reactions in humans.
Individuals having an allergic skin reaction to this product may have an allergic skin reaction to similar material(s).
The similar material(s) is/are:
Ethylenediamine (EDA).
Triethylenetetramine (TETA).
Piperazine.
Tetraethylenepentamine (TEPA).
Aminoethylethanolamine (AEEA).
Aminoethylpiperazine (AEP).
Has demonstrated the potential for contact allergy in mice.
Has caused allergic skin reactions when tested in guinea pigs.

Remarks : For respiratory sensitization:
No specific, relevant data available for assessment.

Aminoethylethanolamine:

Assessment : The product is a skin sensitizer, sub-category 1A.
Remarks : Skin contact may cause an allergic skin reaction.
Individuals who have had an allergic skin reaction to similar materials may have an allergic skin reaction to this product.
The similar material(s) is/are:
Triethylenetetramine (TETA).
Has caused allergic skin reactions when tested in guinea pigs.
Has demonstrated the potential for contact allergy in mice.

Remarks : For respiratory sensitization:
No specific, relevant data available for assessment.

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Remarks: In vitro genetic toxicity studies were negative in some cases and positive in other cases.
Animal genetic toxicity studies were inconclusive

Components:**Aminoethylpiperazine:**

Genotoxicity in vitro : Remarks: In vitro genetic toxicity studies were negative in

D.E.H.® 39 Epoxy Hardener

Version 12.0	Revision Date: 07-13-2020	SDS Number: 101234570	Date of last issue: 06-16-2017 Date of first issue: 07-13-2020
-----------------	------------------------------	--------------------------	---

some cases and positive in other cases.
Animal genetic toxicity studies were inconclusive

Diethylenetriamine:

Genotoxicity in vitro : Remarks: In vitro genetic toxicity studies were negative.
Animal genetic toxicity studies were negative.

Aminoethylethanolamine:

Genotoxicity in vitro : Remarks: In vitro genetic toxicity studies were negative.
Animal genetic toxicity studies were negative.

Carcinogenicity**Product:**

Remarks : No relevant data found.

Components:**Aminoethylpiperazine:**

Remarks : No relevant data found.

Diethylenetriamine:

Remarks : Did not cause cancer in laboratory animals.

Aminoethylethanolamine:

Remarks : No relevant data found.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity**Product:**

Effects on fertility : Remarks: Contains component(s) which have interfered with fertility in animal studies.

Effects on fetal development : Remarks: Has been toxic to the fetus in laboratory animal tests.

Components:**Aminoethylpiperazine:**

Effects on fertility : Remarks: Contains component(s) which have interfered with fertility in animal studies.

D.E.H.® 39 Epoxy Hardener

Version	Revision Date:	SDS Number:	Date of last issue: 06-16-2017
12.0	07-13-2020	101234570	Date of first issue: 07-13-2020

Effects on fetal development : Remarks: Has been toxic to the fetus in laboratory animal tests.

Reproductive toxicity - Assessment : Suspected human reproductive toxicant

Diethylenetriamine:

Effects on fertility : Remarks: In animal studies, did not interfere with fertility.

Effects on fetal development : Remarks: Has been toxic to the fetus in laboratory animals at doses toxic to the mother.
Did not cause birth defects in laboratory animals.

Aminoethylethanolamine:

Effects on fertility : Remarks: In animal studies, has been shown to interfere with fertility.

Effects on fetal development : Remarks: Has caused birth defects in laboratory animals.
Has been toxic to the fetus in laboratory animal tests.

Reproductive toxicity - Assessment : Presumed human reproductive toxicant
Effects on or via lactation

STOT-single exposure**Product:**

Assessment : Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Components:**Aminoethylpiperazine:**

Assessment : Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Diethylenetriamine:

Routes of exposure : Inhalation
Target Organs : Respiratory system
Assessment : May cause respiratory irritation.

Aminoethylethanolamine:

Routes of exposure : Inhalation
Target Organs : Respiratory Tract
Assessment : May cause respiratory irritation.

D.E.H.® 39 Epoxy Hardener

Version	Revision Date:	SDS Number:	Date of last issue: 06-16-2017
12.0	07-13-2020	101234570	Date of first issue: 07-13-2020

STOT-repeated exposure**Components:****Aminoethylpiperazine:**

Routes of exposure	:	Inhalation
Target Organs	:	Respiratory Tract
Assessment	:	Causes damage to organs through prolonged or repeated exposure.

Repeated dose toxicity**Product:**

Remarks	:	In animals, effects have been reported on the following organs: Respiratory tract.
---------	---	---

Components:**Aminoethylpiperazine:**

Remarks	:	In animals, effects have been reported on the following organs: Respiratory tract.
---------	---	---

Diethylenetriamine:

Remarks	:	Based on available data, repeated exposures are not anticipated to cause additional significant adverse effects.
---------	---	--

Aminoethylethanolamine:

Remarks	:	In animals, effects have been reported on the following organs: Gastrointestinal tract. Kidney. Repeated skin application to laboratory animals did not produce systemic toxicity.
---------	---	---

Aspiration toxicity**Product:**

Aspiration into the lungs may occur during ingestion or vomiting, causing tissue damage or lung injury.

Components:**Aminoethylpiperazine:**

Aspiration into the lungs may occur during ingestion or vomiting, causing tissue damage or lung injury.

Diethylenetriamine:

Based on physical properties, not likely to be an aspiration hazard.

D.E.H.® 39 Epoxy Hardener

Version 12.0	Revision Date: 07-13-2020	SDS Number: 101234570	Date of last issue: 06-16-2017 Date of first issue: 07-13-2020
-----------------	------------------------------	--------------------------	---

Aminoethylethanolamine:

Aspiration into the lungs may occur during ingestion or vomiting, causing tissue damage or lung injury.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Toxicity to fish	:	Remarks: Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested). LC50 (Pimephales promelas (fathead minnow)): 2,190 mg/l Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 203 or Equivalent
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 58 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202 or Equivalent GLP: yes
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l End point: Growth rate inhibition Exposure time: 72 h Method: OECD Test Guideline 201 or Equivalent

Components:**Aminoethylpiperazine:**

Toxicity to fish	:	Remarks: Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested). LC50 (Pimephales promelas (fathead minnow)): 2,190 mg/l Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 203 or Equivalent
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 58 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202 or Equivalent GLP: yes
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l

D.E.H.® 39 Epoxy Hardener

Version	Revision Date:	SDS Number:	Date of last issue: 06-16-2017
12.0	07-13-2020	101234570	Date of first issue: 07-13-2020

End point: Growth rate inhibition
 Exposure time: 72 h
 Method: OECD Test Guideline 201 or Equivalent

Diethylenetriamine:

Toxicity to fish : Remarks: Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested).

LC50 (*Poecilia reticulata* (guppy)): 430 mg/l
 Exposure time: 96 h
 Test Type: semi-static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 16 mg/l
 Exposure time: 48 h
 Test Type: static test
 Method: DIN 38412

Toxicity to algae/aquatic plants : ErC50 (*Pseudokirchneriella subcapitata* (green algae)): 1,164 mg/l
 End point: Growth rate inhibition
 Exposure time: 72 h
 Test Type: static test
 Method: OECD Test Guideline 201 or Equivalent

Toxicity to fish (Chronic toxicity) : NOEC (Fish): > 10 mg/l
 End point: growth
 Exposure time: 28 d
 Test Type: semi-static test

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (*Daphnia magna* (Water flea)): 5.6 mg/l
 End point: number of offspring
 Exposure time: 21 d
 Test Type: semi-static test

MATC (Maximum Acceptable Toxicant Level) (*Daphnia magna* (Water flea)): 7.95 mg/l
 End point: number of offspring
 Exposure time: 21 d
 Test Type: semi-static test

Toxicity to microorganisms : EC50 (Bacteria): > 5,000 mg/l
 Exposure time: 16 h
 Test Type: static test

Toxicity to soil dwelling organisms : EC50 (*Eisenia fetida* (earthworms)): 979 mg/kg
 Exposure time: 28 d

Aminoethylethanolamine:

Toxicity to fish : Remarks: Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested).

LC50 (*Pimephales promelas* (fathead minnow)): 640 mg/l

D.E.H.® 39 Epoxy Hardener

Version	Revision Date:	SDS Number:	Date of last issue: 06-16-2017
12.0	07-13-2020	101234570	Date of first issue: 07-13-2020

	Exposure time: 96 h Method: OECD Test Guideline 203 or Equivalent
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 22 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202 or Equivalent
Toxicity to algae/aquatic plants	: ErC50 (Desmodesmus subspicatus (green algae)): 353.6 mg/l End point: Growth rate inhibition Exposure time: 72 h Method: OECD Test Guideline 201 or Equivalent
Toxicity to microorganisms	: EC50 (Bacteria): > 5,000 mg/l Exposure time: 16 h

Persistence and degradability**Product:**

Biodegradability	: Remarks: Material is not readily biodegradable according to OECD/EEC guidelines.
------------------	--

Remarks: Material is not readily biodegradable according to OECD/EEC guidelines.

Result: Not biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301F or Equivalent
Remarks: 10-day Window: Fail

Result: Not biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301F or Equivalent
Remarks: 10-day Window: Fail

Chemical Oxygen Demand (COD)	: 1.84 mg/mg
------------------------------	--------------

1.84 mg/mg

ThOD	: 3.34 mg/mg
------	--------------

3.34 mg/mg

Photodegradation	: Rate constant: 2.14E-10 cm ³ /s Method: Estimated.
------------------	--

Rate constant: 2.14E-10 cm³/s
Method: Estimated.

D.E.H.® 39 Epoxy Hardener

Version	Revision Date:	SDS Number:	Date of last issue: 06-16-2017
12.0	07-13-2020	101234570	Date of first issue: 07-13-2020

Components:**Aminoethylpiperazine:**

Biodegradability : Remarks: Material is not readily biodegradable according to OECD/EEC guidelines.

Result: Not biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301F or Equivalent
Remarks: 10-day Window: Fail

Chemical Oxygen Demand (COD) : 1.84 mg/mg

ThOD : 3.34 mg/mg

Photodegradation : Rate constant: 2.14E-10 cm³/s
Method: Estimated.

Diethylenetriamine:

Biodegradability : Result: Readily biodegradable.
Remarks: Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability). Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

aerobic
Biodegradation: > 80 %
Exposure time: 30 d
Method: OECD Test Guideline 302A or Equivalent
Remarks: 10-day Window: Not applicable

Biochemical Oxygen Demand (BOD) : 23.000 %
Incubation time: 5 d

46.000 %
Incubation time: 10 d

70.000 %
Incubation time: 20 d

ThOD : 3.42 mg/mg

Photodegradation : Sensitizer: OH radicals
Concentration: 1,500,000 1/cm³
Rate constant: 1.48E-10 cm³/s
Method: Estimated.

Aminoethylethanolamine:

Biodegradability : Result: Readily biodegradable.
Remarks: Material is readily biodegradable. Passes OECD

D.E.H.® 39 Epoxy Hardener

Version 12.0	Revision Date: 07-13-2020	SDS Number: 101234570	Date of last issue: 06-16-2017 Date of first issue: 07-13-2020
-----------------	------------------------------	--------------------------	---

test(s) for ready biodegradability.

Concentration: 18 mg/l
Biodegradation: > 97 %
Exposure time: 28 d
Method: OECD Test Guideline 301F or Equivalent
Remarks: 10-day Window: Pass

Chemical Oxygen Demand (COD) : 1,070 mg/g

ThOD : 2.77 mg/mg

Bioaccumulative potential**Components:****Aminoethylpiperazine:**

Partition coefficient: n-octanol/water : log Pow: -1.48
Method: Measured
Remarks: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Diethylenetriamine:

Bioaccumulation : Bioconcentration factor (BCF): < 0.3
Method: Measured

Aminoethylethanolamine:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): < 3.7
Exposure time: 42 d
Concentration: 0.1 mg/l
Method: Measured

Partition coefficient: n-octanol/water : log Pow: -1.46
Method: Measured
Remarks: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Mobility in soil**Product:**

Distribution among environmental compartments : Koc: 37000
Method: Estimated.
Remarks: Expected to be relatively immobile in soil (Koc > 5000).

Koc: 37000
Method: Estimated.
Remarks: Expected to be relatively immobile in soil (Koc > 5000).

D.E.H.® 39 Epoxy Hardener

Version	Revision Date:	SDS Number:	Date of last issue: 06-16-2017
12.0	07-13-2020	101234570	Date of first issue: 07-13-2020

Components:**Aminoethylpiperazine:**

Distribution among environmental compartments : Koc: 37000
Method: Estimated.
Remarks: Expected to be relatively immobile in soil (Koc > 5000).

Diethylenetriamine:

Distribution among environmental compartments : Koc: 19111
Method: Estimated.
Remarks: Expected to be relatively immobile in soil (Koc > 5000).
Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Aminoethylethanolamine:

Distribution among environmental compartments : Koc: 3.5
Method: Estimated.
Remarks: Potential for mobility in soil is very high (Koc between 0 and 50).
Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Other adverse effects**Components:****Aminoethylpiperazine:**

Results of PBT and vPvB assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Diethylenetriamine:

Results of PBT and vPvB assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Aminoethylethanolamine:

Results of PBT and vPvB assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING

D.E.H.® 39 Epoxy Hardener

Version	Revision Date:	SDS Number:	Date of last issue: 06-16-2017
12.0	07-13-2020	101234570	Date of first issue: 07-13-2020

PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL.
THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information.
All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations.
Regulations may vary in different locations.
Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator.
DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER.
FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number	: UN 2815
Proper shipping name	: N-AMINOETHYLPIPERAZINE
Class	: 8
Subsidiary risk	: 6.1
Packing group	: III
Labels	: 8 (6.1)

IATA-DGR

UN/ID No.	: UN 2815
Proper shipping name	: N-Aminoethylpiperazine
Class	: 8
Subsidiary risk	: 6.1
Packing group	: III
Labels	: Corrosive, Toxic
Packing instruction (cargo aircraft)	: 856
Packing instruction (passenger aircraft)	: 852

IMDG-Code

UN number	: UN 2815
Proper shipping name	: N-AMINOETHYLPIPERAZINE
Class	: 8
Subsidiary risk	: 6.1
Packing group	: III
Labels	: 8 (6.1)
EmS Code	: F-A, S-B
Marine pollutant	: no
Remarks	: Stowage category B

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

D.E.H.® 39 Epoxy Hardener

Version	Revision Date:	SDS Number:	Date of last issue: 06-16-2017
12.0	07-13-2020	101234570	Date of first issue: 07-13-2020

Domestic regulation**49 CFR**

UN/ID/NA number	: UN 2815
Proper shipping name	: N-Aminoethylpiperazine

Class	: 8
Subsidiary risk	: 6.1
Packing group	: III
Labels	: CORROSIVE, TOXIC
ERG Code	: 153
Marine pollutant	: no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know****SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	: Acute toxicity (any route of exposure) Skin corrosion or irritation Serious eye damage or eye irritation Respiratory or skin sensitization Reproductive toxicity Specific target organ toxicity (single or repeated exposure)
-----------------------------	--

SARA 313	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
-----------------	---

US State Regulations**Pennsylvania Right To Know**

Aminoethylpiperazine	140-31-8
----------------------	----------

California Prop. 65

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

International Regulations

Montreal Protocol (Ozone Depleting Substances)	: Not applicable
--	------------------

Rotterdam Convention (Prior Informed Consent)	: Not applicable
---	------------------

Stockholm Convention (Persistent Organic Pollutants)	: Not applicable
--	------------------

The ingredients of this product are reported in the following inventories:

D.E.H.® 39 Epoxy Hardener

Version 12.0	Revision Date: 07-13-2020	SDS Number: 101234570	Date of last issue: 06-16-2017 Date of first issue: 07-13-2020
-----------------	------------------------------	--------------------------	---

CH INV	:	All intentional components are listed on the inventory, are exempt, or are supplier certified.
DSL	:	All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.
AICS	:	All intentional components are listed on the inventory, are exempt, or are supplier certified.
NZIoC	:	All intentional components are listed on the inventory, are exempt, or are supplier certified.
ENCS	:	All intentional components are listed on the inventory, are exempt, or are supplier certified.
ISHL	:	All intentional components are listed on the inventory, are exempt, or are supplier certified.
KECI	:	All intentional components are listed on the inventory, are exempt, or are supplier certified.
PICCS	:	All intentional components are listed on the inventory, are exempt, or are supplier certified.
IECSC	:	All intentional components are listed on the inventory, are exempt, or are supplier certified.
TCSI	:	All intentional components are listed on the inventory, are exempt, or are supplier certified.
TSCA	:	All substances listed as active on the TSCA Inventory or are not required to be listed.

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.


D.E.H.® 39 Epoxy Hardener

Version	Revision Date:	SDS Number:	Date of last issue: 06-16-2017
12.0	07-13-2020	101234570	Date of first issue: 07-13-2020

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
OSHA P0	:	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
ACGIH / TWA	:	8-hour, time-weighted average
OSHA P0 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable

SAFETY DATA SHEET



D.E.H.® 39 Epoxy Hardener

Version	Revision Date:	SDS Number:	Date of last issue: 06-16-2017
12.0	07-13-2020	101234570	Date of first issue: 07-13-2020

Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07-13-2020

BLUE CUBE OPERATIONS LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US / Z8