

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



ETHYLENE GLYCOL POLYESTER GRADE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000009934	Date of first issue: 07/10/2014

SECTION 1. IDENTIFICATION

Product Identifier : ETHYLENE GLYCOL POLYESTER GRADE
Product code : 00000000016140170
Synonyms : No data available

Manufacturer or supplier's details

Company : Univar Solutions USA
Address : 3250 Lacey Rd., Suite 600
Downers Grove, IL 60515
United States of America (USA)

Emergency telephone number:

Univar Solutions USA:-CHEMTREC INTERNATIONAL Tel # 703-527-3887

Additional Information: : Phone: 1-855-429-2661
Regulatory Information Number: 1-855-429-2661
Email: SDSNA@univarsolutions.com

Recommended use of the chemical and restrictions on use

Recommended use : Industrial chemical

SECTION 2. HAZARD IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Acute toxicity (Oral) : Category 4

Specific target organ toxicity : Category 2 (Kidney)
- repeated exposure

Other hazards

None known.

Hazards associated with a change in physical form:

No data available

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H302 Harmful if swallowed.
H373 May cause damage to organs through prolonged or repeated exposure.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



ETHYLENE GLYCOL POLYESTER GRADE

Version 1.12	Revision Date: 07/01/2026	SDS Number: 100000009934	Date of last issue: 05/22/2026 Date of first issue: 07/10/2014
-----------------	------------------------------	-----------------------------	---

Precautionary statements : **Prevention:**
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.

Response:
P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P314 Get medical advice/ attention if you feel unwell.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Hazards resulting from a reaction with other chemicals under normal conditions of use:

No data available

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Hazardous components

CAS-No.	Chemical name	Weight percent	Trade secret
107-21-1	Ethylene glycol	90 - 100	-
111-46-6	Diethylene glycol	5 - 10	-

Actual concentration is withheld as a trade secret

Any concentration shown as a range is due to batch variation.

SECTION 4. FIRST-AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.

In case of skin contact : Wash off with soap and water.
If skin irritation persists, call a physician.

In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



ETHYLENE GLYCOL POLYESTER GRADE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000009934	Date of first issue: 07/10/2014

Most important symptoms and effects, both acute and delayed	:	Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital. Do not induce vomiting without medical advice.
Immediate Medical Attention and Special Treatment	:	Harmful if swallowed. May cause damage to organs through prolonged or repeated exposure. Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam Dry chemical Carbon dioxide (CO ₂)
Unsuitable extinguishing media	:	High volume water jet
Hazardous combustion products	:	Carbon oxides Carbon monoxide, carbon dioxide, unburned hydrocarbons (smoke), fume. toxic fumes
Further information	:	Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment and precautions for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Precautions for safe handling	:	Do not breathe vapours/dust. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



ETHYLENE GLYCOL POLYESTER GRADE

Version 1.12 Revision Date: 07/01/2026 SDS Number: 100000009934 Date of last issue: 05/22/2026
Date of first issue: 07/10/2014

plification area.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
107-21-1	Ethylene glycol	TWA (Vapour)	25 ppm	ACGIH
		STEL (Vapour)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m ³	ACGIH
		C	50 ppm 125 mg/m ³	OSHA P0
111-46-6	Diethylene glycol	TWA	10 mg/m ³	US WEEL

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Skin and body protection : Impervious clothing
Choose body protection according to the amount and con-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



ETHYLENE GLYCOL POLYESTER GRADE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000009934	Date of first issue: 07/10/2014

Hygiene measures : centration of the dangerous substance at the work place.
: When using do not eat or drink.
: When using do not smoke.
: Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	: liquid
Colour	: Clear, colorless
Odour	: sweet, slight
Odour Threshold	: No data available
pH	: No data available
Freezing point (Melting point/freezing point)	: -13 - -11.2 °C (9 - 11.8 °F)
Boiling point (Boiling point/boiling range)	: 197.4 °C (387.3 °F)
Flash point	: 111 - 116 °C (232 - 241 °F) Method: closed cup
Evaporation rate	: 0.01 (Butyl Acetate = 1)
Flammability (solid, gas)	: No data available
Upper explosion limit	: 22 %(V)
Lower explosion limit	: 1.8 %(V)
Vapour pressure	: < 1 hPa @ 20 - 25 °C (68 - 77 °F)
Relative vapour density	: < 2.14 @ 20 - 25 °C (68 - 77 °F)
Relative density	: 1.115 @ 20 °C (68 °F) Reference substance: (water = 1)
Density	: 1.11 g/cm ³ @ 20 °C (68 °F)
Solubility(ies)	
Water solubility	: soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: log Pow: -1.36
Auto-ignition temperature	: 398 °C
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: 19.83 - 21 mPa.s @ 20 - 25 °C (68 - 77 °F)
Viscosity, kinematic	: 145 mm ² /s @ 25 °C (77 °F)
Particle characteristics	: No data available

SECTION 10. STABILITY AND REACTIVITY

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



ETHYLENE GLYCOL POLYESTER GRADE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000009934	Date of first issue: 07/10/2014

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed.
Conditions to avoid	:	Keep away from heat, flame, sparks and other ignition sources.
Incompatible materials	:	Aldehydes Reducing agents Strong acids Strong bases Strong oxidizing agents Aluminium
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity	:	Acute toxicity estimate: 489.08 mg/kg Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: 2,500 mg/kg Method: Calculation method

Components:

107-21-1:

Acute oral toxicity	:	Assessment: The component/mixture is moderately toxic after single ingestion.
Acute inhalation toxicity	:	LC50 (Rat, male and female): > 2.5 mg/l Exposure time: 6 h Test atmosphere: dust/mist

Acute dermal toxicity	:	LD50 (Mouse, male and female): > 3,500 mg/kg
-----------------------	---	--

111-46-6:

Acute oral toxicity	:	LD50 (Human): Calculated 1,120 mg/kg Assessment: The component/mixture is moderately toxic after single ingestion.
---------------------	---	---

Skin corrosion/irritation

Not classified due to lack of data.

Components:

107-21-1:

Species	:	Rabbit
Result	:	No skin irritation

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



ETHYLENE GLYCOL POLYESTER GRADE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000009934	Date of first issue: 07/10/2014

Serious eye damage/eye irritation

Not classified due to lack of data.

Components:

107-21-1:

Species	:	Rabbit
Result	:	No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Components:

107-21-1:

Test Type	:	Maximisation Test
Species	:	Guinea pig
Result	:	Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

May cause damage to organs (Kidney) through prolonged or repeated exposure.

Components:

107-21-1:

Target Organs	:	Kidney
Assessment	:	The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



ETHYLENE GLYCOL POLYESTER GRADE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000009934	Date of first issue: 07/10/2014

Repeated dose toxicity

Components:

107-21-1:

Species	:	Rat, male
NOAEL	:	150 mg/kg
Application Route	:	Oral
Exposure time	:	12 Months
Method	:	OECD Test Guideline 452
Target Organs	:	Kidney
Symptoms	:	Kidney disorders

Aspiration toxicity

Not classified due to lack of data.

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



ETHYLENE GLYCOL POLYESTER GRADE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000009934	Date of first issue: 07/10/2014

federal regulations.

For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Univar Solutions ChemCare: 1-800-637-7922

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations

49 CFR Road

UN/ID/NA number : UN 3082
Proper shipping name : Other regulated substances, liquid, n.o.s.
Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171
Marine pollutant : no

Special Notes: : This material is shipped as a Class 9, Packing Group III when each package meets or exceeds the reportable quantity, otherwise it may be shipped as not regulated.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

CAS-No.	Components	Component RQ (lbs)	Calculated product RQ (lbs)
107-21-1	Ethylene glycol	5000	5000

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



ETHYLENE GLYCOL POLYESTER GRADE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000009934	Date of first issue: 07/10/2014

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Acute toxicity (any route of exposure)
Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

107-21-1	Ethylene glycol	>= 90 - <= 100 %
----------	-----------------	------------------

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

107-21-1	Ethylene glycol	>= 90 - <= 100 %
----------	-----------------	------------------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

107-21-1	Ethylene glycol	>= 90 - <= 100 %
111-46-6	Diethylene glycol	>= 5 - < 10 %

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

75-07-0	Acetaldehyde	>= 0 - < 0.1 %
---------	--------------	----------------

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

75-07-0	Acetaldehyde	>= 0 - < 0.1 %
---------	--------------	----------------

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

107-21-1	Ethylene glycol
75-07-0	Acetaldehyde

Pennsylvania Right To Know

107-21-1	Ethylene glycol
111-46-6	Diethylene glycol
75-07-0	Acetaldehyde

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

107-21-1	Ethylene glycol
75-07-0	Acetaldehyde

Washington Chemicals of High Concern

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



ETHYLENE GLYCOL POLYESTER GRADE

Version 1.12	Revision Date: 07/01/2026	SDS Number: 100000009934	Date of last issue: 05/22/2026 Date of first issue: 07/10/2014
-----------------	------------------------------	-----------------------------	---

107-21-1
75-07-0

Ethylene glycol
Acetaldehyde

California Prop 65

⚠ WARNING: This product can expose you to chemicals including Acetaldehyde, which is/are known to the State of California to cause cancer, and Ethylene glycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

107-21-1 Ethylene glycol

California Permissible Exposure Limits for Chemical Contaminants

107-21-1 Ethylene glycol

The components of this product are reported in the following inventories:

TSCA	: All substances listed as active on the TSCA inventory
AIIC	: Not in compliance with the inventory
CA. DSL	: All components of this product are on the Canadian DSL
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
NZIoC	: On the inventory, or in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



ETHYLENE GLYCOL POLYESTER GRADE


Version
1.12

Revision Date:
07/01/2026

SDS Number:
100000009934

Date of last issue: 05/22/2026
Date of first issue: 07/10/2014

NFPA 704:



HMIS® IV:

HEALTH	*	1
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
US WEEL	:	USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
OSHA P0 / C	:	Ceiling limit
US WEEL / TWA	:	8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Develop-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



ETHYLENE GLYCOL POLYESTER GRADE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000009934	Date of first issue: 07/10/2014

ment; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Univar Solutions Product Compliance Department (1-855-429-2661) SDSNA@univarsolutions.com.

Revision Date : 07/01/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN