

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



METHYL ETHYL KETONE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000004346	Date of first issue: 08/18/2014

SECTION 1. IDENTIFICATION

Product Identifier : METHYL ETHYL KETONE
Product code : 00000000016140315
Synonyms : 2-Butanone
Manufacturer or supplier's details
Company : Univar Solutions USA
Address : 3250 Lacey Rd., Suite 600
Downers Grove, IL 60515
United States of America (USA)

Emergency telephone number:

Univar Solutions USA:-CHEMTREC INTERNATIONAL Tel # 703-527-3887

Additional Information: : Phone: 1-855-429-2661
Regulatory Information Number: 1-855-429-2661
Email: SDSNA@univarsolutions.com

Recommended use of the chemical and restrictions on use

Recommended use : Solvent
Restrictions on use : This product is not recommended for any industrial, professional or consumer use other than the identified uses above.

SECTION 2. HAZARD IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Flammable liquids : Category 2
Eye irritation : Category 2A
Specific target organ toxicity : Category 3 (Central nervous system)
- single exposure

Other hazards

May react with oxygen in air to form peroxides

Hazards associated with a change in physical form:

No data available

GHS label elements

Hazard pictograms :  

Signal word : Danger

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



METHYL ETHYL KETONE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000004346	Date of first issue: 08/18/2014

Hazard statements : H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazards resulting from a reaction with other chemicals under normal conditions of use:

No data available

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Hazardous components

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



METHYL ETHYL KETONE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000004346	Date of first issue: 08/18/2014

CAS-No.	Chemical name	Weight percent	Trade secret
78-93-3	Methyl ethyl ketone	90 - 100	-

Actual concentration is withheld as a trade secret
Any concentration shown as a range is due to batch variation.

Synonyms : 2-Butanone

SECTION 4. FIRST-AID MEASURES

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	: If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Do not induce vomiting without medical advice.
Most important symptoms and effects, both acute and delayed	: Causes serious eye irritation. May cause drowsiness or dizziness.
Immediate Medical Attention and Special Treatment	: Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray
Unsuitable extinguishing media	: High volume water jet
Specific hazards during fire-fighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: No hazardous combustion products are known

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



METHYL ETHYL KETONE

Version 1.12	Revision Date: 07/01/2026	SDS Number: 100000004346	Date of last issue: 05/22/2026 Date of first issue: 08/18/2014
-----------------	------------------------------	-----------------------------	---

- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment and precautions for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Use only explosion-proof equipment.
Keep away from open flames, hot surfaces and sources of ignition.
- Precautions for safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



METHYL ETHYL KETONE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000004346	Date of first issue: 08/18/2014

Conditions for safe storage : regulations.
No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
78-93-3	Methyl ethyl ketone	TWA	75 ppm	ACGIH
		STEL	150 ppm	ACGIH
		TWA	200 ppm 590 mg/m3	NIOSH REL
		ST	300 ppm 885 mg/m3	NIOSH REL
		TWA	200 ppm 590 mg/m3	OSHA Z-1
		TWA	200 ppm 590 mg/m3	OSHA P0
		STEL	300 ppm 885 mg/m3	OSHA P0

Engineering measures : Ensure adequate ventilation, especially in confined areas.
Use appropriate engineering controls and manufacturing technologies to control airborne concentrations (e.g., drip-less quick connections).
Use only in an area equipped with explosion proof exhaust ventilation.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



METHYL ETHYL KETONE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000004346	Date of first issue: 08/18/2014

Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	: liquid
Colour	: clear, colourless
Odour	: characteristic
Odour Threshold	: No data available
pH	: No data available
Freezing point (Melting point/freezing point)	: -86 °C (-123 °F)
Boiling point (Boiling point/boiling range)	: 79 - 80 °C (174 - 176 °F)
Flash point	: -9 - -6 °C (16 - 21 °F)
Evaporation rate	: 7.7 (Butyl Acetate = 1)
Flammability (solid, gas)	: No data available
Upper explosion limit	: 11 - 11.5 %(V)
Lower explosion limit	: 1.5 - 1.8 %(V)
Vapour pressure	: 126 hPa @ 20 - 25 °C (68 - 77 °F)
Relative vapour density	: 2.4 - 2.5 @ 20 °C (68 °F) (Air = 1.0)
Relative density	: 0.804 - 0.806 @ 20 °C (68 °F) Reference substance: (water = 1)
Density	: 0.804 - 0.806 g/cm ³ @ 20 °C (68 °F)
Solubility(ies)	
Water solubility	: partly miscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: log Pow: 0.3
Auto-ignition temperature	: 404 - 515 °C
Thermal decomposition	: No data available
Viscosity	

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



METHYL ETHYL KETONE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000004346	Date of first issue: 08/18/2014

Viscosity, dynamic : 0.4 mPa.s @ 20 °C (68 °F)

Particle characteristics
Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air. May react with oxygen in air to form peroxides
Conditions to avoid	: Heat, flames and sparks. Do not allow vapor to accumulate in low or confined areas. Extremes of temperature and direct sunlight. Exposure to air or moisture over prolonged periods.
Incompatible materials	: Strong oxidizing agents Alkalis Chloroform Nitric acid strong reducing agents peroxides Acids Combustible material
Hazardous decomposition products	: Carbon oxides sulfur dioxide

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

78-93-3:

Acute oral toxicity : LD50 (Rat, male and female): 2,193 mg/kg

Acute dermal toxicity : LD50 (Rabbit, male): > 10 ml/kg

Skin corrosion/irritation

Not classified due to lack of data.

Components:

78-93-3:

Species	: Rabbit
Exposure time	: 24 h
Result	: May cause drying and flaking of the skin.
Remarks	: Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



METHYL ETHYL KETONE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000004346	Date of first issue: 08/18/2014

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

78-93-3:

Species	:	Rabbit
Result	:	Irritating to eyes.
Exposure time	:	24 h

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Components:

78-93-3:

Test Type	:	Buehler Test
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	Did not cause sensitisation on laboratory animals.
Test substance	:	methyl ethyl ketone

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Components:

78-93-3:

Remarks	:	This information is not available.
---------	---	------------------------------------

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
-------------	---

OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
-------------	--

NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
------------	---

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

78-93-3:

Target Organs	:	Central nervous system
---------------	---	------------------------

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



METHYL ETHYL KETONE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000004346	Date of first issue: 08/18/2014

Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

78-93-3:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates : Exposure time: 48 h
Test Type: Immobilization

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100
plants : mg/l
Exposure time: 72 h

Persistence and degradability

Components:

78-93-3:

Biodegradability : Inoculum: Activated sludge, domestic, adaption not specified
Concentration: 2 mg/l
Result: Readily biodegradable.
Biodegradation: 98 %
Exposure time: 28 d

Bioaccumulative potential

No data available

Mobility in soil

No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



METHYL ETHYL KETONE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000004346	Date of first issue: 08/18/2014

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Univar Solutions ChemCare: 1-800-637-7922

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1193
Proper shipping name : METHYL ETHYL KETONE
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1193
Proper shipping name : METHYL ETHYL KETONE
Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



METHYL ETHYL KETONE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000004346	Date of first issue: 08/18/2014

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations

49 CFR Road

UN/ID/NA number	: UN 1193
Proper shipping name	: METHYL ETHYL KETONE
Class	: 3
Packing group	: II
Labels	: FLAMMABLE LIQUID
ERG Code	: 127
Marine pollutant	: no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

CAS-No.	Components	Component RQ (lbs)	Calculated product RQ (lbs)
78-93-3	Methyl ethyl ketone	5000	5000

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

78-93-3	Methyl ethyl ketone	>= 90 - <= 100 %
---------	---------------------	------------------

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



METHYL ETHYL KETONE

Version 1.12	Revision Date: 07/01/2026	SDS Number: 100000004346	Date of last issue: 05/22/2026 Date of first issue: 08/18/2014
-----------------	------------------------------	-----------------------------	---

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

78-93-3

Methyl ethyl ketone

Pennsylvania Right To Know

78-93-3

Methyl ethyl ketone

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

78-93-3

Methyl ethyl ketone

Washington Chemicals of High Concern

78-93-3

Methyl ethyl ketone

California Prop 65

: This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other re-productive harm.

California List of Hazardous Substances

78-93-3

Methyl ethyl ketone

California Permissible Exposure Limits for Chemical Contaminants

78-93-3

Methyl ethyl ketone

The components of this product are reported in the following inventories:

TSCA	: All substances listed as active on the TSCA inventory
AIIC	: On the inventory, or in compliance with the inventory
CA. DSL	: All components of this product are on the Canadian DSL
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
NZIoC	: On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



METHYL ETHYL KETONE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000004346	Date of first issue: 08/18/2014

TSCA list


No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	/	2
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	: 8-hour time weighted average
OSHA P0 / STEL	: Short-term exposure limit
OSHA Z-1 / TWA	: 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



METHYL ETHYL KETONE

Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2026
1.12	07/01/2026	100000004346	Date of first issue: 08/18/2014

Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07/01/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN