

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Kristalex(TM) 3100 Hydrocarbon Resin

Version	Revision Date:	SDS Number:	Date of last issue: 07/04/2023
3.0	09/07/2023	1012-00018	Date of first issue: 10/10/2017

SECTION 1. IDENTIFICATION

Product name : Kristalex(TM) 3100 Hydrocarbon Resin
Product code : P7509301
Other means of identification : 3100

Manufacturer or supplier's details

Company name of supplier : Synthomer Adhesive Technologies LLC
Address : 25435 HARVARD ROAD
BEACHWOOD OH 44122-6201
Emergency telephone : USA +1 866 928 0789 (toll free) // Americas # +1 215 207 0061 / Global (EN speaking only) +44 1865 407333
E-mail address : regulatoryaffairs@synthomer.com

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives
Plastic additive
Coatings
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Combustible dust

GHS label elements

Signal Word : Warning
Hazard Statements : May form combustible dust concentrations in air.

Other hazards

Dust contact with the eyes can lead to mechanical irritation.
Contact with dust can cause mechanical irritation or drying of the skin.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance
Substance name : Alpha-Methylstyrene-styrene copolymer
CAS-No. : 9011-11-4

Components

No hazardous ingredients

SECTION 4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Kristalex(TM) 3100 Hydrocarbon Resin

Version	Revision Date:	SDS Number:	Date of last issue: 07/04/2023
3.0	09/07/2023	1012-00018	Date of first issue: 10/10/2017

In case of skin contact	: Get medical attention if symptoms occur. Wash with water and soap.
In case of eye contact	: Get medical attention if symptoms occur. If in eyes, rinse well with water.
If swallowed	: Get medical attention if irritation develops and persists. If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	: Contact with dust can cause mechanical irritation or drying of the skin. Dust contact with the eyes can lead to mechanical irritation.
Protection of first-aiders	: No special precautions are necessary for first aid responders.
Notes to physician	: Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during fire fighting	: Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard. Do not use a solid water stream as it may scatter and spread fire. Exposure to combustion products may be a hazard to health.
Hazardous combustion products	: Carbon oxides
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	: Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
Environmental precautions	: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Kristalex(TM) 3100 Hydrocarbon Resin

Version	Revision Date:	SDS Number:	Date of last issue: 07/04/2023
3.0	09/07/2023	1012-00018	Date of first issue: 10/10/2017

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).
Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : Static electricity may accumulate and ignite suspended dust causing an explosion.
Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not breathe dust.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Minimize dust generation and accumulation.
Keep container closed when not in use.
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.
Apply measures to prevent dust explosions.
Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Kristalex(TM) 3100 Hydrocarbon Resin

Version 3.0	Revision Date: 09/07/2023	SDS Number: 1012-00018	Date of last issue: 07/04/2023 Date of first issue: 10/10/2017
----------------	------------------------------	---------------------------	---

Hand protection	required.
Remarks	: Wash hands before breaks and at the end of workday.
Eye protection	: Wear the following personal protective equipment: Safety goggles
Skin and body protection	: Skin should be washed after contact.
Hygiene measures	: If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: pellets
Color	: colorless
Odor	: slight
Odor Threshold	: No data available
pH	: No data available
Melting point/freezing point	: 212 °F / 100 °C
Initial boiling point and boiling range	: No data available
Flash point	: 352.9 °F / 178.3 °C Method: closed cup
Evaporation rate	: Not applicable
Flammability (solid, gas)	: May form combustible dust concentrations in air.
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: Not applicable
Relative vapor density	: Not applicable
Relative density	: 1.08 (77 °F / 25 °C)
Density	: No data available
Solubility(ies) Water solubility	: negligible (68 °F / 20 °C)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Kristalex(TM) 3100 Hydrocarbon Resin

Version	Revision Date:	SDS Number:	Date of last issue: 07/04/2023
3.0	09/07/2023	1012-00018	Date of first issue: 10/10/2017

Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	200 mPa.s (356 °F / 180 °C)
Viscosity, kinematic	:	277.77 mm ² /s (356 °F / 180 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available
Particle size	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	May form combustible dust concentrations in air. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks. Avoid dust formation.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Kristalex(TM) 3100 Hydrocarbon Resin

Version	Revision Date:	SDS Number:	Date of last issue: 07/04/2023
3.0	09/07/2023	1012-00018	Date of first issue: 10/10/2017

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Kristalex(TM) 3100 Hydrocarbon Resin

Version	Revision Date:	SDS Number:	Date of last issue: 07/04/2023
3.0	09/07/2023	1012-00018	Date of first issue: 10/10/2017

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	:	Dispose of in accordance with local regulations. Do not dispose of waste into sewer.
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

|| Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	Combustible dust
----------------------	---	------------------

SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
----------	---	---

US State Regulations

Pennsylvania Right To Know

Alpha-Methylstyrene-styrene copolymer

9011-11-4

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Kristalex(TM) 3100 Hydrocarbon Resin

Version	Revision Date:	SDS Number:	Date of last issue: 07/04/2023
3.0	09/07/2023	1012-00018	Date of first issue: 10/10/2017

California Prop. 65

WARNING: This product can expose you to chemicals including 2-Phenylpropene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TCSI	: On the inventory, or in compliance with the inventory
TSCA	: All substances listed as active on the TSCA inventory
AIIC	: On the inventory, or in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
ENCS	: On the inventory, or in compliance with the inventory
ISHL	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
NZIoC	: On the inventory, or in compliance with the inventory
TECI	: On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Kristalex(TM) 3100 Hydrocarbon Resin


Version
3.0

Revision Date:
09/07/2023

SDS Number:
1012-00018

Date of last issue: 07/04/2023
Date of first issue: 10/10/2017

NFPA 704:



HMIS® IV:

HEALTH	/	0
FLAMMABILITY		2
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Kristalex(TM) 3100 Hydrocarbon Resin

Version	Revision Date:	SDS Number:	Date of last issue: 07/04/2023
3.0	09/07/2023	1012-00018	Date of first issue: 10/10/2017

(United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/07/2023

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8