

Piccotac(TM) 9095 Hydrocarbon Resin

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2019
1.2	06/01/2020	150000050687	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

SECTION 1. IDENTIFICATION

Product name : Piccotac(TM) 9095 Hydrocarbon Resin

Product code : 9095, P7505605, P750560S, P75056TT, P75056RC, P75056SP, E7505601, P75056ST, P75056MB

Manufacturer or supplier's details

Company name of supplier : Eastman Chemical Company

Address : 200 South Wilcox Drive
Kingsport TN 37660-5280

Telephone : (423) 229-2000

Emergency telephone : CHEMTREC: +1-800-424-9300, +1-703-527-3887
CCN212893

Recommended use of the chemical and restrictions on use

Recommended use : Adhesive

Restrictions on use : None known.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

Combustible dust

GHS label elements

Signal Word : Warning

Hazard Statements : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

Precautionary Statements : **Disposal:**
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Components**

Chemical name	CAS-No.	Concentration (% w/w)
---------------	---------	-----------------------

Piccotac(TM) 9095 Hydrocarbon Resin

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2019
1.2	06/01/2020	150000050687	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

hydrocarbon resin	proprietary	> 99
additive(s)	proprietary	< 1

SECTION 4. FIRST AID MEASURES

- If inhaled : Move to fresh air.
Treat symptomatically.
If symptoms persist, call a physician.
- In case of skin contact : Wash off with soap and water.
If symptoms persist, call a physician.
Cool skin rapidly with cold water after contact with molten material.
Do not peel solidified product off the skin.
Burns must be treated by a physician.
- In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- If swallowed : Seek medical advice.
- Most important symptoms and effects, both acute and delayed : The molten product can cause serious burns.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Dry chemical
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.
- Specific hazards during fire fighting : Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
- Further information : Minimize dust generation and accumulation.
- Special protective equipment for fire-fighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Wear appropriate personal protective equipment.
Local authorities should be advised if significant spillages cannot be contained.

Piccotac(TM) 9095 Hydrocarbon Resin

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2019
1.2	06/01/2020	150000050687	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

Environmental precautions : Avoid release to the environment.

Methods and materials for containment and cleaning up : Sweep up and shovel into suitable containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Minimize dust generation and accumulation.

Advice on safe handling : Wash thoroughly after handling.
Use only in area provided with appropriate exhaust ventilation.
Minimize dust generation and accumulation.

Conditions for safe storage : Keep tightly closed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Contains no substances with occupational exposure limit values.

Engineering measures : Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Wear respiratory protection when its use is identified for certain contributing scenario.

Hand protection

Remarks : Wear suitable gloves. When handling hot material, use heat resistant gloves.

Eye protection : Safety glasses
Wear a face shield when working with molten material.

Skin and body protection : Wear suitable protective clothing.

Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.

Piccotac(TM) 9095 Hydrocarbon Resin

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2019
1.2	06/01/2020	150000050687	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	flakes, molten
Color	:	light yellow
Odor	:	hydrocarbon-like
Odor Threshold	:	not determined
pH	:	not determined
Softening point	:	208 °F / 98 °C
Boiling point/boiling range	:	not determined
Flash point	:	518 °F / 270 °C
		Method: Cleveland open cup
Evaporation rate	:	not determined
Flammability (solid, gas)	:	May form combustible dust concentrations in air during processing, handling or other means.
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	not determined
Vapor pressure	:	not determined
Relative vapor density	:	not determined
Relative density	:	0.97 (77 °F / 25 °C)
Solubility(ies)		
Water solubility	:	negligible
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	not determined
Decomposition temperature	:	Thermal stability not tested. Low stability hazard expected at normal operating temperatures.
Viscosity		

Piccotac(TM) 9095 Hydrocarbon Resin

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2019
1.2	06/01/2020	150000050687	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

Viscosity, dynamic	:	not determined
Viscosity, kinematic	:	not determined
Explosive properties	:	No data available
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	None reasonably foreseeable.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Stable
Conditions to avoid	:	Minimize dust generation and accumulation.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	Carbon monoxide Carbon dioxide (CO ₂)

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Product:

Acute oral toxicity	:	Remarks: No data available
Acute inhalation toxicity	:	Remarks: No data available
Acute dermal toxicity	:	Remarks: No data available

Components:**hydrocarbon resin:**

Acute oral toxicity	:	LD50 Oral (Rat, female): > 2,000 mg/kg Assessment: The substance or mixture has no acute oral toxicity
Acute dermal toxicity	:	LD50 Dermal (Rat, male and female): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Piccotac(TM) 9095 Hydrocarbon Resin

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2019
1.2	06/01/2020	150000050687	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

Product:

Remarks : No data available

Components:**hydrocarbon resin:**

Species	:	Rabbit
Exposure time	:	4 h
Assessment	:	No skin irritation
Result	:	none

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : No data available

Components:**hydrocarbon resin:**

Species	:	Rabbit
Result	:	none
Assessment	:	No eye irritation
Method	:	washed eyes

Species	:	Rabbit
Result	:	none
Assessment	:	No eye irritation
Method	:	unwashed eyes

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : No data available

Components:**hydrocarbon resin:**

Test Type	:	Skin sensitization
Species	:	Guinea pig
Result	:	non-sensitizing

Germ cell mutagenicity

Not classified based on available information.

Piccotac(TM) 9095 Hydrocarbon Resin

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2019
1.2	06/01/2020	150000050687	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

Carcinogenicity

Not classified based on available information.

Product:

Remarks : This information is not available.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Product:

Effects on fertility : Remarks: No data available

STOT-single exposure

Not classified based on available information.

Product:

Remarks : No data available

STOT-repeated exposure

Not classified based on available information.

Product:

Remarks : No data available

Aspiration toxicity

Not classified based on available information.

Product:

No data available

Information on likely routes of exposure**Product:**

Inhalation : Remarks: None known.

Skin contact : Remarks: The molten product can cause serious burns.

Eye contact : Remarks: The molten product can cause serious burns.

Ingestion : Remarks: None known.

Piccotac(TM) 9095 Hydrocarbon Resin

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2019
1.2	06/01/2020	150000050687	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

Further information**Product:**

Remarks : The additives are embedded in a tough plastic matrix which minimizes the likelihood of exposure to the additives.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****hydrocarbon resin:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1 mg/l
Exposure time: 96 h
Remarks: (highest concentration tested)
No toxicity at the limit of solubility.

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia): > 1 mg/l
Exposure time: 24 h
Remarks: (highest concentration tested)
No toxicity at the limit of solubility.

LC50 (Daphnia): > 1 mg/l
Exposure time: 48 h
Remarks: (highest concentration tested)
No toxicity at the limit of solubility.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

Not regulated as a dangerous good

Piccotac(TM) 9095 Hydrocarbon Resin

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2019
1.2	06/01/2020	150000050687	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

Remarks : Solid forms of this product are not regulated. Forbidden on aircraft if transported molten in bulk at temperatures equal to or exceeding 100 C (212 F).

IMDG-Code

UN number : UN 3257
Proper shipping name : ELEVATED TEMPERATURE LIQUID, N.O.S. (molten resin)
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-P
Marine pollutant : no
Remarks : 9, Packing Group III when liquid is offered for transport or is transported, in bulk packaging, at or above 100°C and below its flash point; otherwise, not regulated.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

UN/ID/NA number : UN 3257
Proper shipping name : Elevated temperature liquid, n.o.s. (molten resin)
Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 128
Marine pollutant : no
Remarks : 9, Packing Group III when liquid is offered for transport or is transported, in bulk packaging, at or above 100°C and below its flash point; otherwise, not regulated.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

Piccotac(TM) 9095 Hydrocarbon Resin

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2019
1.2	06/01/2020	150000050687	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Combustible dust

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

The ingredients of this product are reported in the following inventories:

DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
ISHL	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: On the inventory, or in compliance with the inventory
TSCA	: All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION**Further information**

Piccotac(TM) 9095 Hydrocarbon Resin


Version
1.2
PRD

Revision Date:
06/01/2020

SDS Number:
150000050687
SDSUS / Z8 / 0001

Date of last issue: 08/12/2019
Date of first issue: 09/06/2016

NFPA 704:



HMIS® IV:

HEALTH	/	1
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG -

Piccotac(TM) 9095 Hydrocarbon Resin

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2019
1.2	06/01/2020	150000050687	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 06/01/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8