

Section 1. Identification

Product name	: VAR SOL™ 1 FLUID See Section 16 for synonyms.
Product description	: petroleum hydrocarbons
<u>Relevant identified uses of the substance or mixture and uses advised against</u>	
Identified uses	: Solvent
Uses advised against	: This product is not recommended for any industrial, professional or consumer use other than the identified uses above.
Supplier	: ExxonMobil Product Solutions Company (a division of Exxon Mobil Corporation) SDS – LOC. 106 22777 Springwoods Village Parkway Spring, TX 77389-1425 USA
24-Hour emergency telephone number	: 1-800-424-9300 / +1 703-741-5970 / +1-703-527-3887 (CHEMTREC)
Supplier General Contact	: (832) 624-8500
SDS Internet Address	: www.sds.exxonmobil.com

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: FLAMMABLE LIQUIDS - Category 3 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 ASPIRATION HAZARD - Category 1

GHS label elements

Hazard pictograms	: 
Signal word	: Danger
Hazard statements	: H226 - Flammable liquid and vapor. H304 - May be fatal if swallowed and enters airways. H336 - May cause drowsiness or dizziness. H351 - Suspected of causing cancer. H373 - May cause damage to organs through prolonged or repeated exposure. (hearing organs)
<u>Precautionary statements</u>	
Prevention	: P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof electrical, ventilating or lighting equipment. P242 - Use non-sparking tools. P243 - Take action to prevent static discharges. P260 - Do not breathe vapor. P271 - Use only outdoors or in a well-ventilated area.

Section 2. Hazards identification

Response	P280 - Wear protective gloves, protective clothing and eye or face protection. : P301 + P331, P310 - IF SWALLOWED: Do NOT induce vomiting. Immediately call a POISON CENTER or doctor. P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P304 + P312, P340 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell. Remove person to fresh air and keep comfortable for breathing. P308 + P313 - IF exposed or concerned: Get medical advice or attention. P370 + P378 - In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish.
Storage	: P403 + P233 - Store in a well-ventilated place. Keep container tightly closed. P403 + P235 - Keep cool. P405 - Store locked up.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Contains	: low boiling point naphtha, unspecified
Hazards not otherwise classified	: None known.
Note	: This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

Section 3. Composition/information on ingredients

Substance/mixture	: Substance
Chemical name	: low boiling point naphtha, unspecified

Ingredient name	% by weight	Identifiers
low boiling point naphtha, unspecified	100	CAS: 8052-41-3
xylene	≥1 - ≤5	CAS: 1330-20-7
naphthalene	≥0.1 - ≤0.5	CAS: 91-20-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Continue to rinse for at least 10 minutes. Get medical attention.

Section 4. First aid measures

- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Causes mild skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. This material, or a component, may be associated with cardiac sensitization following very high exposures (well above occupational exposure limits) or with concurrent exposure to high stress levels or heart-stimulating substances like epinephrine. Administration of such substances should be avoided.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

Section 5. Fire-fighting measures

Specific hazards arising from the chemical	: Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Incomplete combustion products, Oxides of carbon, Smoke, Fume
Special protective actions for fire-fighters	: Use standard firefighting procedures and consider the hazards of other involved materials. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. Assure an extended cooling down period to prevent re-ignition. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting releases of this material to the environment which exceed the applicable reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at (800)424-8802.

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Put on appropriate personal protective equipment. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
----------------------------------	--

Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Eliminate all ignition sources. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. If the Flash Point does not exceed the Ambient Air Temperature by at least 10C, use booms as a barrier to protect shorelines and allow material to evaporate. If the Flash Point exceeds the Ambient Temperature by 10 degrees C or more, use containment booms and remove

Section 6. Accidental release measures

from the surface by skimming or with suitable absorbents when conditions permit. Seek the advice of a specialist before using dispersants. Warn other shipping. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Static Accumulator	: This material is a static accumulator. A liquid is typically considered a nonconductive, static accumulator if its conductivity is below 100 pS/m (100x10E-12 Siemens per meter) and is considered a semiconductive, static accumulator if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semiconductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, anti-static additives and filtration can greatly influence the conductivity of a liquid.
Loading/Unloading Temperature	: Ambient
Transport Temperature	: Ambient
Transport Pressure	: Ambient
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
Storage Temperature	: Ambient
Storage Pressure	: Ambient
Suitable Containers/Packing	: Barges, Tank Cars, Tank Trucks, Drums
Suitable Materials and Coatings	: Carbon Steel, polyethylene, polypropylene, Teflon, Stainless Steel, Polyester
Unsuitable Materials and Coatings	: Polystyrene, Natural Rubber, butyl rubber, Ethylene-propylene-diene monomer (EPDM)

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
low boiling point naphtha, unspecified	ExxonMobil (COMPANY) TWA: 66 ppm (Total Hydrocarbons). Form: Vapor..
low boiling point naphtha, unspecified	TWA: 400 mg/m³ (Total Hydrocarbons). Form: Vapor.
	NIOSH REL (United States, 10/2020)
	TWA 10 hours: 350 mg/m³.
	CEIL 15 minutes: 1800 mg/m³.
	CAL OSHA PEL (United States, 5/2018)
	TWA 8 hours: 525 mg/m³.
	TWA 8 hours: 100 ppm.
	OSHA PEL (United States, 5/2018)
	TWA 8 hours: 500 ppm.
	TWA 8 hours: 2900 mg/m³.
	OSHA PEL 1989 (United States, 3/1989)
	TWA 8 hours: 100 ppm.
	TWA 8 hours: 525 mg/m³.
	ACGIH TLV (United States, 1/2024)
	TWA 8 hours: 100 ppm.
	TWA 8 hours: 525 mg/m³.
nonane	NIOSH REL (United States, 10/2020)
	TWA 10 hours: 200 ppm.
	TWA 10 hours: 1050 mg/m³.
	CAL OSHA PEL (United States, 5/2018)
	TWA 8 hours: 1050 mg/m³.
	TWA 8 hours: 200 ppm.
	OSHA PEL 1989 (United States, 3/1989)
	TWA 8 hours: 200 ppm.
	TWA 8 hours: 1050 mg/m³.
	ACGIH TLV (United States, 1/2024)
	TWA 8 hours: 200 ppm.
	TWA 8 hours: 1050 mg/m³.
pseudocumene (1,2,4-trimethylbenzene)	NIOSH REL (United States, 10/2020)
	TWA 10 hours: 25 ppm.
	TWA 10 hours: 125 mg/m³.
	CAL OSHA PEL (United States, 5/2018) [trimethylbenzene, all isomers]
	TWA 8 hours: 125 mg/m³.
	TWA 8 hours: 25 ppm.
	OSHA PEL 1989 (United States, 3/1989) [Trimethyl benzene]
	TWA 8 hours: 25 ppm.
	TWA 8 hours: 125 mg/m³.
	ACGIH TLV (United States, 1/2024)
	TWA 8 hours: 10 ppm.
xylenes	CAL OSHA PEL (United States, 5/2018) [xylene]
	STEL 15 minutes: 655 mg/m³.
	STEL 15 minutes: 150 ppm.
	C: 300 ppm.
	TWA 8 hours: 435 mg/m³.
	TWA 8 hours: 100 ppm.
	OSHA PEL (United States, 5/2018) [Xylenes]
	TWA 8 hours: 100 ppm.
	TWA 8 hours: 435 mg/m³.
	OSHA PEL 1989 (United States, 3/1989) [Xylenes (o-, m-, p-isomers)]
	TWA 8 hours: 100 ppm.
	TWA 8 hours: 435 mg/m³.
	STEL 15 minutes: 150 ppm.
	STEL 15 minutes: 655 mg/m³.

Section 8. Exposure controls/personal protection

naphthalene	ACGIH TLV (United States, 1/2024) [p-xylene and mixtures containing p-xylene] Ototoxicant. TWA 8 hours: 20 ppm. NIOSH REL (United States, 10/2020) TWA 10 hours: 10 ppm. TWA 10 hours: 50 mg/m³. STEL 15 minutes: 15 ppm. STEL 15 minutes: 75 mg/m³. CAL OSHA PEL (United States, 5/2018) Absorbed through skin. TWA 8 hours: 0.5 mg/m³. TWA 8 hours: 0.1 ppm. OSHA PEL (United States, 5/2018) TWA 8 hours: 10 ppm. TWA 8 hours: 50 mg/m³. OSHA PEL 1989 (United States, 3/1989) TWA 8 hours: 10 ppm. TWA 8 hours: 50 mg/m³. STEL 15 minutes: 15 ppm. STEL 15 minutes: 75 mg/m³. ACGIH TLV (United States, 1/2024) Absorbed through skin. TWA 8 hours: 10 ppm. TWA 8 hours: 52 mg/m³.
-------------	--

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

Biological exposure indices

Ingredient name	Exposure indices
xylenes	ACGIH BEI (United States, 1/2024) [xylenes (technical or commercial grades)] BEI: 0.3 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift.
naphthalene	ACGIH BEI (United States, 1/2024) BEI: Nonquantitative: Biological monitoring should be considered for this compound based on the review; however, a specific BEI® could not be determined due to insufficient data., 1-naphthol + 2-naphthol [(sample not specified)]. Sampling time: end of shift.

Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Section 8. Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. < 1 hour (breakthrough time): Viton, minimum 0.71 mm thickness or comparable protective barrier material
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties and safety characteristics

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

- Physical state** : Liquid. [Clear]
- Color** : Colorless
- Odor** : Pungent petroleum
- Odor threshold** : Not available.
- pH** : Not applicable.
- Melting point/freezing point** : Not available.
- Boiling point or initial boiling point and boiling range** : 159 to 202°C (318.2 to 395.6°F) [ASTM D86]
- Flash point** : Closed cup: 40°C (104°F) [ASTM D-56]
- Evaporation rate** : 0.2 (butyl acetate = 1) [In-house method]
- Flammability** : Flammable liquids - Category 3
- Lower and upper explosion limit/flammability limit** : Lower: 0.7%
Upper: 6%
- Vapor pressure** : 1.5 mm Hg [20 °C] [Calculated]
- Relative vapor density** : 5 [Air = 1] [In-house method]
- Relative density** : 0.79 [Calculated]
- Density** : 0.79 g/cm³ [0.79°C (33.4°F)] [ASTM D4052]
- Solubility in water** : Negligible
- Partition coefficient: n-octanol/water** : >4 [Estimated]
- Auto-ignition temperature** : 254°C (489.2°F) [ASTM E659]
- Decomposition temperature** : Not available.
- Viscosity** : 1 cSt [40 °C] [Calculated]
- Molecular weight** : 144
- Particle characteristics**
- Median particle size** : Not applicable.

Section 9. Physical and chemical properties and safety characteristics

Pour point : <-51°C [ASTM D5950]
Coefficient of Thermal Expansion : 0.00074 per Deg C

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

Incompatible materials : Reactive or incompatible with the following materials:,oxidizing materials,

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Test	Species	Result	Duration
low boiling point naphtha, unspecified naphthalene	LC50 Inhalation Vapor	Rat	>13.1 mg/l	4 hours
	LD50 Dermal	Rabbit	>3400 mg/kg	-
	LD50 Oral	Rat	>15000 mg/kg	-
	LC50 Inhalation Vapor	Rat	>0.4 mg/l	4 hours
	LD50 Oral	Mouse	533 mg/kg	-

Conclusion/Summary

Inhalation : Minimally Toxic. Data available. Based on test data for structurally similar materials. Test (s) equivalent or similar to OECD Guideline 403

Dermal : Minimally Toxic. Data available. Based on test data for structurally similar materials. Test (s) equivalent or similar to OECD Guideline 402

Oral : Minimally Toxic. Data available. Based on test data for structurally similar materials. Test (s) equivalent or similar to OECD Guideline 401

Irritation/Corrosion

Conclusion/Summary

Skin : May dry the skin leading to discomfort and dermatitis. Mildly irritating to skin with prolonged exposure. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 404

Eyes : May cause mild, short-lasting discomfort to eyes. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 405

Respiratory : Negligible hazard at ambient/normal handling temperatures. No end point data for material.

Respiratory or skin sensitization

Conclusion/Summary

Skin : Not expected to be a skin sensitizer. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 406

Respiratory : Not expected to be a respiratory sensitizer. No end point data for material.

Mutagenicity

Section 11. Toxicological information

Conclusion/Summary : Not expected to be a germ cell mutagen. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 471 473 474 475 479

Carcinogenicity

Conclusion/Summary : May cause cancer. No end point data for material. Based on assessment of the components.

Classification

Product/ingredient name	OSHA	IARC	NTP
xylene	-	3	-
naphthalene	-	2B	Reasonably anticipated to be a human carcinogen.

Reproductive toxicity

Conclusion/Summary : Not expected to be a reproductive toxicant. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 413 414 415

Specific target organ toxicity (single exposure)

Conclusion/Summary : May cause drowsiness or dizziness. No end point data for material.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Target organs
low boiling point naphtha, unspecified	Category 2	hearing organs

Conclusion/Summary : May cause damage to organs through prolonged or repeated exposure. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 408 411 413

Aspiration hazard

Conclusion/Summary : May be fatal if swallowed and enters airways. Based on physico-chemical properties of the material. Data available.

Other information

Contains : NAPHTHALENE: Exposure to high concentrations of naphthalene may cause destruction of red blood cells, anemia, and cataracts. Naphthalene caused cancer in laboratory animal studies, but the relevance of these findings to humans is uncertain.

Product : Vapor/aerosol concentrations above recommended exposure levels are irritating to the eyes and respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects including death. Prolonged and/or repeated skin contact with low viscosity materials may defat the skin resulting in possible irritation and dermatitis. Exposure to this material, or one of its components, in situations where there is the potential for high levels, such as in confined spaces or with abuse, may result in abnormal heart rhythm (arrhythmia). High-level exposure to hydrocarbons (above occupational exposure limits) may initiate arrhythmia in a worker that is undergoing stress or is taking a heart-stimulating substance such as epinephrine, a nasal decongestant, or an asthma or cardiovascular drug. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

Section 12. Ecological information

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

Toxicity

Conclusion/Summary

Acute toxicity : Toxic to aquatic life.

Chronic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

Biodegradability : Material -- Expected to be inherently biodegradable

Section 12. Ecological information

Hydrolysis : Material -- Transformation due to hydrolysis not expected to be significant.

Photolysis : Material -- Transformation due to photolysis not expected to be significant.

Atmospheric Oxidation : Material -- Expected to degrade rapidly in air

Bioaccumulative potential

Not determined.

Mobility in soil

Mobility : Material -- Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.

Other ecological information

VOC (EPA Method 24) : 6.593 lbs/gal

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

RCRA Toxic hazardous waste "U" List

Ingredient	CAS #	Status	Reference number
Xylene	1330-20-7	Listed	U239

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
UN number	UN1268	UN1268	UN1268	UN1268
UN proper shipping name	Petroleum distillates, n.o.s.	PETROLEUM DISTILLATES, N.O.S.	PETROLEUM DISTILLATES, N.O.S.	Petroleum distillates, n.o.s.
Transport hazard class(es)	3	3	3	3
Label(s) / Marks	 	 	 	
Packing group	III	III	III	III
Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.

Section 14. Transport information

Additional information

DOT Classification

: This product may be re-classified as "Combustible Liquid," unless transported by vessel or aircraft. Non-bulk packages (less than or equal to 119 gal) of combustible liquids, that are marine pollutants, are not regulated as hazardous materials in package sizes less than the product reportable quantity, unless transported by vessel. This product is not regulated as a marine pollutant when transported on inland waterways in sizes of ≤5 L or ≤5 kg or by road, rail, or inland air in non-bulk sizes, provided the packagings meet the general provisions of §§ 173.24 and 173.24a. **Reportable quantity** 9434 lbs / 4283 kg [1432.2 gal / 5421.5 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements. **Limited quantity** Yes. **Packaging instruction** Exceptions: 150. Non-bulk: 203. Bulk: 242. **Quantity limitation** Passenger aircraft/rail: 60 L. Cargo aircraft: 220 L. **Special provisions** 144, B1, IB3, T4, TP1, TP29

TDG Classification

: Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3), 2.7 (Marine pollutant mark). The marine pollutant mark is not required when transported by road or rail. **Explosive Limit and Limited Quantity Index** 5 **Passenger Carrying Road or Rail Index** 60 **Special provisions** 91, 92, 150

IMDG

: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. **Emergency schedules** F-E, S-E **Special provisions** 223, 955
Flash point 40 °C C.C.

IATA

: The environmentally hazardous substance mark may appear if required by other transportation regulations. **Quantity limitation** Passenger and Cargo Aircraft: 60 L. Packaging instructions: 355. Cargo Aircraft Only: 220 L. Packaging instructions: 366. Limited Quantities - Passenger Aircraft: 10 L. Packaging instructions: Y344. **Special provisions** A3

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not applicable.

Section 15. Regulatory information

U.S. Federal regulations

: **TSCA 4(a) final test rules:** nonane
TSCA 8(a) PAIR: nonane; naphthalene
TSCA 8(a) CDR Exempt/Partial exemption: Not determined
Clean Water Act (CWA) 307: ethyl benzene; naphthalene; toluene; fluorene
Clean Water Act (CWA) 311: xylenes; ethyl benzene; naphthalene; toluene

TSCA 12(b) - Chemical export notification

Name	One time notification		Annual notification		
	4	5	5(f)	6	7
Nonane	Listed	Not listed	Not listed	Not listed	Not listed

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Listed

Section 15. Regulatory information

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : FLAMMABLE LIQUIDS - Category 3
 CARCINOGENICITY - Category 2
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
 ASPIRATION HAZARD - Category 1

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	pseudocumene (1,2,4-trimethylbenzene)	95-63-6	≥1 - ≤5
	xylenes	1330-20-7	≥1 - ≤5
	ethyl benzene	100-41-4	≥0.1 - ≤0.5
	naphthalene	91-20-3	≥0.1 - ≤0.5
Supplier notification	pseudocumene (1,2,4-trimethylbenzene)	95-63-6	≥1 - ≤5
	xylenes	1330-20-7	≥1 - ≤5
	ethyl benzene	100-41-4	≥0.1 - ≤0.5
	naphthalene	91-20-3	≥0.1 - ≤0.5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: STODDARD SOLVENT; NONANE; PSEUDOCUMENE; XYLENE

New York : The following components are listed: Xylene mixed

New Jersey : The following components are listed: STODDARD SOLVENT; NONANE; PSEUDOCUMENE; XYLENES; ETHYL BENZENE; NAPHTHALENE; TOLUENE

Pennsylvania : The following components are listed: STODDARD SOLVENT; NONANE; PSEUDOCUMENE; BENZENE, DIMETHYL-

Illinois : None of the components are listed.

California Prop. 65

 **WARNING:** Cancer - www.P65Warnings.ca.gov.

Inventory list

Australia inventory (AIIIC) : All components are listed or exempted.

Canada inventory (DSL-NDSL) : All components are listed or exempted.

China inventory (IECSC) : All components are listed or exempted.

Japan inventory (CSCL) : All components are listed or exempted.

Japan inventory (Industrial Safety and Health Act) : All components are listed or exempted.

New Zealand Inventory of Chemicals (NZIoC) : All components are listed or exempted.

Section 15. Regulatory information

Philippines inventory (PICCS)	: All components are listed or exempted.
Korea inventory (KECI)	: All components are listed or exempted.
Taiwan Chemical Substances Inventory (TCSI)	: All components are listed or exempted.
United States inventory (TSCA 8b)	: All components are active or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	3
Flammability		2
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 3	On basis of test data
CARCINOGENICITY - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method
ASPIRATION HAZARD - Category 1	Calculation method

History

Date of issue/Date of revision	: 3 December 2024
Date of previous issue	: 3 December 2024
Version	: 6
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

References : Not available.

Indicates information that has changed from previously issued version.

Section 16. Other information

THIS SDS COVERS THE FOLLOWING MATERIALS :

BRFP VAR SOL AT HYDRO STRIPPING SECTION

Product code : 1165085_13514703

Notice to reader

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.