

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Styrene Monomer 10 - 15 PPM Inhib

Version	Revision Date:	SDS Number:	Date of last issue: 02/25/2026
1.11	09/04/2026	100000009032	Date of first issue: 09/25/2014

SECTION 1. IDENTIFICATION

Product Identifier : Styrene Monomer 10 - 15 PPM Inhib
Product code : 00000000000020010
Synonyms : No data available

Manufacturer or supplier's details

Company : Univar Solutions USA
Address : 3250 Lacey Rd., Suite 600
Downers Grove, IL 60515
United States of America (USA)

Emergency telephone number:

Univar Solutions USA:-CHEMTREC INTERNATIONAL Tel # 703-527-3887

Additional Information: : Phone: 1-855-429-2661
Regulatory Information Number: 1-855-429-2661
Email: SDSNA@univarsolutions.com

Recommended use of the chemical and restrictions on use

Recommended use : Industrial chemical
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARD IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Flammable liquids : Category 3
Acute toxicity (Inhalation) : Category 4
Skin irritation : Category 2
Eye irritation : Category 2A
Specific target organ toxicity : Category 3 (Respiratory system)
- single exposure
Specific target organ toxicity : Category 1 (Auditory system)
- repeated exposure
Aspiration hazard : Category 1

Other hazards

None known.

Hazards associated with a change in physical form:

No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Styrene Monomer 10 - 15 PPM Inhib

Version	Revision Date:	SDS Number:	Date of last issue: 02/25/2026
1.11	09/04/2026	100000009032	Date of first issue: 09/25/2014

GHS label elements

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: H372 Causes damage to organs through prolonged or repeated exposure.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H361 Suspected of damaging fertility or the unborn child.

Precautionary statements

:

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ atten-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Styrene Monomer 10 - 15 PPM Inhib

Version	Revision Date:	SDS Number:	Date of last issue: 02/25/2026
1.11	09/04/2026	100000009032	Date of first issue: 09/25/2014

tion.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazards resulting from a reaction with other chemicals under normal conditions of use:

No data available

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Hazardous components

CAS-No.	Chemical name	Weight percent	Trade secret
100-42-5	Styrene	90 - 100	-

Any concentration shown as a range is due to batch variation.

Molecular formula : C₆H₅-CH=CH₂

SECTION 4. FIRST-AID MEASURES

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice. Move to fresh air.
In case of skin contact	: If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes. Wash contaminated clothing before re-use.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Styrene Monomer 10 - 15 PPM Inhib

Version 1.11	Revision Date: 09/04/2026	SDS Number: 100000009032	Date of last issue: 02/25/2026 Date of first issue: 09/25/2014
-----------------	------------------------------	-----------------------------	---

Most important symptoms and effects, both acute and delayed	: Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Do NOT induce vomiting. Causes skin and eye irritation. Risk of serious damage to the lungs (by aspiration).
---	--

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Water spray Foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during fire-fighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon oxides Carbon oxides
Specific extinguishing methods	: Use a water spray to cool fully closed containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Further information	: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments.
Special protective equipment and precautions for fire-fighters	: Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Styrene Monomer 10 - 15 PPM Inhib

Version	Revision Date:	SDS Number:	Date of last issue: 02/25/2026
1.11	09/04/2026	100000009032	Date of first issue: 09/25/2014

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Precautions for safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Recommended storage temperature : < 104 °F / < 40 °C

Further information on storage stability : Stable under normal conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
100-42-5	Styrene	TWA	50 ppm 215 mg/m3	NIOSH REL
		ST	100 ppm 425 mg/m3	NIOSH REL
		TWA	100 ppm	OSHA Z-2
		CEIL	200 ppm	OSHA Z-2
		Peak	600 ppm	OSHA Z-2

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Styrene Monomer 10 - 15 PPM Inhib

Version 1.11 Revision Date: 09/04/2026 SDS Number: 100000009032 Date of last issue: 02/25/2026
Date of first issue: 09/25/2014

			(5 mins. in any 3 hrs.)	
		TWA	50 ppm 215 mg/m ³	OSHA P0
		STEL	100 ppm 425 mg/m ³	OSHA P0
		TWA	10 ppm	ACGIH
		STEL	20 ppm	ACGIH

Biological occupational exposure limits

CAS-No.	Components	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
100-42-5	Styrene	Mandelic acid plus phenylgly-oxalic acid	Urine	End of shift (As soon as possible after exposure ceases)	150 mg/g mg/g creati-nine	ACGIH BEI
		Styrene	Urine	End of shift (As soon as possible after exposure ceases)	20 µg/l	ACGIH BEI

Engineering measures : Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.
In the case of vapour formation use a respirator with an approved filter.
General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Styrene Monomer 10 - 15 PPM Inhib

Version	Revision Date:	SDS Number:	Date of last issue: 02/25/2026
1.11	09/04/2026	100000009032	Date of first issue: 09/25/2014

Skin and body protection : problems.
: Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
: When using do not smoke.
: Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State : liquid
Colour : colourless, yellow
Odour : aromatic, sweet
Odour Threshold : 0.017 ppm

pH : No data available

Freezing point (Freezing Point) : -31 °C (-24 °F)
Boiling point (Boiling point/boiling range) : 145 °C (293 °F)
(1,013 hPa)

Flash point : 31 °C (88 °F)
(1,013 hPa)

Evaporation rate : No data available
Flammability (solid, gas) : No data available
Upper explosion limit : 6.8 %(V)

Lower explosion limit : 0.9 %(V)

Vapour pressure : 5 mmHg @ 20 °C (68 °F)

Relative vapour density : 3.6 @ 20 - 25 °C (68 - 77 °F)

Relative density : No data available
Density : No data available
Solubility(ies)
Water solubility : 0.32 g/l @ 25 °C (77 °F)

Solubility in other solvents : No data available
Partition coefficient: n-octanol/water : log Pow: 2.96 @ 25 °C (77 °F)
Auto-ignition temperature : 490 °C 1,013 hPa

Thermal decomposition : No data available
Viscosity
Viscosity, dynamic : 0.696 mPa.s @ 25 °C (77 °F)
Viscosity, kinematic : 0.77 mm²/s @ 25 °C (77 °F)

Oxidizing properties : The substance or mixture is not classified as oxidizing.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Styrene Monomer 10 - 15 PPM Inhib

Version	Revision Date:	SDS Number:	Date of last issue: 02/25/2026
1.11	09/04/2026	100000009032	Date of first issue: 09/25/2014

Particle characteristics : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	No hazards to be specially mentioned.
Conditions to avoid	:	Keep away from heat, flame, sparks and other ignition sources. Exposure to light.
Incompatible materials	:	Copper Strong oxidizing agents Peroxides Contamination polymer catalysts Alkali metals aluminum chloride Strong acids Strong bases Copper alloys metal halogenates Rubber
Hazardous decomposition products	:	acid smoke and fumes

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute inhalation toxicity	:	Acute toxicity estimate: 11 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method
---------------------------	---	---

Components:

100-42-5:

Acute inhalation toxicity	:	LC50 (Rat): 12 mg/l Exposure time: 4 h Test atmosphere: vapour
---------------------------	---	--

Skin corrosion/irritation

Product:

Remarks	:	Irritating to skin.
---------	---	---------------------

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Styrene Monomer 10 - 15 PPM Inhib

Version	Revision Date:	SDS Number:	Date of last issue: 02/25/2026
1.11	09/04/2026	100000009032	Date of first issue: 09/25/2014

Components:

100-42-5:

Species	:	Rabbit
Result	:	Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks	:	Severe eye irritation
---------	---	-----------------------

Components:

100-42-5:

Species	:	Rabbit
Result	:	Irritating to eyes.

Germ cell mutagenicity

Components:

100-42-5:

Germ cell mutagenicity - Assessment	:	Tests on bacterial or mammalian cell cultures did not show mutagenic effects.
-------------------------------------	---	---

Carcinogenicity

Product:

Carcinogenicity - Assessment	:	Not classifiable as a human carcinogen.
------------------------------	---	---

Components:

100-42-5:

Carcinogenicity - Assessment	:	Not classifiable as a human carcinogen.
------------------------------	---	---

IARC

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

Reasonably anticipated to be a human carcinogen
100-42-5

Styrene

Reproductive toxicity

Product:

Reproductive toxicity - Assessment	:	Weight of evidence does not support classification for reproductive toxicity
------------------------------------	---	--

Components:

100-42-5:

Effects on fertility	:	Test Type: Three-generation study Species: Rat, male and female Application Route: oral
----------------------	---	---

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Styrene Monomer 10 - 15 PPM Inhib

Version	Revision Date:	SDS Number:	Date of last issue: 02/25/2026
1.11	09/04/2026	100000009032	Date of first issue: 09/25/2014

Dose: 125 and 250 ppm in water
General Toxicity - Parent: 125 ppm
General Toxicity F1: 125 ppm
Symptoms: Reduced embryonic survival
GLP: no

Effects on foetal development

: Species: Rat
Application Route: Inhalation
Dose: 0.519, 1.080, 2.146 mg/l
Duration of Single Treatment: 6 h
Frequency of Treatment: 7 days/week
General Toxicity Maternal: 1.08 mg/L
Developmental Toxicity: 1.08 mg/L
GLP: yes

Reproductive toxicity - Assessment

: Some evidence of adverse effects on development, based on animal experiments.

STOT - single exposure

Components:

100-42-5:

Target Organs

Assessment

: Respiratory system
: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

STOT - repeated exposure

Components:

100-42-5:

Target Organs

Assessment

: Auditory system
: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Aspiration toxicity

Components:

100-42-5:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks

: Solvents may degrease the skin.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Styrene Monomer 10 - 15 PPM Inhib

Version	Revision Date:	SDS Number:	Date of last issue: 02/25/2026
1.11	09/04/2026	100000009032	Date of first issue: 09/25/2014

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

100-42-5:

- | | | |
|--|---|---|
| Toxicity to fish | : | LC50 (Pimephales promelas (fathead minnow)): 4.02 mg/l
Exposure time: 96 h
Test Type: flow-through test |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): 4.7 mg/l
Exposure time: 48 h
Test Type: flow-through test
Method: OECD Test Guideline 202
GLP: yes |
| Toxicity to algae/aquatic plants | : | EC50 (Pseudokirchneriella subcapitata (microalgae)): 4.9 mg/l
Exposure time: 72 h
Test Type: static test
GLP: yes |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | NOEC (Daphnia magna (Water flea)): 1.01 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211 |
| Toxicity to microorganisms | : | Remarks: No data available |

Ecotoxicology Assessment

- | | | |
|--------------------------|---|--|
| Chronic aquatic toxicity | : | Harmful to aquatic life with long lasting effects. |
|--------------------------|---|--|

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

- | | | |
|-----------------------------------|---|--|
| Ozone-Depletion Potential | : | Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). |
| Additional ecological information | : | No data available |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Styrene Monomer 10 - 15 PPM Inhib

Version	Revision Date:	SDS Number:	Date of last issue: 02/25/2026
1.11	09/04/2026	100000009032	Date of first issue: 09/25/2014

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Univar Solutions ChemCare: 1-800-637-7922
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

- UN/ID No. : UN 2055
Proper shipping name : Styrene monomer, stabilized
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

- UN number : UN 2055
Proper shipping name : STYRENE MONOMER, STABILIZED, Styrene monomer, stabilized
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations

49 CFR Road

- UN/ID/NA number : UN 2055
Proper shipping name : Styrene monomer, stabilized
Class : 3
Packing group : III
Labels : FLAMMABLE LIQUID
ERG Code : 128P
Marine pollutant : no

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Styrene Monomer 10 - 15 PPM Inhib

Version 1.11 Revision Date: 09/04/2026 SDS Number: 100000009032 Date of last issue: 02/25/2026
Date of first issue: 09/25/2014

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

CAS-No.	Components	Component RQ (lbs)	Calculated product RQ (lbs)
100-42-5	Styrene	1000	1000
100-41-4	Ethylbenzene	1000	
108-88-3	Toluene	1000	

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

CAS-No.	Components	Component TPQ (lbs)
---------	------------	---------------------

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Acute toxicity (any route of exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

100-42-5	Styrene	100 %
----------	---------	-------

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

100-42-5	Styrene	100 %
----------	---------	-------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

100-42-5	Styrene	100 %
----------	---------	-------

Clean Water Act

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

The following Hazardous Substances are listed under the U.S. Clean Water Act, Section 311, Table 116.4A:

100-42-5	Styrene	100 %
----------	---------	-------

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Styrene Monomer 10 - 15 PPM Inhib

Version 1.11	Revision Date: 09/04/2026	SDS Number: 100000009032	Date of last issue: 02/25/2026 Date of first issue: 09/25/2014
-----------------	------------------------------	-----------------------------	---

100-41-4	Ethylbenzene	0.0999 %
108-88-3	Toluene	0.0999 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

100-42-5	Styrene	100 %
100-41-4	Ethylbenzene	0.0999 %
108-88-3	Toluene	0.0999 %

US State Regulations

Massachusetts Right To Know

100-42-5	Styrene
----------	---------

Pennsylvania Right To Know

100-42-5	Styrene
100-41-4	Ethylbenzene
108-88-3	Toluene

Maine Chemicals of High Concern

100-42-5	Styrene
108-88-3	Toluene

The following chemicals are listed as Maine Chemicals of High Concern:

California Prop 65

⚠ WARNING: This product can expose you to chemicals including Styrene, Ethylbenzene, a-Methylstyrene, which is/are known to the State of California to cause cancer, and Toluene, a-Methylstyrene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA	: On TSCA Inventory
CA. DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard




Styrene Monomer 10 - 15 PPM Inhib

Version	Revision Date:	SDS Number:	Date of last issue: 02/25/2026
1.11	09/04/2026	100000009032	Date of first issue: 09/25/2014

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	*	3
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-2	: USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	: 8-hour time weighted average
OSHA P0 / STEL	: Short-term exposure limit
OSHA Z-2 / TWA	: 8-hour time weighted average
OSHA Z-2 / CEIL	: Acceptable ceiling concentration
OSHA Z-2 / Peak	: Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Styrene Monomer 10 - 15 PPM Inhib

Version	Revision Date:	SDS Number:	Date of last issue: 02/25/2026
1.11	09/04/2026	100000009032	Date of first issue: 09/25/2014

the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECL - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Univar Solutions Product Compliance Department (1-855-429-2661) SDSNA@univarsolutions.com.

Revision Date : 09/04/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN