



SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY

Product name: DOWSIL™ RSN-0249 Flake Resin

Issue Date: 03/26/2020

Print Date: 03/27/2020

THE DOW CHEMICAL COMPANY encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: DOWSIL™ RSN-0249 Flake Resin

Recommended use of the chemical and restrictions on use

Identified uses: Coatings

COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY
2211 H.H. DOW WAY
MIDLAND MI 48674
UNITED STATES

Customer Information Number:

800-258-2436
SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: CHEMTREC +1 800-424-9300

Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with 29 CFR 1910.1200

Combustible dust

Reproductive toxicity - Category 2

Label elements

Hazard pictograms



Signal word: **WARNING!**

Hazards

If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

Suspected of damaging fertility or the unborn child.

Precautionary statements**Prevention**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

IF exposed or concerned: Get medical advice/ attention.

Storage

Store locked up.

Disposal

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Dust contact with the eyes can lead to mechanical irritation.

Contact with dust can cause mechanical irritation or drying of the skin.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms: Silane, dichlorodimethyl-, polymer with trichloromethylsilane and trichlorophenylsilane
This product is a substance.

Substance name: Silane, dichlorodimethyl-, polymer with trichloromethylsilane and trichlorophenylsilane

CASRN: 25766-16-9

Component	CASRN	Concentration
Toluene	108-88-3	>= 0.43 - <= 0.58 %

4. FIRST AID MEASURES

Description of first aid measures**General advice:**

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air and keep comfortable for breathing; consult a physician.

Skin contact: Wash off with plenty of water.

Eye contact: Flush eyes with plenty of water; remove contact lenses after the first 1-2 minutes then continue flushing for several minutes. Only mechanical effects expected. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: Rinse mouth with water. No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Water spray. Alcohol-resistant foam. Carbon dioxide (CO₂). Dry chemical.

Unsuitable extinguishing media: None known..

Special hazards arising from the substance or mixture

Hazardous combustion products: Carbon oxides. Chlorine compounds. Silicon oxides.

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health.. Pneumatic conveying and other mechanical handling operations can generate combustible dust. To reduce the potential for dust explosions, do not permit dust to accumulate.. May form explosive dust-air mixture during processing, handling or other means..

Advice for firefighters

Fire Fighting Procedures: Use water spray to cool unopened containers.. Evacuate area.. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations..

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus.. Use personal protective equipment..

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Sweep up or vacuum up spillage and collect in suitable container for disposal. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

See sections: 7, 8, 11, 12 and 13.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not breathe dust. Avoid contact with eyes. Do not swallow. Avoid prolonged or repeated contact with skin. Minimize dust generation and accumulation. Keep container closed when not in use. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment. Pneumatic conveying and other mechanical handling operations can generate combustible dust. To reduce the potential for dust explosions, do not permit dust to accumulate. Handle in accordance with good industrial hygiene and safety practice. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied.

Use only with adequate ventilation. This material can accumulate static charge due to its inherent physical properties and can therefore cause an electrical ignition source to vapors. In order to prevent a fire hazard, as bonding and grounding may be insufficient to remove static electricity, it is necessary to provide an inert gas purge before beginning transfer operations. Static electricity may accumulate and ignite suspended dust causing an explosion. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.

Conditions for safe storage: Keep in properly labelled containers. Store locked up. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents.

Unsuitable materials for containers: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Toluene	ACGIH	TWA	20 ppm
	Further information: visual impair: Visual impairment; female repro: Female reproductive; pregnancy loss: Pregnancy loss; BEI: Substances for which there is a Biological Exposure Index or Indices (see BEI® section); A4: Not classifiable as a human carcinogen		
	OSHA Z-1		See Further information
	Further information: (2): See Table Z-2		
	OSHA Z-2	TWA	200 ppm
	Further information: Z37.12-1967		

	OSHA Z-2	CEIL	300 ppm
	Further information: Z37.12-1967		
	OSHA Z-2	Peak	500 ppm
	Further information: Z37.12-1967		

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Toluene	108-88-3	Toluene	In blood	Prior to last shift of workweek	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields).

Skin protection

Hand protection: Chemical protective gloves should not be needed when handling this material. Consistent with general hygienic practice for any material, skin contact should be minimized. Use gloves to protect from mechanical injury. Selection of gloves will depend on the task.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. In dusty or misty atmospheres, use an approved particulate respirator. The following should be effective types of air-purifying respirators: When dust/mist are present use a/an Particulate filter.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	
Physical state	flakes
Color	white
Odor	none
Odor Threshold	No data available
pH	Not applicable
Melting point/range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	Not applicable
Flash point	closed cup >100 °C (212 °F)
Evaporation Rate (Butyl Acetate = 1)	Not applicable
Flammability (solid, gas)	Not classified as a flammability hazard
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapor Pressure	Not applicable
Relative Vapor Density (air = 1)	No data available
Relative Density (water = 1)	1.30
Water solubility	No data available
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Dynamic Viscosity	Not applicable
Kinematic Viscosity	Not applicable
Explosive properties	Not explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.
Molecular weight	No data available
Particle size	1,000 µm

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents. Dust can form an explosive mixture in air. When heated to temperatures above 150 °C (300 °F) in the presence of air, trace quantities of formaldehyde may be released. Adequate ventilation is required.

Conditions to avoid: None known.

Incompatible materials: Oxidizing agents

Hazardous decomposition products:

Decomposition products can include and are not limited to: Benzene.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Information on likely routes of exposure

Inhalation, Eye contact, Skin contact, Ingestion.

Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):
LD50, > 5,000 mg/kg Estimated.

Information for components:

Toluene

LD50, Rat, 5,580 mg/kg

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):
LD50, > 2,000 mg/kg Estimated.

Information for components:

Toluene

LD50, Rabbit, 12,267 mg/kg

Acute inhalation toxicity

At room temperature, exposure to vapor is minimal due to low volatility; single exposure is not likely to be hazardous.

As product: The LC50 has not been determined.

Information for components:

Toluene

LC50, Rat, male, 4 Hour, vapour, 25.7 mg/l

LC50, Rat, female, 4 Hour, vapour, 30 mg/l

Skin corrosion/irritation

Typical for this family of materials.

Brief contact is essentially nonirritating to skin.

Information for components:

Toluene

Brief contact may cause slight skin irritation with local redness.

Prolonged contact may cause moderate skin irritation with local redness.

May cause drying and flaking of the skin.

Serious eye damage/eye irritation

Typical for this family of materials.

Solid or dust may cause irritation or corneal injury due to mechanical action.

Information for components:

Toluene

May cause slight eye irritation.

May cause slight temporary corneal injury.

Vapor may cause eye irritation experienced as mild discomfort and redness.

Vapor may cause lacrimation (tears).

Sensitization

For skin sensitization:

Contains component(s) which did not cause allergic skin sensitization in guinea pigs.

For respiratory sensitization:

No relevant data found.

Information for components:

Toluene

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Information for components:

Toluene

May cause drowsiness or dizziness.

Route of Exposure: Inhalation

Target Organs: Central nervous system

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

Information for components:

Toluene

May be fatal if swallowed and enters airways.

Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)

Specific Target Organ Systemic Toxicity (Repeated Exposure)

No relevant data found.

Information for components:

Toluene

In animals, effects have been reported on the following organs:

Central nervous system.

Excessive exposure may cause neurologic signs and symptoms.

Toluene has caused hearing loss in laboratory animals upon exposure to high concentrations.

Intentional misuse by deliberately inhaling toluene may cause nervous system damage, hearing loss, liver and kidney effects and death.

Carcinogenicity

Contains component(s) which did not cause cancer in laboratory animals.

Information for components:

Toluene

Did not cause cancer in laboratory animals.

Teratogenicity

In laboratory animals, toluene has been toxic to the fetus at doses toxic to the mother; it has caused birth defects in mice when administered orally, but not by inhalation.

Information for components:

Toluene

In laboratory animals, toluene has been toxic to the fetus at doses toxic to the mother; it has caused birth defects in mice when administered orally, but not by inhalation.

Reproductive toxicity

Contains component(s) which did not interfere with reproduction in animal studies.

Information for components:

Toluene

In animal studies, did not interfere with reproduction.

Mutagenicity

Contains a component(s) which were negative in in vitro genetic toxicity studies. Contains component(s) which were negative in animal genetic toxicity studies.

Information for components:

Toluene

The majority and most reliable of the many genetic toxicity studies on toluene, both in vitro and in animals, indicate that it is not genetically toxic.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

Toluene

Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 5.8 mg/l

Acute toxicity to aquatic invertebrates

LC50, water flea Ceriodaphnia dubia, semi-static test, 48 Hour, 3.78 mg/l

Acute toxicity to algae/aquatic plants

EbC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Biomass, 12.5 mg/l, OECD Test Guideline 201

Toxicity to bacteria

IC50, Bacteria, 16 Hour, 29 mg/l

Chronic toxicity to fish

NOEC, Fish, flow-through test, 40 d, growth, 1.4 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Ceriodaphnia dubia (water flea), 7 d, number of offspring, 0.74 mg/l

Toxicity to soil-dwelling organisms

LC50, Eisenia fetida (earthworms), 150 - 280 mg/kg

Persistence and degradability

Toluene

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Not applicable

Biodegradation: 100 %

Exposure time: 14 d

Method: OECD Test Guideline 301C or Equivalent

Theoretical Oxygen Demand: 3.13 mg/mg Calculated.

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals

Atmospheric half-life: 2 d

Method: Estimated.

Bioaccumulative potential**Toluene**

Bioaccumulation: Bioconcentration potential is low ($BCF < 100$ or $\log Pow < 3$).

Partition coefficient: n-octanol/water(log Pow): 2.73 Measured

Bioconcentration factor (BCF): 13.2 - 90 Fish Measured

Mobility in soil**Toluene**

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 37 - 178 Estimated.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Not regulated for transport

**Transport in bulk
according to Annex I or II
of MARPOL 73/78 and the
IBC or IGC Code**

Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Combustible dust
Reproductive toxicity

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components

Silane, dichlorodimethyl-, polymer with trichloromethylsilane
and trichlorophenylsilane

CASRN

25766-16-9

California Prop. 65

WARNING: This product can expose you to chemicals including Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System

NFPA

Health	Flammability	Instability
0	1	0

HMIS

Health	Flammability	Physical Hazard
0*	3	0

* = Chronic Effects (See Hazards Identification)

Revision

Identification Number: 4119439 / A001 / Issue Date: 03/26/2020 / Version: 8.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	ACGIH - Biological Exposure Indices (BEI)
CEIL	Acceptable ceiling concentration
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	USA. Occupational Exposure Limits (OSHA) - Table Z-2
Peak	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift
TWA	8-hour, time-weighted average

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US

DOWSIL™ RSN-0249 Flake Resin



WARNING

Contains: Silane, dichlorodimethyl-, polymer with trichloromethylsilane and trichlorophenylsilane / 25766-16-9; Toluene / 108-88-3

Hazards: If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air. Suspected of damaging fertility or the unborn child. **Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection. **Response:** IF exposed or concerned: Get medical advice/ attention. **Storage:** Store locked up. **Disposal:** Dispose of contents/ container to an approved waste disposal plant. **Supplemental information** Dust contact with the eyes can lead to mechanical irritation. Contact with dust can cause mechanical irritation or drying of the skin.

Refer to the Safety Data Sheet before use.

COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY
2211 H.H. DOW WAY
MIDLAND MI 48674
UNITED STATES

**EMERGENCY TELEPHONE
NUMBER**

24-Hour Emergency Contact:
CHEMTREC +1 800-424-9300
Local Emergency Contact:
800-424-9300

Customer Information Number:
800-258-2436



® ™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

Revision

Identification Number: 4119439 / A001 / Issue Date:
03/26/2020 / Version: 8.0