

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Methyl isobutyl ketone

Version	Revision Date:	SDS Number:	Date of last issue: 09/08/2025
1.12	09/02/2026	100000003128	Date of first issue: 07/08/2014

SECTION 1. IDENTIFICATION

Product Identifier : Methyl isobutyl ketone
Product code : 00000000000056043
Synonyms : 2-methyl-4-pentanone, 2-methylproyl methyl ketone, 2-pentanone, hexone, isobutyl methyl ketone

Manufacturer or supplier's details

Company : Univar Solutions USA
Address : 3250 Lacey Rd., Suite 600
Downers Grove, IL 60515
United States of America (USA)

Emergency telephone number:

Univar Solutions USA:-CHEMTREC: 1-800-424-9300
CHEMTREC INTERNATIONAL Tel # 703-527-3887

Additional Information: : Phone: 1-855-429-2661
Regulatory Information Number: 1-855-429-2661
Email: SDSNA@univarsolutions.com

Recommended use of the chemical and restrictions on use

Recommended use : Catalyst
Intermediate
paint and coatings
Pharmaceutical
Process raw material
Solvent
Restrictions on use : Uses other than those identified are not recommended.

SECTION 2. HAZARD IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Flammable liquids : Category 2
Acute toxicity (Inhalation) : Category 4
Eye irritation : Category 2A
Carcinogenicity : Category 2
Specific target organ toxicity : Category 3 (Central nervous system)
- single exposure

Other hazards

None known.

Hazards associated with a change in physical form:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Methyl isobutyl ketone

Version	Revision Date:	SDS Number:	Date of last issue: 09/08/2025
1.12	09/02/2026	100000003128	Date of first issue: 07/08/2014

No data available

GHS label elements

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.

Precautionary statements

:

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Methyl isobutyl ketone

Version 1.12	Revision Date: 09/02/2026	SDS Number: 100000003128	Date of last issue: 09/08/2025 Date of first issue: 07/08/2014
-----------------	------------------------------	-----------------------------	---

tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazards resulting from a reaction with other chemicals under normal conditions of use:

No data available

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Hazardous components

CAS-No.	Chemical name	Weight percent	Trade secret
108-10-1	Methyl isobutyl ketone	90 - 100	-

Actual concentration is withheld as a trade secret

Any concentration shown as a range is due to batch variation.

Synonyms : 2-methyl-4-pentanone, 2-methylproyl methyl ketone, 2-pentanoe, hexone, isobutyl methyl ketone

SECTION 4. FIRST-AID MEASURES

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	: If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital. Do not induce vomiting without medical advice.
Most important symptoms and effects, both acute and delayed	: Causes serious eye irritation. Harmful if inhaled. May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Methyl isobutyl ketone

Version 1.12	Revision Date: 09/02/2026	SDS Number: 100000003128	Date of last issue: 09/08/2025 Date of first issue: 07/08/2014
-----------------	------------------------------	-----------------------------	---

Immediate Medical Attention and Special Treatment : Suspected of causing cancer.
Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon monoxide, carbon dioxide, unburned hydrocarbons (smoke), fume.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

Special protective equipment and precautions for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Methyl isobutyl ketone

Version 1.12 Revision Date: 09/02/2026 SDS Number: 100000003128 Date of last issue: 09/08/2025
Date of first issue: 07/08/2014

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Use only explosion-proof equipment.
Keep away from open flames, hot surfaces and sources of ignition.

Precautions for safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
108-10-1	Methyl isobutyl ketone	TWA	20 ppm	ACGIH
		STEL	75 ppm	ACGIH
		TWA	50 ppm 205 mg/m3	NIOSH REL
		ST	75 ppm 300 mg/m3	NIOSH REL
		TWA	100 ppm 410 mg/m3	OSHA Z-1
		TWA	50 ppm 205 mg/m3	OSHA P0
		STEL	75 ppm 300 mg/m3	OSHA P0

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Methyl isobutyl ketone

Version 1.12 Revision Date: 09/02/2026 SDS Number: 100000003128 Date of last issue: 09/08/2025
Date of first issue: 07/08/2014

Biological occupational exposure limits

CAS-No.	Components	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
108-10-1	Methyl isobutyl ketone	methyl iso-butyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	1 mg/l	ACGIH BEI

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State : liquid
Colour : Clear, colorless
Odour : pungent, sweet, characteristic
Odour Threshold : 7.8 ppm

pH : No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Methyl isobutyl ketone

Version 1.12	Revision Date: 09/02/2026	SDS Number: 100000003128	Date of last issue: 09/08/2025 Date of first issue: 07/08/2014
-----------------	------------------------------	-----------------------------	---

Freezing point (Melting point/freezing point)	: Estimated -85 - -84 °C (-121 - -119 °F)
Boiling point (Boiling point/boiling range)	: Estimated 116 - 117 °C (241 - 243 °F)
Flash point	: 14 °C (57 °F)
Evaporation rate	: 1.6 (Butyl Acetate = 1)
Flammability (solid, gas)	: No data available
Upper explosion limit	: 8 %(V)
Lower explosion limit	: 1.2 %(V)
Vapour pressure	: Estimated 15.0 mmHg @ 20 °C (68 °F)
Relative vapour density	: < 3.5 @ 20 - 25 °C (68 - 77 °F) (Air = 1.0)
Relative density	: 0.801 - 0.804 @ 20 - 25 °C (68 - 77 °F) Reference substance: (water = 1)
Density	: Estimated 0.799 - 0.802 g/cm ³ @ 20 - 25 °C (68 - 77 °F)
Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: Pow: Estimated 24 log Pow: 1.38 - 1.9
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: 0.585 mPa.s @ 20 °C (68 °F)
Viscosity, kinematic	: 0.73 mm ² /s @ 20 °C (68 °F)
Particle characteristics	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Keep away from heat, flame, sparks and other ignition sources. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Acids Aldehydes

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Methyl isobutyl ketone

Version	Revision Date:	SDS Number:	Date of last issue: 09/08/2025
1.12	09/02/2026	100000003128	Date of first issue: 07/08/2014

Hazardous decomposition products : Bases
halogens
Strong oxidizing agents
No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if inhaled.

Components:

108-10-1:

Acute inhalation toxicity : LC50 (Rat): 11.6 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

108-10-1:

Species : Rabbit
Result : Irritating to eyes.
Method : OECD Test Guideline 405
GLP : yes

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Components:

108-10-1:

Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Carcinogenicity

Suspected of causing cancer.

Components:

108-10-1:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Methyl isobutyl ketone

Version	Revision Date:	SDS Number:	Date of last issue: 09/08/2025
1.12	09/02/2026	100000003128	Date of first issue: 07/08/2014

Carcinogenicity - Assessment : Suspected human carcinogens

IARC Group 2B: Possibly carcinogenic to humans
108-10-1 Methyl isobutyl ketone

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified due to lack of data.

Components:

108-10-1:

Reproductive toxicity - Assessment : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

108-10-1:

Target Organs : Narcotic effects
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Methyl isobutyl ketone

Version	Revision Date:	SDS Number:	Date of last issue: 09/08/2025
1.12	09/02/2026	100000003128	Date of first issue: 07/08/2014

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Univar Solutions ChemCare: 1-800-637-7922

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1245
Proper shipping name : Methyl isobutyl ketone
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1245
Proper shipping name : METHYL ISOBUTYL KETONE
Class : 3
Packing group : II

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Methyl isobutyl ketone

Version	Revision Date:	SDS Number:	Date of last issue: 09/08/2025
1.12	09/02/2026	100000003128	Date of first issue: 07/08/2014

Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations

49 CFR Road

UN/ID/NA number : UN 1245
Proper shipping name : Methyl isobutyl ketone
Class : 3
Packing group : II
Labels : FLAMMABLE LIQUID
ERG Code : 127
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

CAS-No.	Components	Component RQ (lbs)	Calculated product RQ (lbs)
108-10-1	Methyl isobutyl ketone	5000	5000

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Acute toxicity (any route of exposure)
Carcinogenicity
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

108-10-1	Methyl isobutyl ketone	>= 90 - <= 100 %
----------	------------------------	------------------

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Methyl isobutyl ketone

Version	Revision Date:	SDS Number:	Date of last issue: 09/08/2025
1.12	09/02/2026	100000003128	Date of first issue: 07/08/2014

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

108-10-1	Methyl isobutyl ketone	>= 90 - <= 100 %
----------	------------------------	------------------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

108-10-1	Methyl isobutyl ketone	>= 90 - <= 100 %
----------	------------------------	------------------

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. Clean Water Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. Clean Water Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

108-10-1	Methyl isobutyl ketone
----------	------------------------

Pennsylvania Right To Know

108-10-1	Methyl isobutyl ketone
----------	------------------------

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

Product does not contain any listed chemicals

Washington Chemicals of High Concern

Product does not contain any listed chemicals

California Prop 65

⚠ WARNING: This product can expose you to chemicals including Methyl isobutyl ketone, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

108-10-1	Methyl isobutyl ketone
----------	------------------------

California Permissible Exposure Limits for Chemical Contaminants

108-10-1	Methyl isobutyl ketone
----------	------------------------

The components of this product are reported in the following inventories:

TSCA	: All substances listed as active on the TSCA inventory
AIIC	: On the inventory, or in compliance with the inventory
CA. DSL	: All components of this product are on the Canadian DSL
ENCS	: On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Methyl isobutyl ketone

Version	Revision Date:	SDS Number:	Date of last issue: 09/08/2025
1.12	09/02/2026	100000003128	Date of first issue: 07/08/2014

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

TSCA list


No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	*	2
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Methyl isobutyl ketone

Version	Revision Date:	SDS Number:	Date of last issue: 09/08/2025
1.12	09/02/2026	100000003128	Date of first issue: 07/08/2014

	its for Air Contaminants
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	: 8-hour time weighted average
OSHA P0 / STEL	: Short-term exposure limit
OSHA Z-1 / TWA	: 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 09/02/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Methyl isobutyl ketone

Version	Revision Date:	SDS Number:	Date of last issue: 09/08/2025
1.12	09/02/2026	100000003128	Date of first issue: 07/08/2014

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN