

Safety Data Sheet

KWIK DRI 66

Version 1.10

Revision Date: 10/08/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : KWIK DRI 66

Recommended use of the chemical and restrictions on use

Recommended use : Industrial chemical
Solvent

Manufacturer or supplier's details

Company : Univar Solutions USA
Address : 3075 Highland Pkwy Suite 200
Downers Grove, IL 60515
United States of America (USA)

Emergency telephone number:

Transport North America: CHEMTREC (1-800-424-9300)

CHEMTREC INTERNATIONAL Tel # 703-527-3887

Additional Information: : Responsible Party: Product Compliance Department
E-mail: SDSNA@univarsolutions.com
SDS Requests: 1-855-429-2661
Website: www.univarsolutions.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist or vapours.

Safety Data Sheet

KWIK DRI 66

Version 1.10

Revision Date: 10/08/2025

P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Chemical name	Weight percent
64742-47-8	Distillates (petroleum), hydrotreated light	90 - 100
111-84-2	Nonane	5 - 10

Actual concentration is withheld as a trade secret

Any Concentration shown as a range is due to batch variation.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.

Safety Data Sheet

KWIK DRI 66

Version 1.10

Revision Date: 10/08/2025

If swallowed	Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
	: Keep respiratory tract clear. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical Water spray
Unsuitable extinguishing media	: High volume water jet
Specific hazards during fire-fighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon oxides
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, ver-

Safety Data Sheet

KWIK DRI 66

Version 1.10

Revision Date: 10/08/2025

miculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
64742-47-8	Distillates (petroleum), hydrotreated light	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA	200 mg/m ³ (total hydrocarbon vapor)	ACGIH
		TWA (Mist)	5 mg/m ³	OSHA P0
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
		PEL (particulate)	5 mg/m ³	CAL PEL
111-84-2	Nonane	TWA	200 ppm	ACGIH
		TWA	200 ppm 1,050 mg/m ³	NIOSH REL
		TWA	200 ppm 1,050 mg/m ³	OSHA P0

Safety Data Sheet

KWIK DRI 66

Version 1.10

Revision Date: 10/08/2025

		PEL	200 ppm 1,050 mg/m ³	CAL PEL
--	--	-----	------------------------------------	---------

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : Clear, colorless

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Freezing Point (Melting point/range) : -58 - -49 °C (-72 - -56 °F)

Boiling Point (Boiling point/boiling range) : 149 - 185 °C (300 - 365 °F)

Flash point : 39.4 - 42.2 °C (102.9 - 108.0 °F)
Method: Tag closed cup

Evaporation rate : > 1
(Butyl Acetate = 1)

Flammability (solid, gas) : No data available

Upper explosion limit : 6 %(V)

Lower explosion limit : 0.8 %(V)

Vapour pressure : > 1 mmHg @ 20 °C (68 °F)

Safety Data Sheet**KWIK DRI 66**

Version 1.10

Revision Date: 10/08/2025

Relative vapour density	: < 4.8 @ 20 - 25 °C (68 - 77 °F) (Air = 1.0)
Relative density	: 0.76 - 0.78 @ 15.6 °C (60.1 °F) Reference substance: (water = 1)
Density	: Estimated 0.76 - 0.78 g/cm3
Solubility(ies)	
Water solubility	: slightly soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: 230 - 316 °C
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: 0.9 mm2/s @ 40 °C (104 °F)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Keep away from heat, flame, sparks and other ignition sources. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon oxides Sulphur oxides

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified due to lack of data.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Product:

Result: No skin irritation

Components:**64742-47-8:**

Result: Irritating to skin.

Safety Data Sheet

KWIK DRI 66

Version 1.10

Revision Date: 10/08/2025

111-84-2:

Species: Rabbit

Result: Irritating to skin.

Test substance: Information given is based on data obtained from similar substances.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Product:

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified due to lack of data.

Respiratory sensitisation: Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

64742-47-8:

Target Organs: Nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

111-84-2:

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Safety Data Sheet

KWIK DRI 66

Version 1.10

Revision Date: 10/08/2025

Components:

64742-47-8:

May be fatal if swallowed and enters airways.

111-84-2:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Acute aquatic toxicity- Assessment : Toxic to aquatic life.

Chronic aquatic toxicity- Assessment : Toxic to aquatic life with long lasting effects.

Components:

64742-47-8:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 25 mg/l
Exposure time: 96 h
Test Type: semi-static test

Toxicity to fish (Chronic toxicity) : NOEC: 0.098 mg/l

M-Factor (Chronic aquatic toxicity) : 1

Acute aquatic toxicity- Assessment : Toxic to aquatic life.

Chronic aquatic toxicity- Assessment : Toxic to aquatic life with long lasting effects.

111-84-2:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.2 mg/l
Exposure time: 48 h
Test Type: static test

M-Factor (Acute aquatic toxicity) : 1

Chronic aquatic toxicity- Assessment : Very toxic to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Safety Data Sheet
KWIK DRI 66

Version 1.10

Revision Date: 10/08/2025

Mobility in soil

No data available

Other adverse effects**Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Univar Solutions ChemCare: 1-800-637-7922

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION**DOT (Department of Transportation):**

NA1268, PETROLEUM DISTILLATES, N.O.S., CBL, III

IATA (International Air Transport Association):

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III

IMDG (International Maritime Dangerous Goods):

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III, Marine Pollutant (NONANE) , Flash Point:39.4 - 42.2 °C(102.9 - 108.0 °F)

Special Notes: : The flash point for this material is greater than 100 °F (38 °C) and may be re-classified as "Combustible liquid" in accordance with 49 CFR 173.150(f). Therefore, non-bulk containers (<450L or <119 gallon capacity) of this material may be shipped as non-regulated when transported solely by land, as long as the material is not a hazardous waste, a marine pollu-

Safety Data Sheet

KWIK DRI 66

Version 1.10

Revision Date: 10/08/2025

tant, or specifically listed as a hazardous substance.

SECTION 15. REGULATORY INFORMATION

WHMIS Classification : B3: Combustible Liquid
D2A: Very Toxic Material Causing Other Toxic Effects
D2B: Toxic Material Causing Other Toxic Effects

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
**Toluene	108-88-3	1000	*
**Cumene	98-82-8	5000	*
**Naphthalene	91-20-3	100	*
**Benzene	71-43-2	10	*
**Ethylbenzene	100-41-4	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Aspiration hazard
Specific target organ toxicity (single or repeated exposure)

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

108-88-3	**Toluene
91-20-3	**Naphthalene
71-43-2	**Benzene
100-41-4	**Ethylbenzene

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

108-88-3	**Toluene
91-20-3	**Naphthalene

Safety Data Sheet

KWIK DRI 66

Version 1.10

Revision Date: 10/08/2025

71-43-2 **Benzene
100-41-4 **Ethylbenzene

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307
This product does not contain any priority pollutants related to the U.S. Clean Water Act

Massachusetts Right To Know

64742-47-8 Distillates (petroleum), hydrotreated light
111-84-2 Nonane

Pennsylvania Right To Know

64742-47-8 Distillates (petroleum), hydrotreated light
111-84-2 Nonane
108-88-3 **Toluene

California Prop 65

 **WARNING:** This product can expose you to chemicals including Distillates (petroleum), hydrotreated light, **Cumene, **Naphthalene, **Benzene, **Ethylbenzene, which is/are known to the State of California to cause cancer, and **Toluene, **Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA	: On TSCA Inventory
AIIC	: On the inventory, or in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
ENCS	: not determined
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
NZIoC	: On the inventory, or in compliance with the inventory

Safety Data Sheet


KWIK DRI 66

Version 1.10

Revision Date: 10/08/2025

SECTION16. OTHER INFORMATION

NFPA:



HMIS III:

HEALTH	2*
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 =Extreme, * = Chronic

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Univar Solutions Product Compliance Department (1-855-429-2661) SDSNA@univarsolutions.com.

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Univar Solutions Product Compliance Department (1-855-429-2661) SDSNA@univarsolutions.com.

Revision Date : 10/08/2025

Legacy SDS: : R0013947

Material number:

16223766, 16215228, 16205205, 16153203, 16120048, 16108455, 508416, 70147, 554126, 102988, 102423, 102916, 53284, 54497, 54511, 573152, 554125, 554039, 53219, 680258, 658366, 613107, 613108, 129570, 85980, 20589, 16038136, 16036242, 16009106, 752733, 504395, 54510, 20588, 70234, 504394

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency

Safety Data Sheet

KWIK DRI 66

Version 1.10

Revision Date: 10/08/2025

NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		