

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MINERAL SPIRITS NE

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2026
1.8	07/01/2026	100000002569	Date of first issue: 11/11/2014

SECTION 1. IDENTIFICATION

Product Identifier : MINERAL SPIRITS NE
Product code : 000000000000086037
Synonyms : Solvent naphtha, petroleum, medium aliphatic; Stoddard Solvent; Low aromatic hydrocarbon solvents - medium flashpoint.

Manufacturer or supplier's details

Company : Univar Solutions USA
Address : 3250 Lacey Rd., Suite 600
Downers Grove, IL 60515
United States of America (USA)

Emergency telephone number:

Univar Solutions USA:-CHEMTREC INTERNATIONAL Tel # 703-527-3887

Additional Information: : Phone: 1-855-429-2661
Regulatory Information Number: 1-855-429-2661
Email: SDSNA@univarsolutions.com

Recommended use of the chemical and restrictions on use

Recommended use : Solvent
Reserved for industrial and professional use.
Restrictions on use : None known

SECTION 2. HAZARD IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Flammable liquids : Category 3
Eye irritation : Category 2B
Carcinogenicity : Category 2
Specific target organ toxicity : Category 3 (Central nervous system)
- single exposure
Specific target organ toxicity : Category 1 (Central nervous system)
- repeated exposure
Aspiration hazard : Category 1

Other hazards

None known.

Hazards associated with a change in physical form:

No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MINERAL SPIRITS NE

Version 1.8	Revision Date: 07/01/2026	SDS Number: 100000002569	Date of last issue: 06/19/2026 Date of first issue: 11/11/2014
----------------	------------------------------	-----------------------------	---

GHS label elements

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H320 Causes eye irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

: **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or al-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MINERAL SPIRITS NE

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2026
1.8	07/01/2026	100000002569	Date of first issue: 11/11/2014

cohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazards resulting from a reaction with other chemicals under normal conditions of use:

No data available

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Chemical name	Weight percent	Trade secret
8052-41-3 / 64742-88-7	Stoddard Solvent AND/OR Low Aro. Hyd Solvent, Medium Aliph. AND/OR Solvent naphtha (petroleum), medium aliph.	90 - 100	-
95-63-6	**1,2,4-trimethylbenzene	5 - 10	-
1330-20-7	**Mixed Xylenes	5 - 10	-
25551-13-7	**Benzene, trimethyl-	5 - 10	-
111-84-2	**Nonane	1 - 5	-
100-41-4	**Ethylbenzene	0.1 - 1	-
91-20-3	**Naphthalene	0.1 - 1	-
98-82-8	**Cumene	0.1 - 1	-

Actual concentration is withheld as a trade secret

Any concentration shown as a range is due to batch variation.

Synonyms

: Solvent naphtha, petroleum, medium aliphatic; Stoddard Solvent; Low aromatic hydrocarbon solvents - medium flashpoint.

SECTION 4. FIRST-AID MEASURES

General advice : Move out of dangerous area.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MINERAL SPIRITS NE

Version 1.8	Revision Date: 07/01/2026	SDS Number: 100000002569	Date of last issue: 06/19/2026 Date of first issue: 11/11/2014
----------------	------------------------------	-----------------------------	---

		Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.
If inhaled	:	Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	:	If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	:	Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	:	May be fatal if swallowed and enters airways. Causes eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure.
Immediate Medical Attention and Special Treatment	:	Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Use dry chemical, Carbon dioxide (CO ₂), water spray (fog) or foam.
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire-fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	No hazardous combustion products are known
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment and precautions for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MINERAL SPIRITS NE

Version 1.8	Revision Date: 07/01/2026	SDS Number: 100000002569	Date of last issue: 06/19/2026 Date of first issue: 11/11/2014
----------------	------------------------------	-----------------------------	---

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Keep away from open flames, hot surfaces and sources of ignition.
- Precautions for safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MINERAL SPIRITS NE

Version
1.8

Revision Date:
07/01/2026

SDS Number:
100000002569

Date of last issue: 06/19/2026
Date of first issue: 11/11/2014

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
95-63-6	**1,2,4-trimethylbenzene	TWA	10 ppm	ACGIH
		TWA	25 ppm 125 mg/m3	NIOSH REL
		TWA	25 ppm 125 mg/m3	OSHA P0
1330-20-7	**Mixed Xylenes	TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	150 ppm 655 mg/m3	OSHA P0
25551-13-7	**Benzene, trimethyl-	TWA	10 ppm	ACGIH
		TWA	25 ppm 125 mg/m3	OSHA P0
111-84-2	**Nonane	TWA	200 ppm	ACGIH
		TWA	200 ppm 1,050 mg/m3	NIOSH REL
		TWA	200 ppm 1,050 mg/m3	OSHA P0
100-41-4	**Ethylbenzene	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0
91-20-3	**Naphthalene	TWA	10 ppm	ACGIH
		TWA	10 ppm 50 mg/m3	NIOSH REL
		ST	15 ppm 75 mg/m3	NIOSH REL
		TWA	10 ppm 50 mg/m3	OSHA Z-1
		STEL	15 ppm 75 mg/m3	OSHA P0
		TWA	10 ppm 50 mg/m3	OSHA P0
98-82-8	**Cumene	TWA	5 ppm	ACGIH
		TWA	50 ppm	NIOSH REL

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MINERAL SPIRITS NE

Version 1.8 Revision Date: 07/01/2026 SDS Number: 100000002569 Date of last issue: 06/19/2026
Date of first issue: 11/11/2014

			245 mg/m3	
		TWA	50 ppm 245 mg/m3	OSHA Z-1
		TWA	50 ppm 245 mg/m3	OSHA P0

Engineering measures : Ensure adequate ventilation, especially in confined areas.
Use appropriate engineering controls and manufacturing technologies to control airborne concentrations (e.g., drip-less quick connections).
Use only in an area equipped with explosion proof exhaust ventilation.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State : liquid
Colour : Clear, colorless
Odour : hydrocarbon-like
Odour Threshold : No data available
pH : No data available

Freezing point : No data available
Boiling point (Boiling point/boiling range) : 150 - 218 °C (302 - 424 °F)
Flash point : 39 - 42 °C (102 - 108 °F)
Method: Closed Cup

Evaporation rate : 0.14 - 0.2
(Butyl Acetate = 1)
Flammability (solid, gas) : No data available
Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 0.22 - 0.62 mmHg @ 20 °C (68 °F)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MINERAL SPIRITS NE

Version 1.8	Revision Date: 07/01/2026	SDS Number: 100000002569	Date of last issue: 06/19/2026 Date of first issue: 11/11/2014
----------------	------------------------------	-----------------------------	---

Relative vapour density	: 4.9
Relative density	: 0.77 - 0.80 @ 20 °C (68 °F) Reference substance: (water = 1)
Density	: 0.76 - 0.79 g/cm3
Solubility(ies)	
Water solubility	: 0.05 g/l negligible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: < 20 mm2/s @ 40 °C (104 °F)
Particle characteristics	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Reducing agents Strong bases Strong oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Skin corrosion/irritation

Not classified due to lack of data.

Components:

8052-41-3 / 64742-88-7:

Result : No skin irritation

Serious eye damage/eye irritation

Causes eye irritation.

Components:

8052-41-3 / 64742-88-7:

Result : Mild eye irritation

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MINERAL SPIRITS NE

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2026
1.8	07/01/2026	100000002569	Date of first issue: 11/11/2014

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Components:

8052-41-3 / 64742-88-7:

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity

Suspected of causing cancer.

Components:

8052-41-3 / 64742-88-7:

Carcinogenicity - Assessment : Suspected human carcinogens

IARC	Group 2B: Possibly carcinogenic to humans	
	100-41-4	**Ethylbenzene
	Group 2B: Possibly carcinogenic to humans	
	91-20-3	**Naphthalene
	Group 2B: Possibly carcinogenic to humans	
	98-82-8	**Cumene

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP	Reasonably anticipated to be a human carcinogen	
	91-20-3	**Naphthalene
	Reasonably anticipated to be a human carcinogen	
	98-82-8	**Cumene

Reproductive toxicity

Not classified due to lack of data.

Components:

8052-41-3 / 64742-88-7:

Reproductive toxicity - Assessment : Fertility classification not possible from current data.
Embryotoxicity classification not possible from current data.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

8052-41-3 / 64742-88-7:

Assessment : The substance or mixture is classified as specific target organ

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MINERAL SPIRITS NE

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2026
1.8	07/01/2026	100000002569	Date of first issue: 11/11/2014

toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Components:

8052-41-3 / 64742-88-7:

Target Organs	:	Central nervous system
Assessment	:	The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Repeated dose toxicity

Components:

8052-41-3 / 64742-88-7:

Species	:	Mouse, male and female
LOAEL	:	138 mg/m ³
Application Route	:	Inhalation
Exposure time	:	14 wks
Number of exposures	:	6 h/d, 5 d/wk
Dose	:	138, 275, 550, 1100, 2200mg/m ³
Control Group	:	yes
Symptoms	:	Spleen effects

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

8052-41-3 / 64742-88-7:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks	:	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.
---------	---	---

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

8052-41-3 / 64742-88-7:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MINERAL SPIRITS NE

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2026
1.8	07/01/2026	100000002569	Date of first issue: 11/11/2014

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

Components:

95-63-6:

Partition coefficient: n-octanol/water : Remarks: No data available

1330-20-7:

Partition coefficient: n-octanol/water : log Pow: 2.77 - 3.15

91-20-3:

Partition coefficient: n-octanol/water : log Pow: 3.4 (77 °F / 25 °C)
pH: 7 - 7.5

98-82-8:

Partition coefficient: n-octanol/water : log Pow: 3.55 (73 °F / 23 °C)

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Univar Solutions ChemCare: 1-800-637-7922

Contaminated packaging : Empty remaining contents.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MINERAL SPIRITS NE

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2026
1.8	07/01/2026	100000002569	Date of first issue: 11/11/2014

Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No.	: UN 1268
Proper shipping name	: PETROLEUM DISTILLATES, N.O.S.
Class	: 3
Packing group	: III
Labels	: Flammable Liquids
Packing instruction (cargo aircraft)	: 366
Packing instruction (passenger aircraft)	: 355

IMDG-Code

UN number	: UN 1268
Proper shipping name	: PETROLEUM DISTILLATES, N.O.S. (Nonane)
Class	: 3
Packing group	: III
Labels	: 3
EmS Code	: F-E, S-E
Marine pollutant	: yes

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations

49 CFR Road

UN/ID/NA number	: UN 1268
Proper shipping name	: PETROLEUM DISTILLATES, N.O.S.
Class	: 3
Packing group	: III
Labels	: FLAMMABLE LIQUID
ERG Code	: 128
Marine pollutant	: no

Special Notes: : This product may be re-classified as "Combustible Liquid", unless transported by vessel or aircraft. Non-bulk packages (less than or equal to 119 gal) of combustible liquids, that are marine pollutants, are not regulated as hazardous materials in package sizes less than the product reportable quantity, unless transported by vessel.

This product is not regulated as a marine pollutant when transported on inland waterways in sizes of ≤5 L or ≤5 kg or by road, rail, or inland air in non-bulk sizes, provided the packagings meet the general provisions of §§ 173.24 and 173.24a.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MINERAL SPIRITS NE

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2026
1.8	07/01/2026	100000002569	Date of first issue: 11/11/2014

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

CAS-No.	Components	Component RQ (lbs)	Calculated product RQ (lbs)
1330-20-7	**Mixed Xylenes	100	2000
91-20-3	**Naphthalene	100	20000

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard
Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

95-63-6	**1,2,4-trime-thylbenzene	>= 5 - < 10 %
1330-20-7	**Mixed Xylenes	>= 5 - < 10 %
100-41-4	**Ethylbenzene	>= 0.1 - < 1 %
91-20-3	**Naphthalene	>= 0.1 - < 1 %
98-82-8	**Cumene	>= 0.1 - < 1 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

1330-20-7	**Mixed Xylenes	>= 5 - < 10 %
-----------	-----------------	---------------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489):

1330-20-7	**Mixed Xylenes	>= 5 - < 10 %
-----------	-----------------	---------------

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MINERAL SPIRITS NE

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2026
1.8	07/01/2026	100000002569	Date of first issue: 11/11/2014

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

1330-20-7	**Mixed Xylenes	>= 5 - < 10 %
100-41-4	**Ethylbenzene	>= 0.1 - < 1 %
91-20-3	**Naphthalene	>= 0.1 - < 1 %
108-88-3	**Toluene	>= 0.1 - < 1 %
71-43-2	**Benzene	>= 0 - < 0.1 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

1330-20-7	**Mixed Xylenes	>= 5 - < 10 %
100-41-4	**Ethylbenzene	>= 0.1 - < 1 %
91-20-3	**Naphthalene	>= 0.1 - < 1 %
108-88-3	**Toluene	>= 0.1 - < 1 %
71-43-2	**Benzene	>= 0 - < 0.1 %

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

95-63-6	**1,2,4-trimethylbenzene
1330-20-7	**Mixed Xylenes
25551-13-7	**Benzene, trimethyl-
111-84-2	**Nonane
71-43-2	**Benzene

Pennsylvania Right To Know

	Stoddard Solvent AND/OR Low Aro. Hyd Solvent, Medium Aliph. AND/OR Solvent naphtha (petroleum), medium aliph.
95-63-6	**1,2,4-trimethylbenzene
1330-20-7	**Mixed Xylenes
25551-13-7	**Benzene, trimethyl-
111-84-2	**Nonane
100-41-4	**Ethylbenzene
91-20-3	**Naphthalene
98-82-8	**Cumene
108-88-3	**Toluene

Maine Chemicals of High Concern

108-88-3	**Toluene
71-43-2	**Benzene

Vermont Chemicals of High Concern

100-41-4	**Ethylbenzene
108-88-3	**Toluene
71-43-2	**Benzene

Washington Chemicals of High Concern

100-41-4	**Ethylbenzene
108-88-3	**Toluene

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MINERAL SPIRITS NE

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2026
1.8	07/01/2026	100000002569	Date of first issue: 11/11/2014

71-43-2

**Benzene

California Prop 65

⚠ WARNING: This product can expose you to chemicals including **Ethylbenzene, **Naphthalene, **Cumene, **Benzene, which is/are known to the State of California to cause cancer, and **Toluene, **n-Hexane, **Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

95-63-6	**1,2,4-trimethylbenzene
1330-20-7	**Mixed Xylenes
25551-13-7	**Benzene, trimethyl-
111-84-2	**Nonane

California Permissible Exposure Limits for Chemical Contaminants

95-63-6	**1,2,4-trimethylbenzene
1330-20-7	**Mixed Xylenes
25551-13-7	**Benzene, trimethyl-
111-84-2	**Nonane

The components of this product are reported in the following inventories:

TSCA	: All substances listed as active on the TSCA inventory
AIIC	: All components are listed on the inventory, regulatory obligations/restrictions apply
CA. DSL	: All components of this product are on the Canadian DSL
ENCS	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
NZIoC	: not determined

TSCA list

No substances are subject to a Significant New Use Rule.

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:
111-84-2 **Nonane

Special Notes: : ** Other substances in the product which may present a health or environmental hazard.

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MINERAL SPIRITS NE


Version
1.8

Revision Date:
07/01/2026

SDS Number:
100000002569

Date of last issue: 06/19/2026
Date of first issue: 11/11/2014

NFPA 704:



HMIS® IV:

HEALTH	*	3
FLAMMABILITY		2
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population;

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MINERAL SPIRITS NE

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2026
1.8	07/01/2026	100000002569	Date of first issue: 11/11/2014

LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Univar Solutions Product Compliance Department (1-855-429-2661) SDSNA@univarsolutions.com.

Revision Date : 07/01/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN